

TDK-Lambda**DRB15-100 Series****15-100W, 5-48V Output DIN Rail Mount Power Supplies****Features**

- ◆ Compact Size
- ◆ High Efficiency (Up to 91%)
- ◆ ErP Compliant Design
- ◆ Low No Load Power Draw
- ◆ Class 2 Models to UL1310
- ◆ Class 1 Div 2 for Hazardous Locations

**Key Market Segments & Applications**

Specifications		DRB15	DRB30	DRB50	DRB100
Input Voltage range	V	85 - 264VAC, 120 - 373VDC* (Withstands 300VAC for 5 seconds)			
Input Frequency	Hz	47 - 63Hz			
Inrush Current (typ) (Cold Start)	A	35A	40A	50A	40A
Power Factor (110/230VAC) Meets EN61000-3-2	-	0.55 / 0.42	0.56 / 0.46	0.6 / 0.5	0.98 / 0.93
Input Current (110/230VAC)	A	0.27 / 0.17	0.55 / 0.33	0.9 / 0.55	1.2 / 0.6
Line & Load Regulation	-	See model selector			
Ripple & Noise	-	See model selector			
Overcurrent Protection	-	Hiccup with auto recovery			
Overvoltage Protection	-	See model selector. Cycle AC input voltage to reset			
Hold Up Time (230VAC input)	ms	> 20ms			
Efficiency	-	See model selector			
No Load Power Draw	W	<0.3W	<0.3W	<0.3W	<0.5W
LED Indicator	-	Green LED indicates DC is OK			
Operating Temperature (1)	°C	-20 to +70°C. (DRB30-100, derate linearly to 50% load from 55 to 70°C)			
Storage Temperature	-	-40 to +85°C			
Operating Humidity (non condensing)	%RH	5 - 95%RH			
Parallel Operation	-	Not available			
Series Operation	-	Possible			
Cooling	-	Convection			
Withstand Voltage (For 1 minute)	VAC	Input to Output 3kVAC, Input to GND 1.5kVAC, Output to GND 500VAC			
Isolation Resistance	MΩ	>100MΩ at 25°C, 70%RH & 500VDC			
Vibration (Non operating)	-	10-55Hz (sweep for 1 min); 19.6m/s ² (2G) Constant; X,Y,Z each 1 hour			
Shock	-	294m/s (30G) 11ms half sine			
Safety Agency Certifications	-	UL508 Listed, IEC/UL/CSA/EN62368-1, IEC/UL/CSA/EN60950-1, CE Mark, UL1310 Class 2 (2), Class 1 Div 2, Group A, B, C, D (ISA 12.12.01)			
Conducted & Radiated EMI	-	EN55032-B Radiated & Conducted			
Immunity	-	EN61000-4-2 (lvl 4), -3 (lvl 3), -4 (lvl 4) -5 (norm mode lvl 3, com mode lvl 4), -6 (lvl 3), -8 (lvl 4), -11 (class 3)			
Line Dips	-	SEMI-F47 (200VAC input)			
Weight (Typ)	g	85	95	175	300
Size (WxHxD)	in	0.71 x 2.95 x 3.54	0.83 x 2.95 x 3.54	1.18 x 2.95 x 3.54	1.77 x 2.95 x 3.94
Mounts on TS-35/7.5 or -35/15 rail	mm	18 x 75 x 90	21 x 75 x 90	30 x 75 x 90	45 x 75 x 100
Case material	-	Flame Retardant Polycarbonate (UL94 V-0)			
Warranty	yrs	Three years			

(1) For operation below -10°C, start up load is derated linearly to 50% load down to -20°C


(2) NEC Class 2 in accordance with UL1310. Excludes DRB50-5-1 and DRB100-24-1 models

* Safety certified for AC input only


Model	Output Voltage	Adjust Range	Max Current	Max Power	Load Reg	Line Reg	Ripple & Noise	Overvoltage Protection	Efficiency (%) (115/230VAC)
DRB50-5-1	5V	5 - 5.5V	6.0A	30W	50mV	50mV	30mV	5.75 - 6.75V	79 / 80
DRB30-12-1	12V	12 - 15V	2.5A	30W	150mV	150mV	40mV	15.96 - 18.72V	86 / 88
DRB50-12-1	12V	12 - 15V	3.4A	51W(3)	150mV	150mV	20mV	15.96 - 18.72V	88 / 90
DRB50-15-1	15V	12 - 15V	3.4A	51W(3)	150mV	150mV	20mV	15.96 - 18.72V	88 / 90
DRB15-24-1	24V	24 - 28V	0.63A	15.1W	240mV	240mV	20mV	30 - 33.6V	87 / 90
DRB30-24-1	24V	24 - 28V	1.25A	30W	240mV	240mV	30mV	30 - 33.6V	88 / 90
DRB50-24-1	24V	24 - 28V	2.1A	50.4W	240mV	240mV	30mV	30 - 33.6V	88 / 90
DRB100-24-1	24V	24 - 28V	4.2A	100.8W	240mV	240mV	30mV	30 - 33.6V	90 / 91
DRB50-48-1	48V	48 - 52.8V	1.05A	50.4W	480mV	480mV	40mV	53.76 - 68.16V	90 / 91

(3) With output set at 15V. 40.8W maximum power when output is set at 12V.

Outline DRB15



Outline DRB100



For additional information, please visit <https://product.tdk.com/en/power/>





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk