



TECHNICAL INFORMATION SHEET

IP44 JUNCTION BOXES WITH CABLE HOLDER INLETS



PRODUCT TYPE:

Wall-mounted junction boxes

APPLICATIONS:

Outdoor wall installations

DIMENSIONS:

Product Name

Dimensions mm (LxHxD)

IP44 01 GRI	Ø 65x35
IP44 02 GRI	Ø 80x40
IP44 03 GRI	80x80x40

COLOUR RANGE:

Grey RAL 7035

MATERIAL:

ABS (Halogen Free)

DECLARATION OF CONFORMITY:

All Pico range products come under the scope of the Low Voltage Directive 2014/35/UE and comply with all relevant essential requirements set in the Directive.

Compliance with the Directive is indicated by the **CE** marking and by all required symbols and markings affixed on the product, its packaging, in the assembly instructions and product catalogue, as well as by full product compliance with applicable standards.

NORMATIVE REFERENCES:

- **EN 60670-1:** "Boxes and enclosures for electrical accessories for household and similar fixed electrical installations - Part 1: General requirements"
- **EN 60670-22:** "Boxes and enclosures for electrical accessories for household and similar fixed electrical installations Part 22 : Particular requirements for connecting boxes and enclosures".

Degree of protection provided by Enclosures as per EN 60529 standard "Degrees of protection provided by enclosures (IP Code)": IP44

Resistance to impact as per EN 62262 Standard "Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK Code)": IK07 (2 Joules)



Resistance to hot-wire based test as per EN 60695-2-11 Standard "Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products": passed the 650 °C test

Electric insulation (EN 61439-1): products feature full insulation components for protection against indirect contact (Class II). However, in order to ensure protection, they must be correctly installed according to the instructions provided by the manufacturer and using the appropriate accessories (e.g. screw caps, clamps).

MINIMUM INSTALLATION AND SERVICE TEMPERATURE:

-25 °C

MAXIMUM SERVICE TEMPERATURE:

+60 °C

RATED INSULATION VOLTAGE:

750 V

RESISTANCE TO CHEMICAL AGENTS:

	Saline	Acids		Bases		Solvents				Mineral Oil
		Concentrated	Thinned	Concentrated	Thinned	Hexane	Benzoic acid	Acetone	Ethyl-alcohol	
	Resistant	Unsuitable	Resistant	Resistant	Resistant	Resistant in certain conditions	Unsuitable	Unsuitable	Resistant in certain conditions	Resistant in certain conditions

UV RESISTANCE:

yes

OTHER FEATURES:

Press-on lid

MARKINGS AND CERTIFICATIONS:



CONFORMITY WITH 2011/65/CE (ROHS) DIRECTIVE:

yes





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk