




# SOLENOID VALVES

ISO 15218 (CNOMO, size 30) interface  
direct operated, pad mounting body  
subbases for instant fittings or 1/8 thread

NC



**3/2**  
Series  
**190**

## FEATURES

- CNOMO pad-mount version for valve piloting applications
- Compact size and low weight for easy installation on single or joinable subbases
- AC/DC interchangeability of the solenoid operator without any need for disassembly of the valve
- Version with M12 connection with visual indication and peak voltage suppression conforming to "UL" standards
- Flexible installation on joinable subbases
- Manual operator as standard
- The solenoid valves satisfy all relevant EU directives

## GENERAL

**Differential pressure** See "SPECIFICATIONS" [1 bar = 100 kPa]  
**Maximum allowable pressure** 16 bar  
**Response time** 5 ms

| fluids (*)     | temperature range (TS) | seal materials (*) |
|----------------|------------------------|--------------------|
| air, inert gas | - 10°C to + 60°C       | NBR (nitrile)      |

## MATERIALS IN CONTACT WITH FLUID

(\*) Ensure that the compatibility of the fluids in contact with the materials is verified

|                         |                  |
|-------------------------|------------------|
| Body                    | PA, glass-filled |
| Core tube               | Stainless steel  |
| Core and plugnut        | Stainless steel  |
| Internal parts, springs | Stainless steel  |
| Seals                   | NBR              |
| Shading coil            | Copper           |

## CONSTRUCTION

**Mounting pad** ISO 15218 (CNOMO 06-05-80 / NF E 49066, size 30)

## ELECTRICAL CHARACTERISTICS

**Coil insulation class** F  
**Connector** Spade plug (cable Ø 6-10 mm) or M12  
 ISO 4400 / EN 175301-803, form A  
 or CNOMO E03.62.520.N (M12)

**Connector specification**

## Electrical safety

**Electrical enclosure protection** IEC 335

**Standard voltages** Moulded IP65 (EN 60529)

(Other voltages and 60 Hz on request)

DC (=): 24V - 48V (M12: 24V + LED and protection)  
 AC (~): 24V - 48V - 115V - 230V / 50 Hz

| - | power ratings |              |               |       | operator<br>ambient<br>temperature<br>range (TS)<br>(C°) | replacement coil |          | type <sup>(1)</sup> |
|---|---------------|--------------|---------------|-------|----------------------------------------------------------|------------------|----------|---------------------|
|   | inrush<br>~   | holding<br>~ | hot/cold<br>= |       |                                                          | ~                | =        |                     |
|   | (VA)          | (VA)         | (W)           | (W)   |                                                          | 230 V/50 Hz      | 24 V DC  |                     |
| - | 9             | 4            | 3             | 3 / 3 | -10 to + 60                                              | 43004472         | 43004473 | 01                  |
| - |               |              |               |       |                                                          | -                | 43005525 | 06                  |

<sup>(1)</sup> Refer to the dimensional drawings on the following page.

## SPECIFICATIONS

| pipe<br>size                   | orifice<br>size |               | flow<br>at 6 bar<br>l/min (ANR) |       | flow<br>coefficient<br>Kv |                  | operating pressure<br>differential (bar) |           |    | power coil<br>(W) |   | without<br>man. operator | maintained<br>man. operator | impulse<br>man. operator | button<br>man. operator | catalogue number  |                      |                   |
|--------------------------------|-----------------|---------------|---------------------------------|-------|---------------------------|------------------|------------------------------------------|-----------|----|-------------------|---|--------------------------|-----------------------------|--------------------------|-------------------------|-------------------|----------------------|-------------------|
|                                | 1 → 2<br>(mm)   | 2 → 3<br>(mm) | 1 → 2                           | 2 → 3 | 1 → 2<br>(l/min)          | 2 → 3<br>(l/min) | min.                                     | max. (PS) |    | ~                 | = |                          |                             |                          |                         | with<br>connector | without<br>connector | M12<br>connection |
|                                |                 |               |                                 |       |                           |                  |                                          | air (*)   |    |                   |   |                          |                             |                          |                         |                   |                      |                   |
|                                |                 |               |                                 |       |                           |                  |                                          | ~         | =  |                   |   |                          |                             |                          |                         |                   |                      |                   |
| NC - Normally closed           |                 |               |                                 |       |                           |                  |                                          |           |    |                   |   |                          |                             |                          |                         |                   |                      |                   |
| pad<br>mounting <sup>(2)</sup> | 1,6             | 1,5           | 70                              | 84    | 1                         | 1,2              | 0                                        | 10        | 10 | 3                 | 3 | ×                        |                             |                          |                         | 19000005          | 19000013             | 19000043          |
|                                |                 |               |                                 |       |                           |                  |                                          |           |    |                   |   |                          | ●                           |                          |                         | 19000006          | 19000014             | 19000044          |
|                                |                 |               |                                 |       |                           |                  |                                          |           |    |                   |   |                          |                             | ▼                        |                         | 19000017          | 19000018             | 19000046          |
|                                |                 |               |                                 |       |                           |                  |                                          |           |    |                   |   |                          |                             |                          | ■                       | 19000008          | 19000016             | 19000045          |

## SUBBASES

| pipe<br>size                       | designation                                                                                                                | composition | catalogue number        |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-------------|-------------------------|
| <b>6/6 polyamide subbases</b>      |                                                                                                                            |             |                         |
| instant<br>fittings <sup>(3)</sup> | single subbase (instant fittings OD 4 mm)                                                                                  |             | 35300069                |
|                                    | joinable subbase (instant fittings OD 4 mm)                                                                                |             | 35300070                |
|                                    | set of 2 joinable end subbases,<br>right-hand pressure intake,<br>endpieces with instant fittings OD 6 mm                  |             | 35300071                |
|                                    | set of 2 joinable end subbases,<br>right-hand and/or left-hand pressure intake,<br>endpieces with instant fittings OD 6 mm |             | 35300072 <sup>(4)</sup> |
| <b>Zamak subbases</b>              |                                                                                                                            |             |                         |
| G 1/8 <sup>(3)</sup><br>tapped     | laterally-connected single subbase                                                                                         |             | 35300047                |
|                                    | laterally-connected joinable subbase                                                                                       |             | 35300048                |

<sup>(2)</sup> Port 3: M5.

<sup>(3)</sup> These subbases can be mounted on omega rail to EN 50022 using 2 clips (clips sold in packs of 10, catalogue number: 33400036).

<sup>(4)</sup> The equipment can be used for two different pressure intakes, supplied with one blanking plug to cover unused port.

All leaflets are available on: [www.asco.com](http://www.asco.com)

Solenoid valves (3/2) - 29


### OPTIONS

- Explosionproof enclosures for use in zones 1/21-2/22, categories 2-3 to ATEX Directive 2014/34/EU (see "Explosionproof solenoids" section): Ex mb (PV), **PV19000005/6/17/8** / Potentially explosive atmospheres (SG), zone 22
- Straight M12 connector (IP67 protection with connector correctly installed): with 5 m cable: catalogue number **88130212**
- Right-angle M12 connector (IP67 protection with connector correctly installed), with 5 m cable: catalogue number **88130213**
- Catalogue number (without connector) + connector catalogue number (with integrated LED indicator and electrical protection): 24 V (~/-), **88122603** - 48 V (~/-), **88122604** - 115 V (~), **88122605** - 230 V (~), **88122608**
- M5 flow control regulator to fit port 3, catalogue number: **34600380**
- Plug with visual indication and peak voltage suppression or with cable length of 2 m (see Solenoids, Coils & Accessories section)

### INSTALLATION



- The solenoid valves can be mounted in any position without affecting operation
- Mounting on single or joinable subbases
- ATEX 2014/34/EU versions (options "SG" and "PV") can be installed on single (all versions) or joinable zinc diecast subbases
- Pipe connections 1/8 have standard thread according to ISO 228/1
- Installation/maintenance instructions are included with each valve

### DIMENSIONS (mm), WEIGHT (kg)




**TYPE 01-06**  
Spade plug /M12  
IEC 335 /  
EN 175301-803 (11 mm)  
E03.62.520.N, IP65

19000005 to 19000045



**TYPE 02**  
Single instant fitting  
subbase  
Polyamide


35300069





### ORDERING EXAMPLES:

|              |                 |
|--------------|-----------------|
| 19000006     | 230V / 50 Hz    |
| 19000044     | 24V / DC        |
| basic number | voltage options |



- Manual operator location
- Port 3: M5, depth 5,5 mm
- Mounting: two CM4 x 33,5 screws
- Instant-fitting connection for OD 4 mm tube
- Mounting: two dia. 3,5 mm securing holes, dia. 6,5 mm counter-bores, depth 3,5 mm
- Instant-fitting connection for OD 6 mm tube
- Mounting: two dia. 4,5 mm securing holes
- Adaptable clips
- Subbase mounting hole, adapter




**TYPE 03**  
Joinable instant fitting subbase  
Polyamide  
**35300070**  
**35300071** (set of 2)




**TYPE 04**  
Single subbase  
Zamak  
**35300047**



**TYPE 05**  
Joinable subbase  
Zamak  
**35300048**



Joinable subbases assembled with adapter locked by sunk set screws.  
For DIN rail mounting: see type 03.




Right-hand pressure intake option or 2 different pressure intakes by procuring the set of two end subbases with endpieces (catalogue number: 35300072).  
When mounted on DIN rail, it is recommended to use a securing clip on the end subbases as well as on the central subbase.

| type | weight <sup>(1)</sup> |
|------|-----------------------|
| 01   | 0,180                 |
| 02   | 0,135                 |
| 04   | 0,185                 |
| 06   | 0,170                 |

<sup>(1)</sup> including coil and connector.  
(except M12 connection type 06)

| number of subbases | type 03 |     | type 05 |     |
|--------------------|---------|-----|---------|-----|
|                    | A       | B   | A       | B   |
| 2                  | 88      | 72  | 62      | 52  |
| 3                  | 119     | 103 | 93      | 83  |
| 4                  | 150     | 134 | 124     | 114 |
| 5                  | 181     | 165 | 155     | 145 |
| 6                  | 212     | 196 | 186     | 176 |
| 7                  | 243     | 227 | 217     | 207 |
| 8                  | 274     | 258 | 248     | 238 |



| type  | weight <sup>(2)</sup> |       |       |       |       |       |       |
|-------|-----------------------|-------|-------|-------|-------|-------|-------|
|       | number of subbases    |       |       |       |       |       |       |
|       | 2                     | 3     | 4     | 5     | 6     | 7     | 8     |
| 03+01 | 0,415                 | 0,610 | 0,805 | 1,000 | 1,195 | 1,390 | 1,585 |
| 03+06 | 0,395                 | 0,580 | 0,765 | 0,950 | 1,135 | 1,320 | 1,505 |
| 05+01 | 0,490                 | 0,735 | 0,980 | 1,225 | 1,470 | 1,715 | 1,960 |
| 05+06 | 0,470                 | 0,705 | 0,940 | 1,175 | 1,410 | 1,645 | 1,880 |

<sup>(2)</sup> Including seals, set screws and joining unit.

All leaflets are available on: [www.asco.com](http://www.asco.com)



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)