




MANUALLY AND MECHANICALLY OPERATED VALVES

Product Index




ports/positions	Function		pipe connections				max. pressure (bar)	flow at 6 bar l/min (ANR)	type of operator		technology		Type	Illustration	Series	Page
	NC	NO	 - instant fittings O.D. (mm)  - internal thread ØG						button / lever	pedal	poppet	spool				
				1/8	1/4	ØG 3/8										
Manually operated valves																
3/2	●	●					8	112	●		●		micro-valve		307	1
	●						10	280	●		●	●			310	5
3/2	●	●					10	200	●			●	mini spool valve		550	7
5/2																
3/2	●	●					10	860	●	●		●	spool valve		551	09
5/2							10	860-1610	●	●		●			551 552	11
5/3							10	760-1610	●			●			551 552	13
5/2							10	655		●		●			ZF2F	15

ports/ positions	Function		pipe connections			max. pressure (bar)	flow at 6 bar l/min (ANR)	technology		Type	Illustration	Series	Page		
	NC	NO	 - instant fittings O.D. (mm)	 - internal thread ØG	4			1/8	1/4					poppet	spool
Mechanically operated valves															
3/2	●					8	140	●	●	micro-valve		309	17		
3/2	●					8	140	●		micro-valve		308	19		
3/2	●					10	280	●	●	micro-valve		310	21		
3/2	●	●				10	200		●	mini spool valve		550	23		
5/2															
3/2	●					10	860		●	spool valve		551	25		
5/2															
3/2	●	●				10	406		●	micro-valve		320	27		
Two-hand pneumatic safety start units and blocks															
												336			
Sensors															
Sensors with or without mechanical contact												333	 See "Pneumatic Automation"		
Falling pressure sensors															

MANUALLY OPERATED PILOT VALVE


for panel mounting Ø 22
instant fittings for Ø 4 mm O.D. tube or G 1/8



3/2
Series
307

FEATURES

- Microvalve composed of an operating head, an adaptor, an intermediary subbase and one or two pneumatic modules.
- Modules allowing the following combination of functions:



- Adaption of metal or plastic buttons designed to meet the highest quality standards.
- Secure and robust fastening of the button on the microvalve.

GENERAL

Fluid	Air filtered, lubricated or no
Ports	Instant fittings Ø 4 O.D. or G 1/8
Operating pressure	0 to 8 bar
Ambient temperature	-5°C to +60°C
Operators	Manual
Flow (Qv at 6 bar)	112 l/min (ANR)
Nominal diameter	2 mm

CONSTRUCTION

Popet valve construction	Internal parts in stainless steel and elastomer
Body diecast	Exhaust port not tapped

SPECIFICATIONS - METAL operating head and adaptor



pilot valve			operating head	adaptator		intermediary subbase + pneumatic(s) module(s)												
 or  =  +  +  or 																		
designa tion	type	color	cat. number	cat. number		connect.	cat. number		cat. number									
	flush push button	black	88130757	88130754	+													
		green	88130758															
		red	88130759															
	push-turn	red	88130770			Ø 4 mm O.D.	NC	30701009	NC+NC		30701011							
		push-pull	red										88130752					
	impulse	red	88130762				NO	30701010	NC+NO		30701012							
		black	88130763															
		black	88130772															
	switch button	2 positions fixed	black			88130771	G1/8	NC	30701013	NC+NC		30701015						
	key removal at 0 and 1	black	88130761			NO								30701014	NC+NO		30701016	
		black	88130772															
	lever switch button	2 positions fixed				black	88130760											
		3 positions fixed				black	88130767											
		3 positions self centring				black	88130766											

*These components are not security mechanism

Order example :

1 pilot valve, instant fittings ports, with impulse black flush push button, NC :
1x **88130757** + 1x **88130754** + 1x **30701009**

SPECIFICATIONS - PLASTIC operating head and adaptor

pilot valve			operating head	adaptator		intermediary subbase + pneumatic module(s)					
 or  =  +  +  or 											
designation	type	color	cat. number	cat. number	88130753 +	connect.	cat. number		cat. number		
	flush push button	impulse	black	88130745							
		green	88130744								
		red	88130743								
	mushroom* button Ø 40	push-turn	red	88130740				NC	30701009	NC+NC	30701011
		impulse	red	88130741							
	black		88130742								
	Ø 60	impulse	black	88130748							
	switch button	2 positions fixed	black	88130739			G1/8	NC	30701013	NC+NC	30701015
	key operated button	key removal at 0 and 1	black	88130738							
	lever switch button	2 positions fixed		black			88130737				
		3 positions fixed		black			88130736				
		3 positions self centring		black			88130735				


*These components are not security mechanism

Order example:

1 pilot valve, connection G 1/8, with impulse red flush push button, NC+NC :
 1x **88130743** + 1x **88130753** + 1x **30701015**

OPERATION OF 3 POSITION SWITCHES


type	operation on module	
	left	right
3 positions fixed 	0 → not operated	not operated
	1 → not operated	operated
	2 → operated	not operated
3 positions self centring 	0 → not operated	not operated
	1 → not operated	operated
	2 → operated	not operated




SEPARATED PNEUMATIC MODULES

connection	function	cat. number
instant fittings Ø 4 mm O.D.	NC	30701001
	NO	30701002
tapped G 1/8	NC	30701005
	NO	30701006



INTERMEDIARY SUBBASE

	cat. number
	88130775


DIMENSIONS




PANEL DRILLING



REDUCING ADAPTER Ø 30 → Ø 22 mm




MOUNTING




metal operating head

- ➔ 1 2 3 ◀ mounting
◀ 4 5 6 ➔ dismantling



plastic operating head


- ➔ 1 2 3 ◀ mounting
◀ 4 5 ➔ dismantling



PILOT VALVE

manually operated

instant fittings for Ø 4 mm O.D. tube or G 1/8



3/2
Series
310

SPECIFICATIONS


FLUID	: Air or neutral gas, filtered, lubricated or not
PORTS	: instant fittings Ø4 O.D. or G 1/8
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -5°C to +60°C
FLOW (Qv at 6 bar)	: 280 l/min (ANR)
Ø NOMINAL	: 3,5 mm

CONSTRUCTION

Spool and poppet design closed centre
Body zinc diecasting
Internal parts acetal
Sealing NBR (nitrile)




CHOICE OF EQUIPMENT


FUNCTION NC Normally closed			 1 = Pressure 2 = Outlet 3 = Exhaust		
Type	Description	Operating effort (daN)	CODES		
			Head ALONE	COMPLETE PILOT VALVE	
				Instant fittings	G 1/8
—	Valve alone BODY NC	5	—	31090002	31090001
	Push button Ø 40	5	88131007	31000015	31000008
	Impulse mushroom Ø 60	5	88131004	31000016	31000009
	Lever positive 2 maintained positions	—	88131003	31000017	31000010

DIMENSIONS AND WEIGHTS


Valve alone
Weight : 0,100 kg




Button Ø 40
Weight : 0,145 kg



Impulse mushroom Ø 60
Weight : 0,150 kg



Lever positive, 2 maintained positions
Weight : 0,120 kg



MINI SPOOL VALVE

manually operated
G 1/8

3/2-5/2
Series
550

SPECIFICATIONS

FLUID	: Air or neutral gas, filtered, lubricated
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -10 °C to +60 °C
FUNCTIONS	: 3/2 - 5/2
PORTS	: G 1/8
FLOW (Qv at 6 bar)	: 200 l/min (ANR)

CONSTRUCTION

Body anodized light alloy
Covers light alloy and acetal
Internal parts light alloy
Sealing nitrile (NBR)
Button synthetic resin







Possible mounting panel (percing Ø 16,5)

The 3/2 spool valve can be used as a 3/2 NC or 3/2 NO version, by connecting as indicated opposite



Ports of 3/2	
NC	NO
1 = Pressure	Exhaust
2 = Outlet	Outlet
3 = Exhaust	Pressure
Ports of 5/2	
1 = Pressure	
2,4 = Outlets	
3,5 = Exhausts	



CHOICE OF EQUIPMENT

Symbols Functions		Operators		CODES
		Pilot	Return	
3/2		Push button	Spring	55000040
		Push-pull button		55000039
		Lever - lever detented		55000043
5/2		Push button	Spring	55000009
		Push-pull button		55000010
		Lever - lever detented		55000011

5/2



Weight : 74 g

Weight : 94 g



Weight : 76 g

Weight : 92 g



① Dimensions on flats

SPECIFICATIONS

FLUID	: air or neutral gas, filtered, lubricated or not
PORTS	: G 1/4
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -25°C to +60°C
FLOW (Qv at 6 bar)	: 860 l/min (ANR)

CONSTRUCTION

Environmentally-protected construction
Body: treaded aluminium
Internal parts: zinc diecasting, steel,
stainless steel, acetal (POM)
Sealings: nitrile (NBR) and polyurethane (PUR)







For 3/2 NC
connection

1 = Pressure
2 = Outlet
3 = Exhaust



CHOICE OF EQUIPMENT

[Configurator - CAD Files](#)

Symbols functions	Operators		CODES
	Pilot	Return	
LEVER OPERATED			
	Lever - Lever detented		55102088
	Lever	Spring	55102089
PEDAL OPERATED			
	Pedal 2 positions		55102090
	Pedal	Spring	55102091
BUTTON OPERATED			
	Button	Spring	55102082
	Button push-pull		55102083


Note: do not connect the pressure supply to the exhaust port 3. For a "distributing" function or use in NO function, contact us.

These products exist in versions [5/2](#) and [5/3](#)

DIMENSIONS AND WEIGHTS

VALVE LEVER OPERATED

Weight: 0,360 kg




- ① 2 fixing holes : Ø 5,3 - counterbore : Ø 9, depth 5
- ② 2 fixing holes : Ø 8,5
- ③ Return pedal 2 positions

Configurator - CAD Files

VALVE PEDAL OPERATED


Weight: 0,515 kg



BUTTON

BUTTON PUSH-PULL

Weight: 0,230 kg



SPECIFICATIONS

FLUID	: air or neutral gas, filtered, lubricated (G 3/8) or not (G 1/4)
PORTS	: G 1/4 - G 3/8
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -25°C to +60°C
FLOW (Qv at 6 bar)	: see table below

CONSTRUCTION

series 551

Environmentally-protected construction
Body G 1/4, treated aluminium
Internal parts: zinc diecasting, steel, stainless steel, acetal (POM)
Sealings: nitrile (NBR) and polyurethane (PUR)

series 552







Body G 3/8, in light alloy
Internal parts: stainless steel, light alloy
Sealings: nitrile (NBR)



1	= Pressure
2,4	= Outlets
3,5	= Exhausts

CHOICE OF EQUIPMENT

[Configurator - CAD Files](#)


Symbols functions	Operators		Ø ports	Flow at 6 bar l/min (ANR)	CODES
	Pilot	Return			
LEVER OPERATED					
	Lever - Lever detented		G 1/4	860	55102092
	Lever 2 positions		G 3/8	1610	55200036
	Lever	Spring	G 1/4	860	55102093
			G 3/8	1610	55200037
PEDAL OPERATED					
	Pedal 2 positions		G 1/4	860	55102094
	Pedal	Spring	G 1/4	860	55102095
BUTTON OPERATED					
	Buton	Spring	G 1/4	860	55102085
	Button push-pull		G 1/4	860	55102086

DIMENSIONS AND WEIGHTS

VALVE LEVER OPERATED

Series 551: ports G 1/4

Weight: 0,390 kg




- ① 2 fixing holes: Ø 5,3 - counterbore : Ø 9, dept 5
- ② 2 fixing holes: Ø 8,5
- ③ 4 fixing holes: Ø 5,5
- ④ Return pedal 2 positions

VALVE PEDAL OPERATED

Series 551: ports G 1/4


Weight: 0,545 kg



Configurator - CAD Files

Series 552: ports G 3/8


Weight: 0,900 kg



BUTTON, BUTTON PUSH-PULL

Series 551: ports G 1/4

Weight: 0,265 Kg



SPECIFICATIONS

FLUID	: air or neutral gas, filtered, lubricated (G 3/8) or not (G 1/4)
PORTS	: G 1/4 - G 3/8
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -25°C to +60°C
FLOW (Qv at 6 bar)	: See table below

CONSTRUCTION

series 551

Environmentally-protected construction

Body G 1/4, treated aluminium

Internal parts: zinc diecasting, steel, stainless steel, acetal (POM)

Sealings: nitrile (NBR) and polyurethane (PUR)

series 552

Body G 3/8, in light alloy

Internal parts: stainless steel, light alloy





Sealings: nitrile (NBR)



1 = Pressure
2,4 = Outlets
3,5 = Exhausts


CHOICE OF EQUIPMENT

[Configurator - CAD Files](#)

	Symbols functions	Operators	Ø ports	Flow at 6 bar l/min (ANR)	CODES
5/3 closed position (W1)		Lever 3 positions detented (W1)	G 1/4	760	55102096
			G 3/8	1610	55200038
		Lever 3 positions spring to centre (W1)	G 1/4	760	55102097
			G 3/8	1610	55200039
5/3 open position to exhaust (W3)		Lever 3 positions detented (W3)	G 1/4	760	55102098
		Lever 3 positions spring to centre (W3)	G 1/4	760	55102099

DIMENSIONS AND WEIGHTS
VALVE LEVER OPERATED
Series 551: ports G 1/4

Weight: 0,510 kg





① 2 fixing holes: Ø 5,3 - counterbore : Ø 9, dept 5

② 4 fixing holes: Ø 5,5

[Configurator - CAD Files](#)
Series 552 : ports G 3/8

Weight: 0,900 kg





FEATURES


- valve with a covering cap
- Spring return or pedal return

SPECIFICATIONS

Fluid	Air or neutral gas, filtered, lubricated or not
Ports	G 1/4
Pressure	2 to 10 bar
Temperature	-25°C to +60°C
Flow (Qv at 6 bar)	655 l/min (ANR)

CONSTRUCTION


Covering cap	Shock-resistant plastic (polyethylene) in signal yellow
Housing	Shock-resistant plastic (polyethylene) in black
Internal parts	Anodized or nickel plated aluminium, stainless, brass
Seals	NBR (nitrile)



SPECIFICATIONS

Symbols functions		Operators		catalogue number
		Pilot	Return	
5/2		Pedal 2 positions		ZF2FD400OG00000
		Pedal	Spring	ZF2FA400OG00000


DIMENSIONS (mm), WEIGHT (kg) (mm)



PILOT VALVE

mechanically operated

instant fittings for Ø 4mm OD tube



3/2
Series
309

SPECIFICATION


FLUID	: Air filtered, lubricated or not
PORTS	: Instant fittings for flexible tube Ø 4 mm OD
PRESSURE	: 0 to 8 bar
TEMPERATURE	: -5°C to +50°C
OPERATORS	: Mechanical
FLOW (Qv at 6 bar)	: 140 l/min (ANR)
Ø NOMINAL	: 2,5 mm

CONSTRUCTION

Spool and poppet design closed centre
Body zinc diecasting
Internal parts in stainless steel and elastomer
Instant fittings in brass
Sealing NBR (nitrile)
Built-in silencer



CHOICE OF EQUIPMENT


FUNCTION NC Normally closed			Mechanical operator	1 = Pressure 2 = Outlet 3 = Exhaust (not tapped)		
Operating head + body		Effort (daN) Supply pressure			CODES	
Type	Description	2 bar	5 bar	8 bar		
	Simple push	1	1,7	2,5	30900002	
	Lever roller plastic roller	0,5	0,9	1,3	30900003	
	Lever roller ball bearing roller	0,5	0,9	1,3	30900001	
	1 way trip plastic roller (Life : 1 million cycles)	0,5	0,9	1,3	30900004	
	Threaded head push (※)	1	1,7	2,5	30900006	

(*) The pilot valve with a threaded head, is equipped with a treated steel stop rig which allows the valve to be used as an end stop (max. force 200 kg, 50 mm dia. cylinder).

MOUNTING





- A** : Actuating point
(small flow established)
- B** : Release point
- DC** : End of stroke position




**Side
operation
30°**

Max. speed :
1 m/s (plastic roller)
0,3 m/s (ball bearing roller)



1 way trip plastic roller



Max. speed :
0,5 m/s (plastic roller)




DIMENSIONS AND WEIGHTS

Tapped
Weight : 65 g

Stroke : 1,6
Max. stroke : 4




Push button
Weight : 80 g




	PA	PO	PRT	PR	PFC
Stroke (mm)	0,7	1	1,5	3	0

PA = Max. outflow
PO = Closed outflow
PRT = Release
PR = Rest
PFC = End of stroke

Lever roller
Weight : 75 g




1 way trip plastic roller
Weight : 80 g



HEAVY DUTY PILOT VALVE

mechanically operated
instant fittings
for Ø 4 mm OD tube or G 1/8

NC



3/2
Series
308

SPECIFICATION


FLUID	: Air filtered, lubricated or not
PORTS	: instant fittings for Ø 4 mm OD tube or G 1/8
PRESSURE	: 0,1 to 8 bar
TEMPERATURE	: -5°C to +50°C
FLOW (Qv at 6 bar)	: 140 l/min (ANR)
Ø NOMINAL	: 2,5 mm
OPERATING HEADS	: Mechanical
IMPLANTING	: CENELEC EN 50047 CNOMO n° 06.05.35

CONSTRUCTION

Centre closed poppet valve
Body diecast
Internal parts in stainless steel and elastomer
Built-in exhaust silencer (exhaust port can be piped G 1/8)
Instant fittings brass



CHOICE OF EQUIPMENT



FUNCTION NC Normally closed					1 = Pressure 2 = Outlet 3 = Exhaust	
Operating head		Action	Effort (daN) with 8 bar	CODES		
Type	Operator			Operating head ALONE	Valve body + operating head	
					Instant fittings	Tapped G 1/8
	Single lever plastic roller	Left and right	1,2	88130801 (*)	30800009	30800015
	Single lever bearing roller (CNOMO 06.05.35)	Left and right	1,2	88130802 (*)	30800010	30800016
	Adjustable lever with plastic roller	Left and right	0,4 to 1,2	88130803 (*)	30800011	30800017
	Adjustable lever with ball bearing roller	Left and right	0,4 to 1,2	88130804 (*)	30800012	30800018
	Flexible lever	Left and right	0,3 to 1,2	88130807 (*)	30800027	30800030
	Rotating head alone	Left and right	-	-	30800001	30800005

(*) The different levers are fitted to the valve fitted with a head with a side spindle (code 30800001 or 30800005)

CONNECTING

Exhaust
Flat silencers removable revealing an G 1/8 port.

Alternative pressure port G 1/8 in this case plug port (1).



All leaflets are available on: www.asco.com

Manually & Mechanically operated valves (3/2) - 19




DIMENSIONS AND WEIGHTS (Max. weight : 0,200 kg)

Valve with rotating
head alone

Single lever
plastic roller

Adjustable lever
with plastic roller or

Flexible lever




- ① Axe of the levers
- ② CENELEC mounting 2 holes Ø 4.2
- ③ CNOMO mounting 2 holes Ø 5.2
- ④ Instant fittings for tube Ø 4 mm or G 1/8
- ⑤ Exhaust with built-in silencer (can be piped G 1/8)

MOUNTING : SELECTING CONTROL POSITION

Single lever :

4 possible actions function of:


- (1) lever axe in relation to the head
- (2) roller position in relation to the lever



Upright adjustable lever :

2 possible mountings, by tilting the lever

Lever all types
on rotating head



- A** Actuation point
(small flow established)
- B** Release point
- Fdc** End of stroke position


PILOT VALVE

mechanically operated

instant fittings

for Ø 4 mm OD tube or G 1/8

NC


3/2
Series
310

SPECIFICATIONS





FLUID	: Air or neutral gas, filtered, lubricated or not
PORTS	: instant fittings for Ø 4 mm OD tube or G 1/8
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -5°C to +60°C
FLOW (Qv at 6 bar)	: 280 l/min (ANR)
Ø NOMINAL	: 3,5 mm

CONSTRUCTION

Spool and poppet design closed centre
 Body zinc diecasting
 Internal parts POM (acetal)
 Sealing NBR (nitrile)




CHOICE OF EQUIPMENT


FUNCTION NC Normally closed			 1 = Pressure 2 = Outlet 3 = Exhaust		
Type	Description	Effort (daN)	CODES		
			Head ALONE	ASSEMBLY (valve + head)	
				Instant fittings	G 1/8
—	Valve alone BODY NC	5	—	31090002	31090001
	Lever roller acetal	2	88131001	31000011	31000004
	One way trip acetal	1,5	88131002	31000012	31000005
	Lever roller metal	2	88131005	31000013	31000006

DIMENSIONS AND WEIGHTS


Valve alone
Weight : 1,100 kg




Lever roller
Weight : 0,110 kg



One way trip
Weight : 0,110 kg



Lever metal
Weight : 0,145 kg



SPECIFICATIONS

FLUID	: Air or neutral gas, filtered, lubricated
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -10°C to +60°C
FUNCTIONS	: 3/2 - 5/2
PORTS	: G 1/8
FLOW (Qv at 6 bar)	: 200 l/min (ANR)

CONSTRUCTION

Body anodized light alloy
Covers light alloy and acetal (POM)
Internal parts light alloy
Sealing NBR (nitrile)
Lever and tappet steel
The 3/2 spool valve can be used as a 3/2 NC or 3/2 NO version, by connecting as indicated opposite



Ports of 3/2	
NC	NO
1 = Pressure	Exhaust
2 = Outlet	Outlet
3 = Exhaust	Pressure
Ports of 5/2	
1 = Pressure	
2,4 = Outlets	
3,5 = Exhausts	

CHOICE OF EQUIPMENT

	Symbols Functions	Operators		Operating effort (daN)	CODES
		Pilot	Return		
3/2		Roller-lever	Spring	2	55000046
		Tappet	Spring	3	55000047
5/2		Roller-lever	Spring	2	55000012
		Tappet	Spring	3	55000052

OPTION

Mini spool valve with one way trip (contact us).

MINI SPOOL VALVE MECHANICALLY OPERATED SERIES 550

DIMENSIONS AND WEIGHTS



3/2

ROLLER-LEVER

Weight : 77 g

5/2

Weight : 86 g




TAPPET


Weight : 60 g

Weight : 76 g

Stroke : 3 mm
Max. stroke : 5,5 mm



Stroke : 3 mm
Max. stroke : 5,5 mm





SPOOL VALVE

mechanically operated

G 1/4

3/2-5/2
Series
551

SPECIFICATIONS

FLUID	: Air or neutral gas, filtered, lubricated or not
PORTS	: G 1/4
PRESSURE	: 0 to 10 bar
TEMPERATURE	: -25°C to +60°C
FLOW (Qv at 6 bar)	: 860 l/min (ANR)

CONSTRUCTION

Environmentally-protected construction
Spool valve
Body: treated aluminium
Internal parts: zinc diecasting, steel, stainless steel, acetal (POM)
Seals: NBR (nitrile) and PUR (polyurethane)



1 = Pressure
2,4 = Outlets
3,5 = Exhausts

CHOICE OF EQUIPMENT

[Configurator - CAD Files](#)

Type	Pilot	Return	Operating effort (daN)	CODES
3/2 	Roller	Spring	4,8	55102084
5/2 	Roller	Spring	4,8	55102087


Note: do not connect the pressure supply to the exhaust port 3. For a "distributing" function or use in NO function, contact us.

DIMENSIONS AND WEIGHTS


ROLLER

[Configurator - CAD Files](#)**3/2**

Weight: 0,250 kg

**5/2**


Weight: 0,285 kg



① 2 fixing holes: Ø 5,3 - counterbore : Ø 9, dept 5

Cam angles

Maximum speed: 0,3 m/s



SPECIFICATION

FLUID	: Air or neutral gas, filtered, lubricated
PRESSURE	: 2,5 to 10 bar
TEMPERATURE	: +10°C to +40°C
FLOW (Qv at 6 bar)	: 406 l/min (SRA)
Ø NOMINAL	: 4 mm
PORTS	: G 1/8
FUNCTION	: 3/2 NC - 3/2 NO
LIFE	: 10 million cycles
CONFORMING to CNOMO standard 06-05-25	

CONSTRUCTION

Pilot operated spool valve features:


- **snap-action** operation

- low actuating force



Body: light alloy

Internal parts: stainless steel and light alloy

Sealings: NBR (nitrile)



CHOICE OF EQUIPMENT



OPERATING HEADS			CODES		
			HEAD ALONE	COMPLETE PILOT VALVE	
				NC function 	NO function 
Type	Designation	Mechanical actuation			
	Pilot valve without operating head		-	32000001	32000002
	Pilot valve with mounting screws		-	32000065	32000066
	Single lever	Right and left	88132001	32000039	32000052
		Right or left	88132002	32000040	32000053
	Adjustable lever	Right and left	88132019	32000041	32000054
		Right or left	88132020	32000042	32000055
	Flexible rod lever	Right and left	88132021	32000043	32000056
		Right or left	88132029	32000044	32000057
	Forked one-track roller	Maintained position	88132022	32000045	32000058
	Top roller plunger	Operating force 1,3 daN	88132023	32000046	32000059
	Horizontal side roller plunger	Operating force 2,6 daN	88132024	32000047	32000060

PILOT VALVE MECHANICALLY OPERATED SERIES 320

DIMENSIONS AND WEIGHTS

Pilot valve without operating head
Weight: 0,265 kg

Pilot valve with 4 CM4 screws, 33 long,
for on-site assembly of operating head







Single lever
Weight: 0,505 kg

Adjustable lever
Weight: 0,515 kg


Flexible rod lever
Weight: 0,505 kg

Forked one-track roller
Weight: 0,530 kg




Top roller plunger
Weight: 0,465 kg

Horizontal side roller plunger
Weight: 0,510 kg



Useful stroke: 2
Max. stroke: 5



Useful stroke: 3
Max. stroke: 5


ASSEMBLY

● **SINGLE, ADJUSTABLE OR FLEXIBLE LEVER HEADS**
RIGHT OR LEFT ACTUATION

Actuation speed (v)	Cam angle (α_1)	Lever position (α_2)*
$\leq 1,5$ m/s	30° max.	$0 < \alpha_2 < 35^\circ$
$1,5 < v < 5$ m/s	10° max.	$0 < \alpha_2 < 55^\circ$

Max. travel: 75° from rest position.

* A pre-travel** of 25° must be added to the positioning ranges 0° to 35° and 0° to 55°.




RIGHT AND LEFT ACTUATION

Actuation speed (v)	α_1 and α_3
$\leq 1,5$ m/s	max. 30°
$1,5 < v < 5$ m/s	max. 10°


Max. travel: 75° on either side of the rest position.

Pre-travel^{**}: 25° on either side of the rest position.



- FORKED ONE-TRACK ROLLER, MAINTAINED POSITION

Actuation speed (v)	Cam angle (α_1)
$\leq 0,5 \text{ m/s}$	$45^\circ < \alpha_1 < 90^\circ$



- **ROLLER HEADS**

These completely interchangeable heads can take 4 positions at 90° to the vertical axis of the device. The direction of actuation is indicated by the arrow F (actuation speed: 0,25 m/s).



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk