


1125752	<b>DATA SHEET</b>	
valid from: 01.01.2019	<b>ÖLFLEX® CLASSIC 110 SY</b>	

## Application

ÖLFLEX® CLASSIC 110 SY cables are VDE approved power and control cables for occasional flexible use and fixed installation for medium mechanical stresses. They are among others designed for use in dry, damp and wet conditions. If using outdoors, observe the indicated temperature range and use with UV protection. They are largely resistant to acids, alkalis and certain oils at room temperature. They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm<sup>2</sup> of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

The braid of galvanized steel-wires is an additional mechanical protection.

### Application range:

As power and connecting cable in plant engineering and construction, industrial machinery and in heating and air-conditioning systems as well as in areas with high mechanical stress.

## Design

Design	based on EN 50525-2-51 resp. VDE 0285-525-2-51
Certification	< VDE-REG 7030 >
Conductor	fine wire strands of bare copper, acc. to IEC 60228 resp. VDE 0295, class 5
Insulation	PVC compound T12 acc. to DIN EN 50363-3 resp. VDE 0207-363-3 with increased requirements acc. to Lapp specification
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to DIN EN 50334 resp. VDE 0293-334
Stranding	cores are stranded in layers
Inner sheath	PVC compound TM2 acc. to EN 50363-4-1 resp. VDE 0207-363-4-1 colour: silver grey, similar RAL 7001
Braid	braid of galvanized steel-wires, coverage = 70 % (nominal value)
Outer sheath	PVC compound TM2 acc. to EN 50363-4-1 resp. VDE 0207-363-4-1 colour: transparent

## Electrical properties at 20°C

Rated voltage	U <sub>0</sub> / U: 300 / 500 V
Test voltage	core / core: 4000 V AC core / screen: 4000 V AC

## Mechanical and thermal properties

Minimum bending radius	occasional flexing: 20 x cable diameter fixed installation: 6 x cable diameter
Temperature range	occasional flexing: - 5 °C up to +70 °C max. conductor temp. fixed installation: - 40 °C up to +80 °C max. conductor temp.
Flammability	acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2
Tests	acc. to IEC 60811, EN 50395, EN 50396
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Creator: HESC / PDC	Document: DB1125752EN	Page 1 of 1
Released: ALTE / PDC	Version: 06	

We reserve all rights according to DIN ISO 16016.

PD 0019/05\_04.18EN



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)