

Technical Data **4115**Effective October 2017
Supersedes July 2015**BUSSMANN**
SERIES

CEO BS88 Offset bolted tags fuse links



Product description

Eaton's Bussmann® series CEO British Standard fuse links, size A4, are specifically designed for the protection of general industrial applications e.g. power distribution, cable protection, motor protection.

Standard features

- Good peak let-through current limitation
- 1:1:6 Selective coordination ratio between "minor" and "major" fuse
- Suitable for motor protection if gM type selected
- Power loss values well within the limits of IEC 60269-2

EATON*Powering Business Worldwide*

Technical Data 4115

Effective October 2017

CEO BS88 Offset bolted tags fuse links

Catalogue symbol:

- CEO (Amps)

Technical data:

- Rated voltage: 500 V a.c. (gG) / 415 V a.c. (gM)
- Rated current: 32 to 100 A
- Breaking capacity: 80kA a.c.
- BS reference: A4
- Breaking range and utilisation category: gG and gM

Standards/approvals:

- BS88-2
- IEC 60269-2
- Suitable for use in RoHS compliant applications

Fuse holder (ordered separately)

- RS100H (Red Spot)


Packaging:

- MOQ 10

Table 1. Technical data

Part number	Voltage	Current rating (amps)	Energy integrals I ² t (A ² S)		Watts loss	Weight
			Pre-arcing	Total at 415V	W	
CEO32	500 V a.c.	32	1000	2760	3.5	75g
CEO40	500 V a.c.	40	1400	3750	4.7	75g
CEO50	500 V a.c.	50	3000	8350	4.9	75g
CEO63	500 V a.c.	63	7000	18,800	5.6	75g
CEO80	500 V a.c.	80	13,000	35,200	7.2	75g
CEO100	500 V a.c.	100	25,000	76,500	8.5	75g
CEO100M125	415 V a.c.	100M125	57,000	150,000	6.5	100g
CEO100M160	415 V a.c.	100M160	72,500	190,000	5	100g
CEO100M200	415 V a.c.	100M200	120,000	290,000	3.5	195g

Dimensions - mm




Catalogue numbers	A	B	C	D	E	F	G	H
CEO32-100	109.5	94	58.5	14.3	11	8.7	24.5	21
CEO100M125-160	109	94	58	14.3	11	8.7	26.8	25.8
CEO100M200	110	94	47	19	10	9	29.5	31

CEO BS88 Offset bolted tags fuse links

Technical Data 4115

Effective October 2017

Time current curve - CEO32 to CEO100 A




Technical Data 4115

Effective October 2017

CEO BS88 Offset bolted tags fuse links

Time current curve - CEO100M



Eaton
 EMEA Headquarters
 Route de la Longeraie 7
 1110 Morges, Switzerland

Eaton Electrical Products Limited
 Melton Road
 Burton-on-the-Wolds
 Leicestershire, LE12 5TH
 United Kingdom

© 2017 Eaton
 All Rights Reserved
 PDF Only
 Publication No. 4115
 October 2017

EATON
 Powering Business Worldwide

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to Trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk