

Technical Data **4102**Effective October 2017
Supersedes January 2016**BUSSMANN**
SERIES

FF BS88 Centre bolted tags fuse links



Product description

Eaton's Bussmann® series FF British Standard, size C2, fuse links are specifically designed for the protection of general industrial applications e.g. power distribution and cable protection.

Standard features

- Good peak let-through current limitation
- 1:1:6 Selective coordination ratio between "minor" and "major" fuse
- Power loss values well within the limits of IEC 60269-2

EATON*Powering Business Worldwide*

Technical Data 4102

Effective October 2017

FF BS88 Centre bolted tags fuse links

Catalogue symbol:

- FF(Amps)

Technical data:

- Rated voltage: 550 V a.c. / 400 V d.c.
- Rated current: 450 to 630 A
- Breaking capacity: 80 kA a.c. / 40 kA d.c.
- Breaking range and utilisation category: gG
- Size: C2

Standards/Approvals:

- BS88-2
- IEC 60269-2
- Suitable for use in RoHS compliant applications


Packaging:

- MOQ 1

Table 1. Technical data

Part number	Rated voltage	Rated current (Amps)	Energy integrals I²t (A²S)		Watts loss	Dimensions (mm)										Product class	Weight
			Pre-arcing	Total at 415 V a.c.		W	A	B	C	D	E	F	G	H	J		
FF450	550 V a.c. 400V d.c.	450	850	1600	32	210	185	77.5	10.5	15.5	25.4	134	74	6.4	gG	1.055Kg	
FF500	550 V a.c. 400 V d.c.	500	1100	2000	38	210	185	77.5	10.5	15.5	25.4	134	74	6.4	gG	1.055Kg	
FF560	550 V a.c. 400V d.c.	560	1400	2400	43	210	185	77.5	10.5	15.5	25.4	134	74	6.4	gG	1.055Kg	
FF630	550 V a.c. 400V d.c.	630	2000	3500	50	210	185	77.5	10.5	15.5	25.4	134	74	6.4	gG	1.055Kg	

Outline drawing




Technical Data 4102

Effective October 2017

FF BS88 Centre bolted tags fuse links

Time current curve



Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to Trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

Eaton
 EMEA Headquarters
 Route de la Longeraie 7
 1110 Morges, Switzerland

Eaton Electrical Products Limited
 Melton Road
 Burton-on-the-Wolds
 Leicestershire, LE12 5TH
 United Kingdom

© 2017 Eaton
 All Rights Reserved
 PDF Only
 Publication No. 4102
 October 2017

EATON
 Powering Business Worldwide

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk