

# End cover - D-MPT 1,5/S - 3248120



<https://www.phoenixcontact.com/il/products/3248120>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---

End cover, length: 33.6 mm, width: 2.2 mm, height: 22.3 mm, color: gray



---

## Your advantages

- End cover, enables the open terminal side to be covered

# End cover - D-MPT 1,5/S - 3248120



<https://www.phoenixcontact.com/il/products/3248120>

## Commercial Data

Order Key	3248120
Packing unit	50 pc
Minimum order quantity	50 pc
Catalog Page	Page 45 (C-1-2019)
GTIN	4046356768696
Weight per Piece (including packing)	1.1 GRM
Weight per Piece (excluding packing)	1.1 GRM
Customs tariff number	85389099
Country of origin	PL

# End cover - D-MPT 1,5/S - 3248120



<https://www.phoenixcontact.com/il/products/3248120>

## Technical Data

### Dimensions

Height NS 15	28.1 mm
Length	33.6 mm
End cover width	2.2 mm
Height	22.3 mm
Width	2.2 mm

### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature 130°C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (actuation)	-5 °C ... 70 °C

### Notes

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

### Material specifications

Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Static insulating material application in cold	-60 °C
Color	gray
Material	PA
Surface flammability NFPA 130 (ASTM E 162)	passed
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Smoke gas toxicity NFPA 130 (SMP 800C)	passed
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Flammability rating according to UL 94	V0
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed

Phoenix Contact 2021 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Israel Ltd.  
 P.O.B. 1799 Industrial Park Hasharon  
 Quadima 60920

# End cover - D-MPT 1,5/S - 3248120

<https://www.phoenixcontact.com/il/products/3248120>



+972-9-8915700

[info@phoenixcontact.co.il](mailto:info@phoenixcontact.co.il)



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)