

ASi-5/ASi-3 Address Programming Device



ASi-5/ASi-3 Address Programming Device

for addressing of
ASi modules of all ASi specifications up to ASi-5



(figure similar)

The **ASi-5/ASi-3 handheld address programming device** is a compact device used for addressing ASi modules of all ASi specifications (2.0, 2.1, 3.0 and ASi-5).

The electromechanical connection takes place via one of the two addressing plugs that allow the addressing of ASi modules of specification 2.0 to ASi-5.

The scope of delivery includes the ASi-5/ASi-3 handheld address programming device, the USB-A to USB-C recharger cable and the addressing cables for addressing ASi-5 or ASi-3 modules (all connecting cables can be ordered as accessories).

Article no.	BW4708
Application	commissioning
Indication	color display (RGB OLED)
Buttons	membrane keyboard with 6 keys
Interface/connection	<ul style="list-style-type: none"> • 1 x connection for jack plug • 1 x connection for barrel plug • 1 x USB-C connection
	short circuit and overload protected
Power Supply ⁽¹⁾	via supercapacitor charging time: fully charged in ca. 30 min, sufficient for ≥120 read/write operations, already 10 min of charging are sufficient to allocate 70 ASi addresses (e.g. AB, single, ASi-5)
Operating time	≥ 120 read/write operations with a fully charged supercapacitor
Protection category according to EN 60529	IP20
Operating temperature	0 °C ... +50 °C
Storage temperature	-20 °C ... +55 °C
Weight	approx. 140 g (without cables)
Dimensions (W / H / D) in mm	60 / 130 / 35
Scope of delivery	<ul style="list-style-type: none"> • ASi-5/ASi-3 address programming device (BW4708) • ASi-5 addressing cable, jack plug to jack plug, 1,5 m (BW4711) • ASi-3 addressing cable, barrel plug to barrel plug, 1,5 m (BW4712) • Recharger cable USB-A to USB-C, 1 m (BW4713) • ASi addressing cable, barrel plug to connecting wires, 1,5 m (BW4731)

⁽¹⁾ Power supply via Recharger cable USB-A to USB-C (BW4713).

Plug-in recharger USB-A for 115 V/230 V (BW4714) is sold separately (see accessories).

Accessories

- ASi-5 addressing cable, jack plug to jack plug, 1,5 m (BW4711)
- ASi-3 addressing cable, barrel plug to barrel plug, 1,5 m (BW4712)
- Recharger cable USB-A to USB-C, 1 m (BW4713)
- Plug-in recharger USB-A for 115 V/230 V (BW4714)
- ASi addressing cable, barrel plug to connecting wires, 1,5 m (BW4731)
- ASi addressing cable, barrel plug to M12 cable socket, straight, 5 poles, 1,5 m (BW4732)



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk