DOWNLOADED FROM SCATTS.CO.UK

OMRON

R88M-1□

1S servo motor

Simplified machine design and maintenance

- 23-bit resolution encoder
- Compact and small motor size
- Multi-turn encoder design without mechanics: 16-bit, 65536 turns
- Battery-free absolute multi-turn encoder or incremental encoder
- Pre-assembled motor cables
- Designed for easy EMC compliance

Ratings

- 230 VAC from 50 W to 1.5 kW (rated torque from 0.159 to 8.59 Nm)
- 400 VAC from 400 W to 15 kW (rated torque from 1.91 to 95.5 Nm)

System configuration

(Refer to servo drive chapter)



1S servo drive

1S servo motor (Flange size 80 mm or less)

SYSMAC always in control





3000 rpm (50 W - 750 W)

1S servo motor (Flange size 100 mm or more)





3000 rpm (1 kW - 5 kW)
2000 rpm (400 W - 3 kW)
1500 rpm (4 kW - 15 kW)
1000 rpm (900 W - 3 kW)

DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Servo motor / Servo drive combination

1S servo motor						1S servo drive
Appearance	Speed	Voltage	Rated torque	Capacity	Model	
	3000 min^{-1}	230 V	0.159 Nm	50 W	R88M-1M05030T-□	R88D-1SN01H-ECT
			0.318 Nm	100 W	R88M-1M10030(H/T)-□	R88D-1SN01H-ECT
			0.637 Nm	200 W	R88M-1M20030(H/T)-□	R88D-1SN02H-ECT
			1.27 Nm	400 W	R88M-1M40030(H/T)-□	R88D-1SN04H-ECT
			2.39 Nm	750 W	R88M-1M75030(H/T)-□	R88D-1SN08H-ECT
			3.18 Nm	1 kW	R88M-1L1K030(H/T)-□	R88D-1SN15H-ECT
			4.77 Nm	1.5 kW	R88M-1L1K530(H/T)-□	R88D-1SN15H-ECT
		400 V	2.39 Nm	750 W	R88M-1L75030C-□	R88D-1SN10F-ECT
			3.18 Nm	1 kW	R88M-1L1K030C-□	R88D-1SN10F-ECT
			4.77 Nm	1.5 kW	R88M-1L1K530C-□	R88D-1SN15F-ECT
			6.37 Nm	2 kW	R88M-1L2K030C-□	R88D-1SN20F-ECT
			9.55 Nm	3 kW	R88M-1L3K030C-□	R88D-1SN30F-ECT
			12.7 Nm	4 kW	R88M-1L4K030C-□	R88D-1SN55F-ECT
			15.9 Nm	5 kW	R88M-1L5K030C-□	R88D-1SN55F-ECT
	2000 min^{-1}	230 V	4.77 Nm	1 kW	R88M-1M1K020(H/T)-□	R88D-1SN15H-ECT
			7.16 Nm	1.5 kW	R88M-1M1K520(H/T)-□	R88D-1SN15H-ECT
		400 V	1.91 Nm	400 W	R88M-1M40020C-□	R88D-1SN06F-ECT
			2.86 Nm	600 W	R88M-1M60020C-□	R88D-1SN06F-ECT
			4.77 Nm	1 kW	R88M-1M1K020C-□	R88D-1SN10F-ECT
			7.16 Nm	1.5 kW	R88M-1M1K520C-□	R88D-1SN15F-ECT
			9.55 Nm	2 kW	R88M-1M2K020C-□	R88D-1SN20F-ECT
			14.3 Nm	3 kW	R88M-1M3K020C-□	R88D-1SN30F-ECT
	1500 min^{-1}	400 V	25.5 Nm	4 kW	R88M-1M4K015C-□	R88D-1SN55F-ECT
			35 Nm	5.5 kW	R88M-1M5K515C-□	R88D-1SN55F-ECT
			47.8 Nm	7.5 kW	R88M-1M7K515C-□	R88D-1SN75F-ECT
			70 Nm	11 kW	R88M-1M11K015C-□	R88D-1SN150F-ECT
			95.5 Nm	15 kW	R88M-1M15K015C-□	R88D-1SN150F-ECT
	1000 min^{-1}	230 V	8.59 Nm	900 W	R88M-1M90010T-□	R88D-1SN15H-ECT
		400 V	8.59 Nm	900 W	R88M-1M90010C-□	R88D-1SN10F-ECT
			19.1 Nm	2 kW	R88M-1M2K010C-□	R88D-1SN20F-ECT
			28.7 Nm	3 kW	R88M-1M3K010C-□	R88D-1SN30F-ECT

Note: For servo motor and cable part numbers, refer to ordering information at the end of this chapter.
Note: Refer to the servo drive chapter for drive options selection and detailed specifications.

Type designation

R88M-1M10030T-BOS2

1S Series servo motor

Servo motor type
L: Low-inertia type
M: Middle-inertia type

Capacity
050: 50 W
100: 100 W
200: 200 W
400: 400 W
600: 600 W
750: 750 W
900: 900 W
1K0: 1 kW
1K5: 1.5 kW
2K0: 2 kW
3K0: 3 kW
4K0: 4 kW
5K0: 5 kW
5K5: 5.5 kW
7K5: 7.5 kW
11K0: 11 kW
15K0: 15 kW

Rated speed
10: 1000 rpm
15: 1500 rpm
20: 2000 rpm
30: 3000 rpm

Shaft end specifications
Blank: Straight shaft, no key
S2: Straight, key, tapped (standard)

Oil seal specifications
Blank: No oil seal
O: Oil seal

Brake specifications
Blank: No brake
B: Brake

Voltage and encoder specifications
H: 230 V, 23-bit incremental encoder
T: 230 V, 23-bit absolute battery-less encoder
C: 400 V, 23-bit absolute battery-less encoder

DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Specifications

3000 r/min servo motors, 230 V

Ratings and specifications

Voltage			230 V						
Servo motor model: R88M-1□		23-bit incremental encoder	–	M10030H-□	M20030H-□	M40030H-□	M75030H-□	L1K030H-□	L1K530H-□
		23-bit absolute encoder	M05030T-□	M10030T-□	M20030T-□	M40030T-□	M75030T-□	L1K030T-□	L1K530T-□
Rated output		W	50	100	200	400	750	1000	1500
Rated torque		Nm	0.159	0.318	0.637	1.27	2.39	3.18	4.77
Instantaneous peak torque		Nm	0.56	1.11	2.2	4.5	8.4	9.55	14.3
Rated current		A (rms)	0.67	0.84	1.5	2.5	4.6	5.2	8.8
Instantaneous max. current		A (rms)	2.6	3.1	5.6	9.1	16.9	16.9	28.4
Rated speed		min^{-1}	3000						
Max. speed		min^{-1}	6000					5000	
Torque constant		N·m/A	0.25	0.42	0.48	0.56	0.59	0.67	0.58
Rotor moment of inertia		$kg·m^2x10^{-4}$ (without brake)	0.0418	0.089	0.2232	0.4452	1.8242	2.1042	
		$kg·m^2x10^{-4}$ (with brake)	0.0496	0.0968	0.2832	0.5052	2.0742	2.5542	
Electrical time constant		ms	0.67	0.83	2.4	2.6	3.3	5.9	6.1
Allowable radial load		N	68		245		490		
Allowable thrust load		N	58		88		196		
Weight		kg (without brake)	0.35	0.52	1.0	1.4	2.9	5.7	
		kg (with brake)	0.59	0.77	1.3	1.9	3.9	7.4	
Brake specifications	Excitation voltage[*1]		24 VDC ±10%						
	Holding brake moment of inertia J	$kg·m^2x10^{-4}$	0.0078		0.06		0.25	0.45	
	Current consumption (at 20°C)	A	0.27		0.32		0.37	0.70	
	Static friction torque	Nm (minimum)	0.32		1.37		2.55	9.3	
Basic specifications	Insulation class		Type F						
	Ambient operating/storage temperature		0 to 40°C/-20 to 65°C						
	Ambient operating/storage humidity		20 to 90% (non-condensing)						
	Atmosphere		No corrosive gases						
	Insulation resistance		10 MΩ min. at 500 VDC between the power terminals and FG terminal						
	Vibration resistance		Vibration acceleration of 49 m/s^2						
	Impact resistance		Acceleration of 98 m/s^2 max. 3 times each in X, Y and Z directions						
	Enclosure		IP67 (except for through-shaft parts when connectors are inserted)						

[*1] This is a non-excitable brake (it is released when excitation voltage is applied).

Torque-speed characteristics

R88M-1M05030T (230 V, 50 W)



R88M-1M10030H/T (230 V, 100 W)



R88M-1M20030H/T (230 V, 200 W)



R88M-1M40030H/T (230 V, 400 W)



R88M-1M75030H/T (230 V, 750 W)



R88M-1L1K030H/T (230 V, 1 kW)



R88M-1L1K530H/T (230 V, 1.5 kW)



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

3000 r/min servo motors, 400 V

Ratings and specifications

Voltage			400 V						
Servo motor model: R88M-1□		23-bit absolute encoder	L75030C-□	L1K030C-□	L1K530C-□	L2K030C-□	L3K030C-□	L4K030C-□	L5K030C-□
Rated output		W	750	1000	1500	2000	3000	4000	5000
Rated torque		Nm	2.39	3.18	4.77	6.37	9.55	12.7	15.9
Instantaneous peak torque		Nm	7.16	9.55	14.3	19.1	28.7	38.2	47.7
Rated current		A (rms)	3.0	3.0	4.5	6.3	8.7	12.8	13.6
Instantaneous max. current		A (rms)	9.6	9.6	14.1	19.8	27.7	42.4	
Rated speed		min^{-1}	3000						
Max. speed		min^{-1}	5000						
Torque constant		N·m/A	0.91	1.17	1.17	1.15	1.23	1.11	1.32
Rotor moment of inertia		$kg·m^2x10^{-4}$ (without brake)	1.3042	2.1042		2.4042	6.8122	8.8122	10.6122
		$kg·m^2x10^{-4}$ (with brake)	1.7542	2.5542		2.8542	7.3122	11.3122	13.1122
Electrical time constant		ms	4.3	5.9		6.3	11.0	12.0	13.0
Allowable radial load		N	490					880	
Allowable thrust load		N	196					343	
Weight		kg (without brake)	4.1	5.7		6.4	11.5	13.5	16.0
		kg (with brake)	5.8	7.4		8.1	12.5	16.0	18.5
Brake specifications	Excitation voltage[*1]		24 VDC ±10%						
	Holding brake moment of inertia J	$kg·m^2x10^{-4}$	0.45				0.50	2.5	
	Current consumption (at 20°C)	A	0.70				0.66	0.6	
	Static friction torque	Nm (minimum)	9.3				12.0	16.0	
Basic specifications	Insulation class		Type F						
	Ambient operating/storage temperature		0 to 40°C/-20 to 65°C						
	Ambient operating/storage humidity		20 to 90% (non-condensing)						
	Atmosphere		No corrosive gases						
	Insulation resistance		10 MΩ min. at 500 VDC between the power terminals and FG terminal						
	Vibration resistance		Vibration acceleration of 49 m/s^2						
	Impact resistance		Acceleration of 98 m/s^2 max. 3 times each in X, Y and Z directions						
	Enclosure		IP67 (except for through-shaft parts when connectors are inserted)						

[*1] This is a non-excitable brake (it is released when excitation voltage is applied).

Torque-speed characteristics

R88M-1L75030C (400 V, 750 W)



R88M-1L1K030C (400 V, 1 kW)



R88M-1L1K530C (400 V, 1.5 kW)



R88M-1L2K030C (400 V, 2 kW)



R88M-1L3K030C (400 V, 3 kW)



R88M-1L4K030C (400 V, 4 kW)



R88M-1L5K030C (400 V, 5 kW)



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

2000 r/min servo motors, 230 V/400 V

Ratings and specifications

Voltage			230 V		400 V					
Servo motor model: R88M-1□		23-bit incremental encoder	M1K020H-□	M1K520H-□						
		23-bit absolute encoder	M1K020T-□	M1K520T-□	M40020C-□	M60020C-□	M1K020C-□	M1K520C-□	M2K020C-□	M3K020C-□
Rated output		W	1000	1500	400	600	1000	1500	2000	3000
Rated torque		Nm	4.77	7.16	1.91	2.86	4.77	7.16	9.55	14.3
Instantaneous peak torque		Nm	14.3	21.5	5.73	8.59	14.3	21.5	28.7	43.0
Rated current		A (rms)	5.2	8.6	1.1	1.6	2.9	4.1	5.7	8.6
Instantaneous max. current		A (rms)	16.9	28.4	3.9	5.5	9.4	13.5	19.8	28.3
Rated speed		min^{-1}	2000							
Max. speed		min^{-1}	3000							
Torque constant		N·m/A	0.93	0.83	1.75	1.84	1.69	1.75		1.74
Rotor moment of inertia		$kg·m^2x10^{-4}$ (without brake)	6.0042	9.0042	2.5042	3.9042	6.0042	9.0042	12.2042	15.3122
		$kg·m^2x10^{-4}$ (with brake)	6.5042	9.5042	2.8472	4.2472	6.5042	9.5042	12.7042	17.4122
Electrical time constant		ms	13.0	15.0	6.8	7.8	13.0	13.0	14.0	20.0
Allowable radial load		N	490							784
Allowable thrust load		N	196							343
Weight		kg (without brake)	6.6	8.5	3.9	4.7	6.6	8.5	10.0	12.0
		kg (with brake)	8.6	10.5	4.8	5.8	8.6	10.5	12.0	15.0
Brake specifications	Excitation voltage*1		24 VDC ±10%							
	Holding brake moment of inertia J	$kg·m^2x10^{-4}$	0.5		0.343		0.5			2.1
	Current consumption (at 20°C)	A	0.51		0.3		0.51		0.66	0.6
	Static friction torque	Nm (minimum)	9.0		3.92		9.0		12.0	16.0
Basic specifications	Insulation class		Type F							
	Ambient operating/storage temperature		0 to 40°C/-20 to 65°C							
	Ambient operating/storage humidity		20 to 90% (non-condensing)							
	Atmosphere		No corrosive gases							
	Insulation resistance		10 MΩ min. at 500 VDC between the power terminals and FG terminal							
	Vibration resistance		Vibration acceleration of 49 m/s^2							
	Impact resistance		Acceleration of 98 m/s^2 max. 3 times each in X, Y and Z directions							
	Enclosure		IP67 (except for through-shaft parts when connectors are inserted)							

*1 This is a non-excitable brake (it is released when excitation voltage is applied).

Torque-speed characteristics

R88M-1M1K020H/T (230 V, 1 kW)



R88M-1M1K520H/T (230 V, 1.5 kW)



R88M-1M40020C (400 V, 400 W)



R88M-1M60020C (400 V, 600 W)



R88M-1M1K020C (400 V, 1 kW)



R88M-1M1K520C (400 V, 1.5 kW)



R88M-1M2K020C (400 V, 2 kW)



R88M-1M3K020C (400 V, 3 kW)



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

1500 r/min servo motors, 400 V

Ratings and specifications

Voltage			400 V				
Servo motor model: R88M-1□		23-bit absolute encoder	M4K015C-□	M5K515C-□	M7K515C-□	M11K015C-□	M15K015C-□
Rated output		W	4,000	5,500	7,500	11,000	15,000
Rated torque		Nm	25.5	35.0	47.8	70	95.5
Instantaneous peak torque		Nm	75	95	119	175	224
Rated current		A (rms)	12.8	14.0	22.0	31.4	33.3
Instantaneous max. current		A (rms)	42.4		56.5	80.7	81.2
Rated speed		min^{-1}	1,500				
Max. speed		min^{-1}	3,000			2,000	
Torque constant		N·m/A (rms)	2.07	2.68	2.49	2.6	3.27
Rotor moment of inertia		$kg·m^2x10^{-4}$ (without brake)	54.0122	77.0122	113.0122	229.0122	340.0122
		$kg·m^2x10^{-4}$ (with brake)	60.0122	83.0122	118.0122	253.0122	365.0122
Electrical time constant		ms	18	19	23	29	
Allowable radial load		N	1,200	1,470		2,500	
Allowable thrust load		N	343	490		686	
Weight		kg (without brake)	21	29	39	63	85
		kg (with brake)	26	34	45	73	99
Brake specifications	Excitation voltage*1		24 VDC ±10%				
	Holding brake moment of inertia J	$kg·m^2x10^{-4}$	6.0		5.0	24.0	25.0
	Current consumption (at 20°C)	A	1.0		1.4	1.7	0.92
	Static friction torque	Nm (minimum)	32 min.	42 min.	54.9 min.	90 min.	100 min.
Basic specifications	Insulation class		Class F				
	Ambient operating/storage temperature		0 to 40°C/-20 to 65°C				
	Ambient operating/storage humidity		20 to 90% (non-condensing)				
	Atmosphere		No corrosive gases				
	Insulation resistance		10 MΩ min. at 500 VDC between the power terminals and FG terminal				
	Vibration resistance		Vibration acceleration of 49 m/s^2				
	Impact resistance		Acceleration of 98 m/s^2 max. 3 times each in X, Y and Z directions				
	Enclosure		IP67 (except for through-shaft parts when connectors are inserted)				

*1 This is a non-excitable brake (it is released when excitation voltage is applied).

Torque-speed characteristics

R88M-1M4K015C (400 V, 4 kW)



R88M-1M5K515C (400 V, 5.5 kW)



R88M-1M7K515C (400 V, 7.5 kW)



R88M-1M11K015C (400 V, 11 kW)



R88M-1M15K015C (400 V, 15 kW)



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

1000 r/min servo motors, 230 V/400 V

Ratings and specifications

Voltage			230 V	400 V		
Servo motor model: R88M-1□		23-bit absolute encoder	M90010T-□	M90010C-□	M2K010C-□	M3K010C-□
Rated output		W	900		2000	3000
Rated torque		Nm	8.59		19.1	28.7
Instantaneous peak torque		Nm	19.3		47.7	71.7
Rated current		A (rms)	6.7	3.6	7.1	10.6
Instantaneous max. current		A (rms)	16.9	9.0	19.5	27.7
Rated speed		min^{-1}	1000			
Max. speed		min^{-1}	2000			
Torque constant		N·m/A	1.28	2.41	3.00	2.97
Rotor moment of inertia		$kg·m^2x10^{-4}$ (without brake)	9.0042		40.0122	68.0122
		$kg·m^2x10^{-4}$ (with brake)	9.5042		45.1122	73.1122
Electrical time constant		ms	15.0	13.0	16.0	19.0
Allowable radial load		N	686		1176	1470
Allowable thrust load		N	196		490	
Weight		kg (without brake)	8.5		18.0	28.0
		kg (with brake)	10.5		22.0	33.0
Brake specifications	Excitation voltage[*1]		24 VDC ±10%			
	Holding brake moment of inertia J	$kg·m^2x10^{-4}$	0.5		5.1	
	Current consumption (at 20°C)	A	0.51		1.2	1.0
	Static friction torque	Nm (minimum)	9.0		22.0	42.0
Basic specifications	Insulation class		Type F			
	Ambient operating/storage temperature		0 to 40°C/-20 to 65°C			
	Ambient operating/storage humidity		20 to 90% (non-condensing)			
	Atmosphere		No corrosive gases			
	Insulation resistance		10 MΩ min. at 500 VDC between the power terminals and FG terminal			
	Vibration resistance		Vibration acceleration of 49 m/s^2			
	Impact resistance		Acceleration of 98 m/s^2 max. 3 times each in X, Y and Z directions			
	Enclosure		IP67 (except for through-shaft parts when connectors are inserted)			

[*1] This is a non-excitable brake (it is released when excitation voltage is applied).

Torque-speed characteristics

R88M-1M90010T (230 V, 900 W)



R88M-1M90010C (400 V, 900 W)



R88M-1M2K010C (400 V, 2 kW)



R88M-1M3K010C (400 V, 3 kW)



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Dimensions

Servo motors

Type 3000 r/min motors (230 V, 50 W)

Dimensions (mm)	Without brake	With brake	Approx. mass (kg)	
Model: R88M-1□	LL	LL	Without brake	With brake
M05030T-□S2	67.5	103.5	0.35	0.59

Models without brake



Models with brake





Shaft end



Type 3000 r/min motors (230 V, 100 W)

Dimensions (mm)	Without brake	With brake	Approx. mass (kg)	
Model: R88M-1□	LL	LL	Without brake	With brake
M10030(H/T)-□S2	90	126	0.52	0.77

Models without brake



Models with brake



Shaft end



Type 3000 r/min motors (230 V, 200 W to 750 W)

Dimensions (mm)	Without brake		With brake		LR	Flange surface					Shaft end							Approx. mass (kg)	
Model: R88M-1□	LL	KL1	LL	KL1		LB	LC	LD	LG	LZ	S	QA	QK	W	U	T	Tap x depth	Without brake	With brake
M20030(H/T)-□S2	79.5	52.6	107.5	52.6	30	50 dia. 0 -0.025	60	70	6	4.5	11 dia. 0 -0.011	2	20	4 0 -0.03	1.5 0 -0.2	4	M4 x 10L	1.0	1.3
M40030(H/T)-□S2	105.5		133.5								14 dia. 0 -0.011			5 0 -0.03	2 0 -0.2	5	M5 x 12L	1.4	1.9
M75030(H/T)-□S2	117.3	63.2	153	63.2	35	70 dia. 0 -0.03	80	90	8	6	19 dia. 0 -0.013	3	24	6 0 -0.03	2.5 0 -0.2	6		2.9	3.9

Models without brake



Models with brake





Shaft end



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Type 3000 r/min motors (230 V, 1 kW to 1.5 kW / 400 V, 750 W to 3 kW)

Dimensions (mm)	Without brake				With brake				LR	Flange surface						Shaft end						Approx. mass (kg)	
Model: R88M-1□	LL	KB1	KB2	KL1	LL	KB1	KB2	KL1		LB	LC	LD	LE	LG	LZ	S	QA	QK	W	U	T	Tap x depth	Without brake	With brake
L1K030(H/T)-□S2	168	85	153	97	209	85	194	97	55	95 dia. $^{0}_{-0.035}$	100	115	3	10	9	19 dia. $^{0}_{-0.013}$	3	42	6 $^{0}_{-0.03}$	2.5 $^{0}_{-0.2}$	6	M5 x 12L	5.7	7.4
L1K530(H/T)-□S2																								
L75030C-□S2	139	56	124		180	56	165	104															4.1	5.8
L1K030C-□S2	168	85	153		209	85	194																5.7	7.4
L1K530C-□S2																								
L2K030C-□S2	179	96	164		220	96	205																6.4	8.1
L3K030C-□S2	184	112	169	116	230	112	215	119		110 dia. $^{0}_{-0.035}$	130	145	4	12	9	22 dia. $^{0}_{-0.013}$			8 $^{0}_{-0.036}$	3 $^{0}_{-0.4}$	7		11.5	12.5

Models without brake



Models with brake





Shaft end



Type 3000 r/min motors (400 V, 4 kW to 5 kW)

Dimensions (mm)	Without brake		With brake		Approx. mass (kg)	
Model: R88M-1□	LL	KB1	LL	KB1	Without brake	With brake
L4K030C-□S2	208	128	251	128	13.5	16.0
L5K030C-□S2	232	152	275	152	16.0	18.5

Models without brake



Models with brake





Shaft end



Type 2000 r/min motors (400 V, 400 W to 600 W)

Dimensions (mm)	Without brake				With brake				Approx. mass (kg)	
Model: R88M-1□	LL	KB1	KB2	KL1	LL	KB1	KB2	KL1	Without brake	With brake
M40020C-□S2	134.8	52	120.5	97	152.3	52	138	104	3.9	4.8
M60020C-□S2	151.8	69	137.5		169.3	69	155		4.7	5.8

Models without brake



Models with brake





Shaft end



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

OMRON

Type 2000 r/min motors (230 V, 1 kW to 1.5 kW / 400 V, 1 kW to 3 kW)

Dimensions (mm)	Without brake					With brake					LR	Shaft end							Approx. mass (kg)	
Model: R88M-1□	LL	KB1	KB2	KL1	KL2	LL	KB1	KB2	KL1	KL2		S	Q	QA	QK	W	U	T	Tap x depth	Without brake	With brake
M1K020(H/T)-□S2	120.5	63	109	76	118	162	63	149	76	118	55	22 dia. $^{0}_{-0.013}$	50	3	42	8 $^{0}_{-0.036}$	3 $^{0}_{-0.4}$	7	M5 x 12L	6.6	8.6
M1K520(H/T)-□S2	138	79	125			179	79	166												8.5	10.5
M1K020C-□S2	120.5	63	109			162	64	150		119										6.6	8.6
M1K520C-□S2	138	79	125			179	81	167												8.5	10.5
M2K020C-□S2	160	98	148			201	99	189												10.0	12.0
M3K020C-□S2	191	119	176	45	116	234	118	219	45	119	65	24 dia. $^{0}_{-0.013}$	60		52				M8 x 20L	12.0	15.0



Type 1500 r/min motors (400 V, 4 kW)

Dimensions (mm)	Without brake		With brake		Approx. mass (kg)	
Model: R88M-1□	LL	KB1	LL	KB1	Without brake	With brake
M4K015C-□S2	176	102	223	102	21.0	26.0



Type 1500 r/min motors (400 V, 5.5 kW to 7.5 kW)

Dimensions (mm)	Without brake		With brake		Approx. mass (kg)	
Model: R88M-1□	LL	KB1	LL	KB1	Without brake	With brake
M5K515C-□S2	248	174	295	174	29.0	34.0
M7K515C-□S2	295	221	352	221	39.0	45.0



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Type 1500 r/min motors (400 V, 11 kW to 15 kW)

Dimensions (mm)	Without brake			With brake		Approx. mass (kg)	
Model: R88M-1□	LL	L2	KB1	LL	KB1	Without brake	With brake
M11K015C-□S2	319	330	249	382	249	63.0	73.0
M15K015C-□S2	397	408	327	493	327	85.0	99.0

Models without brake



Models with brake





Shaft end



Type 1000 r/min motors (230 V, 900 W / 400 V, 900 W)

Dimensions (mm)	Without brake					With brake					Approx. mass (kg)	
Model: R88M-1□	LL	KB1	KB2	KL1	KL2	LL	KB1	KB2	KL1	KL2	Without brake	With brake
M90010T-□S2	138	79	125	76	118	179	79	166	76	118	8.5	10.5
M90010C-□S2							81	167		117		

Models without brake



Models with brake





Shaft end



Type 1000 r/min motors (400 V, 2 kW)

Dimensions (mm)	Without brake					With brake					Approx. mass (kg)	
Model: R88M-1□	LL	KB1	KB2	KL1	KL2	LL	KB1	KB2	KL1	KL2	Without brake	With brake
M2K010C-□S2	159	93	145	45	141	206	92	191	45	144	18.0	22.0

Models without brake



Models with brake





Shaft end



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

OMRON

Type 1000 r/min motors (400 V, 3 kW)

Dimensions (mm)	Without brake					With brake					Approx. mass (kg)	
Model: R88M-1□	LL	KB1	KB2	KL1	KL2	LL	KB1	KB2	KL1	KL2	Without brake	With brake
M3K010C-□S2	228	162	213	45	141	274	162	260	45	144	28.0	33.0

Models without brake



Models with brake





Shaft end



DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Ordering information

(Refer to servo drive chapter)

② Drive options



1S servo drive

1S servo motor (Flange size 80 mm or less)





① 3000 rpm (50 W - 750 W)

1S servo motor (Flange size 100 mm or more)





① 3000 rpm (1 kW - 5 kW)
2000 rpm (400 W - 3 kW)
1500 rpm (4 kW - 15 kW)
1000 rpm (900 W - 3 kW)

Servo motors

① Select motor from R88M-1□ family using motor tables in next pages.

Servo drives

② Refer to the 1S servo drive chapter for detailed drive specifications and selection of drive accessories.

Servo motors

Servo motors 3000 r/min (100 W to 5 kW)

Symbol	Specifications						Model	Compatible 1S servo drive
	Voltage	Encoder and design		Rated torque	Capacity	Flange size		
①	230 V	Incremental encoder (23-bit) Straight shaft with key and tap	Without brake	0.318 Nm	100 W	40 mm	R88M-1M10030H-S2	R88D-1SN01H-ECT
				0.637 Nm	200 W	60 mm	R88M-1M20030H-S2	R88D-1SN02H-ECT
				1.27 Nm	400 W		R88M-1M40030H-S2	R88D-1SN04H-ECT
				2.39 Nm	750 W	80 mm	R88M-1M75030H-S2	R88D-1SN08H-ECT
				3.18 Nm	1 kW	100 mm	R88M-1L1K030H-S2	R88D-1SN15H-ECT
				4.77 Nm	1.5 kW		R88M-1L1K530H-S2	R88D-1SN15H-ECT
			With brake	0.318 Nm	100 W	40 mm	R88M-1M10030H-BS2	R88D-1SN01H-ECT
				0.637 Nm	200 W	60 mm	R88M-1M20030H-BS2	R88D-1SN02H-ECT
				1.27 Nm	400 W		R88M-1M40030H-BS2	R88D-1SN04H-ECT
				2.39 Nm	750 W	80 mm	R88M-1M75030H-BS2	R88D-1SN08H-ECT
				3.18 Nm	1 kW	100 mm	R88M-1L1K030H-BS2	R88D-1SN15H-ECT
				4.77 Nm	1.5 kW		R88M-1L1K530H-BS2	R88D-1SN15H-ECT
		Absolute encoder (23-bit) Straight shaft with key and tap	Without brake	0.159 Nm	50 W	40 mm	R88M-1M05030T-S2	R88D-1SN01H-ECT
				0.318 Nm	100 W		R88M-1M10030T-S2	R88D-1SN01H-ECT
				0.637 Nm	200 W	60 mm	R88M-1M20030T-S2	R88D-1SN02H-ECT
				1.27 Nm	400 W		R88M-1M40030T-S2	R88D-1SN04H-ECT
				2.39 Nm	750 W	80 mm	R88M-1M75030T-S2	R88D-1SN08H-ECT
				3.18 Nm	1 kW	100 mm	R88M-1L1K030T-S2	R88D-1SN15H-ECT
				4.77 Nm	1.5 kW		R88M-1L1K530T-S2	R88D-1SN15H-ECT
			With brake	0.159 Nm	50 W	40 mm	R88M-1M05030T-BS2	R88D-1SN01H-ECT
				0.318 Nm	100 W		R88M-1M10030T-BS2	R88D-1SN01H-ECT
				0.637 Nm	200 W	60 mm	R88M-1M20030T-BS2	R88D-1SN02H-ECT
				1.27 Nm	400 W		R88M-1M40030T-BS2	R88D-1SN04H-ECT
				2.39 Nm	750 W	80 mm	R88M-1M75030T-BS2	R88D-1SN08H-ECT
				3.18 Nm	1 kW	100 mm	R88M-1L1K030T-BS2	R88D-1SN15H-ECT
				4.77 Nm	1.5 kW		R88M-1L1K530T-BS2	R88D-1SN15H-ECT

DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Symbol	Specifications						Model	Compatible 1S servo drive
	Voltage	Encoder and design		Rated torque	Capacity	Flange size		
①	400 V	Absolute encoder (23-bit) Straight shaft with key and tap	Without brake	2.39 Nm	750 W	100 mm	R88M-1L75030C-S2	R88D-1SN10F-ECT
				3.18 Nm	1 kW		R88M-1L1K030C-S2	R88D-1SN10F-ECT
				4.77 Nm	1.5 kW		R88M-1L1K530C-S2	R88D-1SN15F-ECT
				6.37 Nm	2 kW		R88M-1L2K030C-S2	R88D-1SN20F-ECT
				9.55 Nm	3 kW	130 mm	R88M-1L3K030C-S2	R88D-1SN30F-ECT
				12.7 Nm	4 kW		R88M-1L4K030C-S2	R88D-1SN55F-ECT
				15.9 Nm	5 kW		R88M-1L5K030C-S2	R88D-1SN55F-ECT
			With brake	2.39 Nm	750 W	100 mm	R88M-1L75030C-BS2	R88D-1SN10F-ECT
				3.18 Nm	1 kW		R88M-1L1K030C-BS2	R88D-1SN10F-ECT
				4.77 Nm	1.5 kW		R88M-1L1K530C-BS2	R88D-1SN15F-ECT
				6.37 Nm	2 kW		R88M-1L2K030C-BS2	R88D-1SN20F-ECT
				9.55 Nm	3 kW	130 mm	R88M-1L3K030C-BS2	R88D-1SN30F-ECT
				12.7 Nm	4 kW		R88M-1L4K030C-BS2	R88D-1SN55F-ECT
				15.9 Nm	5 kW		R88M-1L5K030C-BS2	R88D-1SN55F-ECT

Servo motors 2000 r/min (400 W to 3 kW)

Symbol	Specifications						Model	Compatible 1S servo drive
	Voltage	Encoder and design		Rated torque	Capacity	Flange size		
①	230 V	Incremental encoder (23-bit) Straight shaft with key and tap	Without brake	4.77 Nm	1 kW	130 mm	R88M-1M1K020H-S2	R88D-1SN15H-ECT
				7.16 Nm	1.5 kW		R88M-1M1K520H-S2	R88D-1SN15H-ECT
			With brake	4.77 Nm	1 kW		R88M-1M1K020H-BS2	R88D-1SN15H-ECT
				7.16 Nm	1.5 kW		R88M-1M1K520H-BS2	R88D-1SN15H-ECT
		Absolute encoder (23-bit) Straight shaft with key and tap	Without brake	4.77 Nm	1 kW		R88M-1M1K020T-S2	R88D-1SN15H-ECT
				7.16 Nm	1.5 kW		R88M-1M1K520T-S2	R88D-1SN15H-ECT
			With brake	4.77 Nm	1 kW		R88M-1M1K020T-BS2	R88D-1SN15H-ECT
				7.16 Nm	1.5 kW		R88M-1M1K520T-BS2	R88D-1SN15H-ECT
	400 V		Without brake	1.91 Nm	400 W	100 mm	R88M-1M40020C-S2	R88D-1SN06F-ECT
				2.86 Nm	600 W		R88M-1M60020C-S2	R88D-1SN06F-ECT
				4.77 Nm	1 kW	130 mm	R88M-1M1K020C-S2	R88D-1SN10F-ECT
				7.16 Nm	1.5 kW		R88M-1M1K520C-S2	R88D-1SN15F-ECT
				9.55 Nm	2 kW		R88M-1M2K020C-S2	R88D-1SN20F-ECT
				14.3 Nm	3 kW		R88M-1M3K020C-S2	R88D-1SN30F-ECT
			With brake	1.91 Nm	400 W	100 mm	R88M-1M40020C-BS2	R88D-1SN06F-ECT
				2.86 Nm	600 W		R88M-1M60020C-BS2	R88D-1SN06F-ECT
				4.77 Nm	1 kW	130 mm	R88M-1M1K020C-BS2	R88D-1SN10F-ECT
				7.16 Nm	1.5 kW		R88M-1M1K520C-BS2	R88D-1SN15F-ECT
				9.55 Nm	2 kW		R88M-1M2K020C-BS2	R88D-1SN20F-ECT
				14.3 Nm	3 kW		R88M-1M3K020C-BS2	R88D-1SN30F-ECT

Servo motors 1500 r/min (4 kW to 15 kW)

Symbol	Specifications						Model	Compatible 1S servo drive
	Voltage	Encoder and design		Rated torque	Capacity	Flange size		
①	400 V	Absolute encoder (23-bit) Straight shaft with key and tap	Without brake	25.5 Nm	4 kW	180 mm	R88M-1M4K015C-S2	R88D-1SN55F-ECT
				35 Nm	5.5 kW		R88M-1M5K515C-S2	R88D-1SN55F-ECT
				47.8 Nm	7.5 kW		R88M-1M7K515C-S2	R88D-1SN75F-ECT
				70 Nm	11 kW	220 mm	R88M-1M11K015C-S2	R88D-1SN150F-ECT
				95.5 Nm	15 kW		R88M-1M15K015C-S2	R88D-1SN150F-ECT
			With brake	25.5 Nm	4 kW	180 mm	R88M-1M4K015C-BS2	R88D-1SN55F-ECT
				35 Nm	5.5 kW		R88M-1M5K515C-BS2	R88D-1SN55F-ECT
				47.8 Nm	7.5 kW		R88M-1M7K515C-BS2	R88D-1SN75F-ECT
				70 Nm	11 kW	220 mm	R88M-1M11K015C-BS2	R88D-1SN150F-ECT
				95.5 Nm	15 kW		R88M-1M15K015C-BS2	R88D-1SN150F-ECT

Servo motors 1000 r/min (900 W to 3 kW)

Symbol	Specifications						Model	Compatible 1S servo drive
	Voltage	Encoder and design		Rated torque	Capacity	Flange size		
①	230 V	Absolute encoder (23-bit) Straight shaft with key and tap	Without brake	8.59 Nm	900 W	130 mm	R88M-1M90010T-S2	R88D-1SN15H-ECT
			With brake	8.59 Nm	900 W		R88M-1M90010T-BS2	R88D-1SN15H-ECT
	400 V		Without brake	8.59 Nm	900 W		R88M-1M90010C-S2	R88D-1SN10F-ECT
				19.1 Nm	2 kW	180 mm	R88M-1M2K010C-S2	R88D-1SN20F-ECT
				28.7 Nm	3 kW		R88M-1M3K010C-S2	R88D-1SN30F-ECT
			With brake	8.59 Nm	900 W	130 mm	R88M-1M90010C-BS2	R88D-1SN10F-ECT
				19.1 Nm	2 kW	180 mm	R88M-1M2K010C-BS2	R88D-1SN20F-ECT
				28.7 Nm	3 kW		R88M-1M3K010C-BS2	R88D-1SN30F-ECT

DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Encoder cables

Symbol	Specifications		Model	Appearance
③	Encoder cable for servo motors R88M-1M05030T-□ R88M-1M(100/200/400/750)30(H/T)-□	1.5 m	R88A-CR1A001-5CF-E	
		3 m	R88A-CR1A003CF-E	
		5 m	R88A-CR1A005CF-E	
		10 m	R88A-CR1A010CF-E	
		15 m	R88A-CR1A015CF-E	
		20 m	R88A-CR1A020CF-E	
	Encoder cable for servo motors R88M-1L(1K0/1K5)30(H/T)-□ R88M-1L(750/1K0/1K5/2K0/3K0/4K0/5K0)30C-□ R88M-1M(1K0/1K5)20(H/T)-□ R88M-1M(400/600/1K0/1K5/2K0/3K0)20C-□ R88M-1M(4K0/5K5/7K5/11K0/15K0)15C-□ R88M-1M90010T-□ R88M-1M(900/2K0/3K0)10C-□	1.5 m	R88A-CR1B001-5NF-E	
		3 m	R88A-CR1B003NF-E	
		5 m	R88A-CR1B005NF-E	
		10 m	R88A-CR1B010NF-E	
		15 m	R88A-CR1B015NF-E	
		20 m	R88A-CR1B020NF-E	

Power cables

Symbol	Specifications			Model	Appearance
④	For 230 V servo motors R88M-1M05030T-□S2 **Note:** For servo motors with brake R88M-1M05030T-BS2, the separate brake cable R88A-CA1A□□□BFR is needed.	Without brake	3 m	R88A-CA1A003SFR	
			5 m	R88A-CA1A005SFR	
			10 m	R88A-CA1A010SFR	
			15 m	R88A-CA1A015SFR	
			20 m	R88A-CA1A020SFR	
	For 230 V servo motors R88M-1M(100/200/400/750)30(H/T)-□S2 **Note:** For servo motors with brake R88M-1M(100/200/400/750)30(H/T)-BS2, the separate brake cable R88A-CA1A□□□BF-E is needed.	Without brake	1.5 m	R88A-CA1A001-5SF-E	
			3 m	R88A-CA1A003SF-E	
			5 m	R88A-CA1A005SF-E	
			10 m	R88A-CA1A010SF-E	
			15 m	R88A-CA1A015SF-E	
			20 m	R88A-CA1A020SF-E	
	For 230 V servo motors R88M-1L(1K0/1K5)30(H/T)-□S2 R88M-1M(1K0/1K5)20(H/T)-□S2 R88M-1M90010T-□S2	Without brake	1.5 m	R88A-CA1C001-5SF-E	
			3 m	R88A-CA1C003SF-E	
			5 m	R88A-CA1C005SF-E	
			10 m	R88A-CA1C010SF-E	
			15 m	R88A-CA1C015SF-E	
			20 m	R88A-CA1C020SF-E	
		With brake	1.5 m	R88A-CA1C001-5BF-E	
			3 m	R88A-CA1C003BF-E	
			5 m	R88A-CA1C005BF-E	
			10 m	R88A-CA1C010BF-E	
			15 m	R88A-CA1C015BF-E	
			20 m	R88A-CA1C020BF-E	
	For 400 V servo motors R88M-1L(750/1K0/1K5/2K0)30C-□S2 R88M-1M(400/600/1K0/1K5/2K0)20C-□S2 R88M-1M90010C-□S2	Without brake	1.5 m	R88A-CA1C001-5SF-E	
			3 m	R88A-CA1C003SF-E	
			5 m	R88A-CA1C005SF-E	
			10 m	R88A-CA1C010SF-E	
			15 m	R88A-CA1C015SF-E	
			20 m	R88A-CA1C020SF-E	
		With brake	1.5 m	R88A-CA1E001-5BF-E	
			3 m	R88A-CA1E003BF-E	
			5 m	R88A-CA1E005BF-E	
			10 m	R88A-CA1E010BF-E	
			15 m	R88A-CA1E015BF-E	
			20 m	R88A-CA1E020BF-E	

DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Symbol	Specifications			Model	Appearance
④	For 400 V servo motors R88M-1L3K030C-□S2 R88M-1M3K020C-□S2 R88M-1M(2K0/3K0)10C-□S2	Without brake	1.5 m	R88A-CA1E001-5SF-E	
			3 m	R88A-CA1E003SF-E	
			5 m	R88A-CA1E005SF-E	
			10 m	R88A-CA1E010SF-E	
			15 m	R88A-CA1E015SF-E	
			20 m	R88A-CA1E020SF-E	
		With brake	1.5 m	R88A-CA1E001-5BF-E	
			3 m	R88A-CA1E003BF-E	
			5 m	R88A-CA1E005BF-E	
			10 m	R88A-CA1E010BF-E	
			15 m	R88A-CA1E015BF-E	
			20 m	R88A-CA1E020BF-E	
	For 400 V servo motors*1 R88M-1L(4K0/5K0)30C-□S2 R88M-1M(4K0/5K5)15C-□S2	Without brake	3 m	R88A-CA1G003SF	
			5 m	R88A-CA1G005SF	
			10 m	R88A-CA1G010SF	
			15 m	R88A-CA1G015SF	
			20 m	R88A-CA1G020SF	
		With brake	3 m	R88A-CA1G003BF	
			5 m	R88A-CA1G005BF	
			10 m	R88A-CA1G010BF	
			15 m	R88A-CA1G015BF	
			20 m	R88A-CA1G020BF	
	For 400 V servo motors R88M-1M7K515C-□S2	Without brake	3 m	R88A-CA1H003SF	
			5 m	R88A-CA1H005SF	
			10 m	R88A-CA1H010SF	
			15 m	R88A-CA1H015SF	
			20 m	R88A-CA1H020SF	
		With brake	3 m	R88A-CA1H003BF	
			5 m	R88A-CA1H005BF	
			10 m	R88A-CA1H010BF	
			15 m	R88A-CA1H015BF	
			20 m	R88A-CA1H020BF	
	For 400 V servo motors R88M-1M(11K0/15K0)15C-□S2	Without brake	3 m	R88A-CA1J003SF	
			5 m	R88A-CA1J005SF	
			10 m	R88A-CA1J010SF	
			15 m	R88A-CA1J015SF	
			20 m	R88A-CA1J020SF	
		With brake	3 m	R88A-CA1J003BF	
			5 m	R88A-CA1J005BF	
			10 m	R88A-CA1J010BF	
			15 m	R88A-CA1J015BF	
			20 m	R88A-CA1J020BF	

*1 Refer to the “Using R88A-CA1G power cables” technical note when using multiple cables in the same duct.

Extension power cables (for 400 V, 4 kW to 15 kW servo motors)

Symbol	Specifications		Model	Appearance
④	R88M-1L(4K0/5K0)30C-□S2 R88M-1M(4K0/5K5)15C-□S2	10 m	R88A-CA1GE10BF	
		20 m	R88A-CA1GE20BF	
	R88M-1M7K515C-□S2	10 m	R88A-CA1HE10BF	
		20 m	R88A-CA1HE20BF	
	R88M-1M(11K0/15K0)15C-□S2	10 m	R88A-CA1JE10BF	
		20 m	R88A-CA1JE20BF	

DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Combinations of Motor power cables and Extension power cables

The table below lists the combinations of cables that can be used to extend the motor power cable for a servomotor of 4 kW or more to more than 20 m.

Use the motor power cable and extension power cable in a specified combination. Not doing so may cause fire, equipment damage, or operation failure.



Length				Combination
Total	Motor power cable	Extension cable 1	Extension cable 2	
3	3	–	–	Motor power cable only
5	5	–	–	Motor power cable only
10	10	–	–	Motor power cable only
15	15	–	–	Motor power cable only
20	20	–	–	Motor power cable only
30	20	10	–	Motor power cable + extension cable 1
40	20	20	–	Motor power cable + extension cable 1
50	20	10	20	Motor power cable + extension cable 1 + extension cable 2*1

*1 A 20 m extension cable 1 and a 10 m extension cable 2 can also be used.

Brake cables (for 230 V, 50 W to 750 W servo motors)

Symbol	Specifications		Model	Appearance
⑤	Brake cable only For 230 V servo motors with brake R88M-1M05030T-BS2	3 m	R88A-CA1A003BFR	
		5 m	R88A-CA1A005BFR	
		10 m	R88A-CA1A010BFR	
		15 m	R88A-CA1A015BFR	
		20 m	R88A-CA1A020BFR	
	Brake cable only For 230 V servo motors with brake R88M-1M(100/200/400/750)30(H/T)-BS2	1.5 m	R88A-CA1A001-5BF-E	
		3 m	R88A-CA1A003BF-E	
		5 m	R88A-CA1A005BF-E	
		10 m	R88A-CA1A010BF-E	
		15 m	R88A-CA1A015BF-E	
		20 m	R88A-CA1A020BF-E	

DOWNLOADED FROM SCATTS.CO.UK

DOWNLOADED FROM SCATTS.CO.UK

Connectors for encoder, power and brake cables

Specifications		Applicable servo motor	Model
Connectors for encoder cables	Drive side (CN2)	All models	R88A-CN101R
	Motor side	R88M-1M05030T-□ R88M-1M(100/200/400/750)30(H/T)-□	R88A-CNK02R
		R88M-1L(1K0/1K5)30(H/T)-□ R88M-1L(750/1K0/1K5/2K0/3K0/4K0/5K0)30C-□ R88M-1M(1K0/1K5)20(H/T)-□ R88M-1M(400/600/1K0/1K5/2K0/3K0)20C-□ R88M-1M(4K0/5K5/7K5/11K0/15K0)15C-□ R88M-1M90010T-□ R88M-1M(900/2K0/3K0)10C-□	R88A-CN104R
Connectors for power cables	Motor side	R88M-1M(100/200/400/750)30(H/T)-_S2	R88A-CN111A
		R88M-1L(1K0/1K5)30(H/T)-S2 R88M-1M(1K0/1K5)20(H/T)-S2 R88M-1M90010T-S2 R88M-1L(750/1K0/1K5/2K0)30C-S2 R88M-1M(400/600/1K0/1K5/2K0)20C-S2 R88M-1M90010C-S2	MS3108E20-4S
		R88M-1L(1K0/1K5)30(H/T)-BS2 R88M-1M(1K0/1K5)20(H/T)-BS2 R88M-1M90010T-BS2	MS3108E20-18S
		R88M-1L3K030C-S2 R88M-1M3K020C-S2 R88M-1M(2K0/3K0)10C-S2	MS3108E22-22S
		R88M-1L(750/1K0/1K5/2K0/3K0)30C-BS2 R88M-1M(400/600/1K0/1K5/2K0/3K0)20C-BS2 R88M-1M(900/2K0/3K0)10C-BS2	MS3108E24-11S
Connectors for brake cables	Motor side	R88M-1M(100/200/400/750)30(H/T)-BS2	R88A-CN111B

Cable shield clamp (spare parts)

Applicable 1S power cable	Model
230 V, 100 W to 750 W models	R88A-SC011S-E
230 V, 1.5 kW model 400 V, 600 W to 3 kW models	R88A-SC021S-E
400 V, 5.5 kW to 15 kW models	R88A-SC10CA-PE

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.
To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

Cat. No. SysCat_I189E-EN-04C In the interest of product improvement, specifications are subject to change without notice.

DOWNLOADED FROM SCATTS.CO.UK

SCATTERGOOD & JOHNSON LTD
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS
Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk