

1231000	DATA SHEET	
valid from: 12.02.2019	ÖLFLEX® HEAT 125 SC	

Application

ÖLFLEX® HEAT 125 SC are heat resistant single cores, insulated with a cross-linked LSZH polyolefin copolymer compound with excellent fire characteristics and a wide temperature range. Typical applications are internal wiring of lamps, heating appliances, electric machines with insulation class B, switchboards and cabinets in apparatus, mechanical and plant engineering.

The product is approved by VDE and certified by DNV GL. These single cores are VDE-tested and according to this marked with <VDE>.

Design

Design	EN 50525-3-41 resp. VDE 0285-525-3-41
Certification	EN 50525-3-41 resp. VDE 0285-525-3-41 (H05Z-K, H07Z-K) Cores without approvals: X05Z-K; X07Z-K DNV GL
Conductor	fine wire strands of non-porous tinned copper acc. to IEC 60228 resp. VDE 0295, Class 5
Insulation	electron beam cross-linked polyolefin copolymer compound, halogen-free and highly flame retardant
Core identification code	individual colours

Electrical properties at 20°C

Rated voltage	U_0 / U	$\leq 1.0 \text{ mm}^2$	300 / 500 V
	U_0 / U	$\geq 1.5 \text{ mm}^2$	450 / 750 V
	U_0 / U	$\geq 1.5 \text{ mm}^2$	for fixed and protected installation: 0,6 / 1 KV
Test voltage	4000 V AC		

Mechanical and thermal properties

Minimum bending radius	occasionally flexing:	6 x outer diameter
	fixed installation:	4 x outer diameter
Temperature range	occasional flexing:	-35 °C up to +120 °C max. conductor temp. (20.000h, IEC 60216)
	fixed installation:	-55 °C up to +125 °C max. conductor temp. up to +145 °C max. conductor temp.(3000 h)
	Short circuit temperature:	+250 °C
Flammability	flame retardant acc. to	IEC 60332-1-2 no flame propagation acc. to IEC 60332-3-24 Cat. C or IEC 60332-3-25 Cat. D (for cable with OD \leq 12.0 mm) Exception: 0.5 mm ²
Halogen free	acc. to IEC 60754-1, EN 60754-1	
Corrosivity of gases	acc. to IEC 60754-2, EN 60754-2	
Smoke density	acc. to IEC 61034-2	
Toxicity	acc. to NES 02-713 (< 3), NF X 70-100 EN 50264-1 resp. VDE 0260-264-1	
UV resistance	acc. to EN ISO 4892-2-2013, method A (change of colour allowed)	
Ozone resistance	acc. to EN 50396 resp. VDE 0473-396, method B	
Oil resistance	acc. to DIN EN 50290-2-22 resp. VDE 0819-102, TM54	
Tests	acc. to IEC 60811, EN 50395	
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)	

Creator: LABU / PDC	Document: DB1231000EN	Page 1 of 1
Released: ALTE / PDC	Version: 10	

We reserve all rights according to DIN ISO 16016.

PD 0019/05_04.18EN



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk