


Accessories

D-sub-data transmission cord for ASi Master in IP65, 1,5 m



ASi Master in IP65 (Specification 2.0)

Clamps	PIN	Function	Colour
1		PE	
2		SHIELD	
3	3	BUS P	green
4	8	BUS N	yellow
5	5	GRND	blue
6		PE	
7		SHIELD	
8		BUS P	
9		BUS N	
10	6	+5 V	red

Article no. BW1097

Connection	RS 485 prefabricated cable
Storage temperature	-40°C ... +85°C
Operating temperature	-25°C ... +60°C
Protection category (IEC) EN 60529	connector IP65, plug IP20
Dimensions (L, W, H)	ca. 50 mm, 20 mm, 30 mm
Length	1,5 m


D-sub-data transmission cord 9-pin, 1,8 m



Article no. BW1058

Connection	D-Sub plug D-Sub socket
Length	1,8m
PIN 1 connected with PIN 1	

D-sub-data transmission cord for ASi Gateways with CAN interface



ASi/CAN Gateway

Clamps	PIN	Function	Colour
1		n.c.	
2	7	CAN_H	white
3		SHIELD	
4	2	CAN_L	brown
5		n.c.	

Article no. BW1226

Connection	D-subsocket, 5-pin COMBICON plug
Operating temperature	-40°C ... +85°C
Storage temperature	-25°C ... +60°C
Protection category (IEC) EN 60529	IP20
Dimensions (L, W, H)	ca. 50 mm, 20 mm, 30 mm
Length	1,5 m

Addressing plug



Article no. BW3340

Color	black
Packing unit	5 pieces

Accessories

Universal protection cap ASi-5/ASi-3 for M12 sockets, IP67



Article no. BW4056	
Color	blue
Packing unit	50 pieces

Memory plug cover



Article no. BW3155	
Color	blue
Packing unit	1 piece

Cross-Link-cable for ASi/Ethernet Gateway



Article no. BW1304

Serial cable for ASi Masters and ASi Monitors in stainless steel



Article no.	BW1575
Connection	D-Sub data cable 9-pin, Mini-Din plug 6-pin
Length	1,8 m

Accessories

USB connector cable for Safety Basic Monitor




Article no.	BW2530
Connection	USB type A – Micro USB
Length	1,8 m
Color	black

ASi Probe



Article no. BW1745

Chip card for Bihl+Wiedemann ASi products



BW2079/BW2222



BW4055

Article no.	BW2079	BW2222	BW4055
Memory capacity	32 kByte (256 kbit)	128 kByte (1024 kbit)	512 kByte (1024 kbit)
Weight	approx. 1 g		
Dimensions (L / W / H in mm)	25 / 15 / 1		
Accessories:			
• BW2079 for all ASi-3 Standard and all ASi-3 Safety products with chip card by Bihl + Wiedemann. • BW2222 for ASi-3 Safety Monitors and ASi-3 Gateways in Stainless Steel Safety Version 4.X (for maximum 4 Safety configurations on a chip card). • BW4055 for Gateways supporting ASi-5			

Memory Plug for Bihl+Wiedemann ASi products



Article no.	BW3241
Memory capacity	32 kByte (256 kbit)
Weight	approx. 2 g
Dimensions (L / W / H in mm)	26,5 / 7 / 4,5
Packing unit	10 pieces



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk