



Product: [70008PU](#)

DataTuff® 5E, 1Q #22 Str TC, PO ins, F/B, PUR HF jkt, PROFINET type C, 5M Trailing

[Request Sample](#)

Product Description

DataTuff® 5E, 1 Quad AWG 22 Tinned Copper - Stranded, Polyolefin (PO, PE, PP) insulation, Foil + Braid(s) shielding, PUR Halogen Free jacket , PROFINET type C, 5M trailing

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | Construction n x D | No. of Quads |
|-----|-----------|--------------------|--------------------|--------------|
| 22 | 19x34 | TC - Tinned Copper | 19x0.15 mm | 1 |

| | |
|------------------------|---|
| Conductor Count: | 4 |
| Total Number of Pairs: | 2 |

Insulation

| Material | Nominal Diameter | Diameter +/- Tolerance |
|-------------------|------------------|------------------------|
| PE - Polyethylene | 1.63 mm | 0.05 mm |

| | |
|--------------|----|
| Bonded-Pair: | No |
|--------------|----|

Color Chart

| Number | Color |
|--------|--------------------------------|
| Quad 1 | White & Blue & Yellow & Orange |

Inner Jacket

| Material | Nominal Diameter |
|---|------------------|
| LSZH - Low Smoke Zero Halogen (Flame Retardant) | 4.2 mm |

| | |
|--------------|---------|
| Table Notes: | Bedding |
|--------------|---------|

Outer Shield

| Type | Material | Min. Coverage [%] |
|-------|-------------------------|-------------------|
| Tape | Bi-Laminate (Alum+Poly) | |
| Braid | Tinned Copper (TC) | 85% |

Outer Jacket

| Material | Color | Nominal Diameter | Diameter +/- Tolerance | Separator Material |
|-----------------------------------|------------------|------------------|------------------------|--------------------|
| PUR - Polyurethane (Halogen Free) | Green (RAL 6018) | 6.5 mm | 0.2 mm | non-Woven Tape |

Construction and Dimensions

Cabling

| Description |
|---------------------------|
| 1 quad with center filler |

Electrical Characteristics

Conductor DCR

| Max. Conductor DCR |
|--------------------|
| |

57.1 Ohm/km

Impedance

| Frequency [MHz] | Nominal Characteristic Impedance | Nominal Characteristic Tolerance |
|-----------------|----------------------------------|----------------------------------|
| 1 - 100 | 100 Ohm | 15 Ohm |

Delay

| Max. Delay | Nominal Velocity of Propagation (VP) [%] |
|-------------|--|
| 530 ns/100m | 68% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. ACRF (ELFEXT) [dB] | Min. SRL (Structural Return Loss) |
|-----------------|-----------------------------------|----------------|-------------------------|-----------------------------------|
| 1 MHz | 2.1 dB/100m | 65 dB | 64 dB | |
| 4 MHz | 4 dB/100m | 56 dB | 52 dB | 23 dB |
| 10 MHz | 6.3 dB/100m | 50 dB | 44 dB | 25 dB |
| 16 MHz | 8 dB/100m | 47 dB | 40 dB | 25 dB |
| 31.25 MHz | 11.4 dB/100m | 43 dB | 34 dB | 23.6 dB |
| 62.5 MHz | 16.5 dB/100m | 38 dB | 28 dB | 21.5 dB |
| 100 MHz | 21.3 dB/100m | 35 dB | 24 dB | 20.1 dB |

Transfer Impedance

| Frequency [MHz] | Transfer Impedance |
|-----------------|--------------------|
| 10 Mhz | Max. 10 mOhm/m |

Voltage

| UL Voltage Rating | Voltage Rating [V] |
|-------------------|--------------------|
| 300 V | 300 V |

Temperature Range

| | |
|---------------------------------------|----------------|
| Installation Temp Range: | -5°C To +60°C |
| UL Temp Rating: | 80°C |
| Storage Temp Range: | -40°C To +80°C |
| Operating Temp Range: | -40°C to +80°C |
| Operating Temp Range (Drag Chain Op): | -5°C To +60°C |

Mechanical Characteristics

| | |
|--|--|
| Oil Resistance: | IEC 60811-2-1 |
| Torsion Test: Min Number of Torsions: | 1000000 |
| Torsion Test: Description: | +/- 180° ,12x/min over 1mtr |
| Max. Pull Tension: | 160 N |
| Min. Bend Radius During Installation: | 65 mm |
| Min. Bend Radius During Operation: | 30 mm |
| Min. Bend Radius (Continuous Flexing): | 65 mm |
| Min Setting Radius: | 30 mm |
| Min No. of Drag Chain Cycles: | 5000000 |
| Drag Chain Parameters: | a= 3m/s ² v= 3 m/s and r= 60 mm |

Standards

| | |
|--------------------------|--|
| UL AWM Style Compliance: | UL AWM 20549 |
| ISO/IEC Compliance: | ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011 |
| Data Category: | Category 5e |

Applicable Environmental and Other Programs

| | |
|----------------------|--------|
| Environmental Space: | Indoor |
|----------------------|--------|

Flammability, LS0H, Toxicity Testing

| | |
|-------------------------------|----------------------|
| UL Flammability: | Horizontal flametest |
| CSA Flammability: | FT2 |
| IEC 60754-1 - Halogen Amount: | Pass |

Related Part Numbers

Variants

| Item # | Color | Put-Up Type | Length | EAN |
|----------------|-------|-------------|---------|---------------|
| 70008PU.01B100 | Green | Flat Box | 100 m | 8719605009463 |
| 70008PU.01305 | Green | Reel | 305 m | 8719605009449 |
| 70008PU.01500 | Green | Reel | 500 m | 8719605009456 |
| 70008PU.011000 | Green | Reel | 1,000 m | 8719605009432 |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.229 Revision Date: 12-15-2021 |
|----------------------|--|

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk