



E32-ET16WR-1 2M

Fiber optic sensor, through-beam, 70mm curtain, 2m cable

Specifications

Sensing method	Through-beam
Sensing height	70 mm
Sensing distance	4000 mm
Cable length	2 m
Features	Flexible fiber, R1 Bending radius 1 mm


Fits to



E3NX-FA41 2M

Fiber amplifier, twin digital display, smart tuning, PNP, single output, 2m cable

Downloads



Fiber Optic Sensors Group Catalogue

EN PDF 7.54 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 2 March, 2022. Click here for [terms of use](#).



INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk