

# I/O module - IOL MA8 EIP DI8

1072839

<https://www.phoenixcontact.com/gb/products/1072839>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Eight-channel IO-Link master provides convenient configuration of IO-Link devices using web-based management. Supports connectivity to EtherNet/IP, MODBUS, and OPC UA. Features eight auxiliary digital inputs, redundant input power supply connections, plug-in push-in terminals.

## Product Description

Provides connectivity to EtherNet/IP, MODBUS TCP, and OPC UA networks. It enables the operation of up to eight IO-Link sensors/actuators and is also used to acquire digital signals. The device is designed for use in systems manufacturing.

## Your advantages

- Web-based management
- Eight-channel IO-Link master
- Diagnostic and status indicators
- Short-circuit and overload protection of the sensor supply
- Plug-in connection terminals, push-in connection technology
- Connections for up to 16 digital sensors

# I/O module - IOL MA8 EIP DI8



1072839

<https://www.phoenixcontact.com/gb/products/1072839>

## Commercial Data

Item number	1072839
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	DRI7PD
Product Key	DRI7PD
Catalog Page	Page 163 (C-6-2019)
GTIN	4055626766904
Weight per Piece (including packing)	371.1 g
Weight per Piece (excluding packing)	366.5 g
Customs tariff number	85176200
Country of origin	US

## I/O module - IOL MA8 EIP DI8



1072839

<https://www.phoenixcontact.com/gb/products/1072839>

## Technical Data

## Dimensions

Width	45 mm
Height	114.5 mm
Depth	99 mm

## Notes

## Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

## Material specifications

Housing material	Polyamide
Color	gray

## Interfaces

## EtherNet/IP™

No. of channels	2
Connection method	RJ45 jack
Transmission speed	10/100 Mbps (with auto negotiation)
Transmission physics	Ethernet in RJ45 twisted pair

## EtherNet/IP™

Equipment type	EtherNet/IP™ slave
----------------	--------------------

## Input data

## Digital

Input name	Digital inputs
Description of the input	IEC 61131-2 type 1
Number of inputs	8
Connection method	Push-in / plug connection
Connection technology	3-conductor
Input voltage range "0" signal	0 V DC ... 5 V DC
Input voltage range "1" signal	15 V DC ... 30 V DC
Nominal input voltage $U_{IN}$	24 V DC
Nominal input current at $U_{IN}$	typ. 3.5 mA
Input frequency	0.5 kHz
Protective circuit	Overload protection Short-circuit protection for the sensor supply

## Digital

Input name	Digital inputs
------------	----------------

## I/O module - IOL MA8 EIP DI8



1072839

<https://www.phoenixcontact.com/gb/products/1072839>

Description of the input	IO-Link ports in digital input (DI) mode
Number of inputs	max. 8 (EN 61131-2 types 1 and 3)
Connection method	Push-in / plug connection
Connection technology	3-conductor
Nominal input voltage $U_{IN}$	24 V DC
Input voltage range "0" signal	8 V DC ... 11.5 V DC (for C/Q pin)
Input voltage range "1" signal	10.5 V DC ... 13 V DC
Sensor current per channel	max. 200 mA (from L+/L-)
Total sensor current	max. 1.6 A (from L+/L-)
Protective circuit	Overload protection; yes Short-circuit protection for the sensor supply; electronic

## IO-Link

Description of the input	Digital inputs (DI)
Connection method	Push-in / plug connection
Nominal input voltage $U_{IN}$	24 V DC
Input voltage range "0" signal	5.2 V DC ... 6.4 V DC
Input voltage range "1" signal	6.8 V DC ... 8 V DC
Nominal input current	typ. 3.5 mA
Sensor current per channel	max. 200 mA (from L+/L-)
Total sensor current	max. 1.6 A (from L+/L-)
Protective circuit	Overload protection; yes Short-circuit protection for the sensor supply; yes

## IO-Link

Number of ports	8
Connection method	Push-in / plug connection
Connection technology	3-conductor

## Output data

## Digital

Maximum output current per channel	200 mA
------------------------------------	--------

## Digital

Output description	IO-Link ports in digital output (DO) mode
Connection method	Push-in / plug connection
Connection technology	3-conductor
Number of outputs	max. 8
Nominal output voltage	24 V DC
Maximum output current per channel	200 mA
Maximum output current per module	1.6 A
Nominal load, ohmic	4.8 W (120 $\Omega$ , at nominal load)
Output voltage when switched off	max. 1 V
Output current when switched off	max. 400 $\mu$ A
Protective circuit	Overload protection

## I/O module - IOL MA8 EIP DI8



1072839

<https://www.phoenixcontact.com/gb/products/1072839>

	Short-circuit protection; yes
Behavior with overload	Shutdown with automatic restart

## Product properties

Type	Block design
Product type	I/O component

## Electrical properties

## Supply: IO-Link

Nominal voltage for I/O supply	24 V DC
Nominal current for every IO-Link port	max. 200 mA (at C/Q)
	max. 200 mA (at L+/L-)
Protective circuit	Overload protection; yes
Permissible cable length	< 20 m

## Potentials

Supply voltage	24 V DC
Supply voltage range	10.8 V DC ... 30 V DC
Current draw	155 mA

## Supply: Module electronics

Supply voltage	24 V DC
Supply voltage range	18 V DC ... 30 V DC
Current consumption	3.7 A

## Supply:

Supply voltage	24 V DC
Supply voltage range	18 V DC ... 30 V DC
Current consumption	max. 3.7 A
Typical current consumption	155 mA (at 24 V DC)

## Connection data

## Conductor connection

Connection method	Push-in connection
Conductor cross section solid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 14
Stripping length	10 mm
Connection method	Push-in connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 14
Stripping length	10 mm

## Ambient conditions

# I/O module - IOL MA8 EIP DI8



1072839

<https://www.phoenixcontact.com/gb/products/1072839>

Ambient temperature (operation)	-25 °C ... 60 °C
Degree of protection	IP20
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 %
Permissible humidity (storage/transport)	10 % ... 95 %

## Mounting

Mounting type	DIN rail
---------------	----------

# I/O module - IOL MA8 EIP DI8



1072839

<https://www.phoenixcontact.com/gb/products/1072839>

## Approvals



**UL Listed**

Approval ID: FILE E 238705



**cUL Listed**

Approval ID: FILE E 238705

**cULus Listed**

# I/O module - IOL MA8 EIP DI8



1072839

<https://www.phoenixcontact.com/gb/products/1072839>

## Classifications

### ECLASS

ECLASS-9.0	27242608
ECLASS-10.0.1	27242608
ECLASS-11.0	27242608

### ETIM

ETIM 8.0	EC001604
----------	----------

### UNSPSC

UNSPSC 21.0	32151602
-------------	----------

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)



**SCATTERGOOD  
& JOHNSON LTD**  
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

**[www.scatts.co.uk](http://www.scatts.co.uk)**