

## **MALE TABS MP608/90**

### **for board mounting**

□

Male tabs have been designed to meet the increasingly stringent requirements of the market with respect to the reliability and safety of electrical connection components.

Manufactured from Brass strip P-Cu Zn 30 UNI 4895/1962 (Cu Zn 30 DIN 17660/1974 ; Cu Zn 30 NF A51-101/1977)

Type MP608D with double tab.

## MALE TABS MP608/90

### Technical characteristics

Properties	
Width	8 mm
Pack qty	5,000
Min. pack qty	100
Pin length	8.5 mm
Bending of the clamp	90°
Ø Stud mm	4 mm
Dimensional form	Male terminal
Dimensional form	Male terminal
Min operating temperature range	-40 °C
Max operating temperature range	125 °C
Material (Body)	Brass

□ □



**SCATTERGOOD  
& JOHNSON LTD**  
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

**[www.scatts.co.uk](http://www.scatts.co.uk)**