

Product datasheet

Specifications



extension ETL iTL 32 - 1P -1NO -
32A - coil 110 VDC - 230...240VAC
50/60Hz

Local distributor code: 396735746 A9C32836

Main

Range of product	Acti 9
Product or component type	Extension for impulse relay
Device short name	iETL iTL 32
Relay application	Remote control
Poles description	1P
Pole contact composition	1 NO
[In] rated current	32 A
Network type	AC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
Control type	Toggle Remote control
Control signal type	Impulse
Switching frequency	5 switching operations/minute
Impulse duration	50 ms
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
[Uc] control circuit voltage	230...240 V AC 50/60 Hz 110 V DC
Supply inrush power	19 VA
Mounting mode	Fixed, on right side of TL
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	60 mm
Width	18 mm
Depth	84 mm
Colour	White
Electrical durability	AC-21: 50000 cycles AC-22: 20000 cycles

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	Tunnel type terminals - <= 10 mm ²
Range compatibility	Acti9 iTL iTL
Product compatibility	ITL 32A

Environment

Standards	EN 669-1 EN 669-2-2
Noise level	60 dB
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	120.0 g
Package 1 Height	3.2 cm
Package 1 width	8.4 cm
Package 1 Length	9.4 cm
Unit Type of Package 2	S03
Number of Units in Package 2	72
Package 2 Weight	9.683 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	8
Package 3 Weight	1.021 kg
Package 3 Height	9 cm
Package 3 width	10 cm
Package 3 Length	26.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure[Product Environmental Profile](#)

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Halogen content performance

Halogen free plastic parts product

Contractual warranty

Warranty

18 months



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk