



## C43

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

Sample image

### IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

#### Rated insulation voltage Ui

Voltage (V)	AC / DC
690	AC

#### Rated impulse withstand voltage Uimp

Voltage (kV)	Overtoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	switch

#### Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
63	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

#### Conventional enclosed thermal current Ithe

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
63	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

#### Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-15	220 - 240	16
AC-15	380 - 440	7
AC-20A	690	63
AC-21A	20 - 690	63
AC-22A	220 - 500	63
AC-22A	660 - 690	63

#### Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	18,50
AC-2	380 - 440	3	3	30
AC-2	500 - 500	3	3	40
AC-2	660 - 690	3	3	37
AC-3	220 - 240	3	3	11
AC-3	380 - 440	3	3	18,50
AC-3	500 - 500	3	3	18,50
AC-3	660 - 690	3	3	18,50
AC-3	110 - 120	1	2	3
AC-3	220 - 240	1	2	6
AC-3	380 - 440	1	2	11
AC-4	220 - 240	3	3	5,50
AC-4	380 - 440	3	3	7,50
AC-4	500 - 500	3	3	7,50
AC-4	660 - 690	3	3	7,50
AC-4	110 - 120	1	2	1,20
AC-4	220 - 240	1	2	2,40
AC-4	380 - 440	1	2	4
AC-23A	220 - 240	3	3	15
AC-23A	380 - 440	3	3	30
AC-23A	500 - 500	3	3	45
AC-23A	660 - 690	3	3	40
AC-23A	110 - 120	1	2	4

Rated operational power				
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-23A	220 - 240	1	2	10
AC-23A	380 - 440	1	2	18,50
Max Fuse Rating IEC				
Fuse characteristic	No. of Fuses			Current (A)
gG	1			80

**UL60947-4-1 , UL508**

Rated insulation voltage Ui			
Voltage (V)		AC / DC	
600		AC	
Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
65	0 - 40	-	

**CSA**

Rated insulation voltage Ui			
Voltage (V)		AC / DC	
600		AC	
Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
65	0 - 40	-	

**GENERAL TECHNICAL INFORMATION**

Tightening torque of screws		
tightening torque (Nm)		tightening torque (lb-in)
3		26,40

Rated short-time withstand current Icw		
Time (s)	Current (A)	
1	1000	

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm <sup>2</sup> ) or (AWG/kcmil)	Material of the wire
solid wire	Min.	1	1.5mm <sup>2</sup>	Copper
solid wire	Min.	2	1.5mm <sup>2</sup>	Copper
flexible wire	Max.	2	AWG 6	Copper
flexible wire	Min.	1	4mm <sup>2</sup>	Copper
flexible wire	Min.	2	4mm <sup>2</sup>	Copper
flexible wire	Max.	2	10mm <sup>2</sup>	Copper
Single-core or stranded wire	Max.	2	AWG 6	Copper
Single-core or stranded wire	Max.	2	16mm <sup>2</sup>	Copper
flexible wire with ferrule according to DIN 46228	Min.	1	2.5mm <sup>2</sup>	Copper
flexible wire with ferrule according to DIN 46228	Min.	2	2.5mm <sup>2</sup>	Copper
flexible wire with ferrule according to DIN 46228	Max.	2	10mm <sup>2</sup>	Copper

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

**IEC 60947-3**  
**EN 60947-3**

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Power loss per pole		
		<i>Power (W)</i>
		1,70
Conditions during transport and storing		
	<i>Minimum temperature (°C)</i>	<i>Maximum temperature (°C)</i> <i>additional requirements</i>
	-40	85    In case of temperatures below -5°C no shock load permissible
Shock / Vibration		
	<i>Type of oscillation</i>	<i>Values</i>
	Resistance to shock	min. 5g, 30ms
	Resistance to vibration	IEC 61373 (1999) Category 1, Class B
General Information		
<i>Text</i>		
<ul style="list-style-type: none"> <li>- Do not lubricate or treat contacts.</li> <li>- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.</li> <li>- Use copper wire only. Do not coat the wire end with tin.</li> <li>- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.</li> <li>- Use only fully insulated cable lugs resp. FASTON receptacles.</li> <li>- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.</li> </ul>		
Operating temperature		
	<i>Min. Temperature [°C]</i>	<i>Max. Temperature [°C]</i>
	-25	60



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)