



Sample image

KG250

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
1000	AC

Rated impulse withstand voltage Uimp

Voltage (kV)	Oversvoltage category	Pollution degree	Supply system	Function
8	III	3	Valid for lines with grounded common neutral termination	switch

Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
250	50	55	Ambient temperature +50°C during 24 hours with peaks up to +55°C

Conventional enclosed thermal current Ithe

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
250	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-20A	1000	250
AC-21A	20 - 690	250
AC-22A	220 - 500	200
AC-22A	660 - 690	125

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3	220 - 240	3	3	37
AC-3	380 - 440	3	3	55
AC-3	500 - 500	3	3	75
AC-3	660 - 690	3	3	40
AC-23A	220 - 240	3	3	37
AC-23A	500 - 500	3	3	110
AC-23A	380 - 440	3	3	90
AC-23A	660 - 690	3	3	45

Max Fuse Rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	250

UL60947-4-1, UL508

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
250	0 - 40	--

General Information

Text

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

CSA

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
250	0 - 40	-	

GENERAL TECHNICAL INFORMATION

Tightening torque of screws	
tightening torque (Nm)	tightening torque (lb-in)
16	140

Rated short-time withstand current Icw	
Time (s)	Current (A)
1	4600

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
solid wire	Min.	1	16mm ²	Copper
flexible wire	Max.	1	MCM 300	Copper
flexible wire	Max.	1	150mm ²	Copper
flexible wire	Min.	1	25mm ²	Copper
Single-core or stranded wire	Max.	1	185mm ²	Copper
Single-core or stranded wire	Max.	1	MCM 350	Copper
flexible wire with sleeve	Max.	1	120mm ²	Copper
flexible wire with ferrule according to DIN 46228	Min.	1	16mm ²	Copper

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Power loss per pole	
Power (W)	
8	

Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

General Information	
Text	

- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- Use copper wire only. Do not coat the wire end with tin.
- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.

Operating temperature	
Min. Temperature [°C]	Max. Temperature [°C]
-5	55



**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk