

LED Einbauleuchte 450

LED recessed luminaire 450

LED Maschineneinbauleuchte mit 24V Betriebsspannung
LED recessed machine luminaire with 24V operating voltage




Einbauwandstärke: ≤ 3mm
Installation wall thickness: ≤ 3mm


Lichtverteilung | Light distribution

Lichtpunkthöhe | Light source height: 100cm

PMMA diffus | PMMA diffuse




ESG diffus | Single-pane-safety glass clear



Dimensionierung | Dimensions

Maximaler Durchmesser |
Maximum diameter: Ø 8,8 mm

Senkkopfschraube |
Countersunk screw: 90°



Technische Daten | Technical data

Leistungsaufnahme:	28W
Power consumption:	28W
Anschlusswert:	24V DC (-10%/+15%)
Connection value:	24V DC (-10%/+15%)
Anschlussart:	M12 Steckverbinder* oder 3m Kabel
Connection type:	M12 connector* or 3m cable
Gehäuse:	Aluminium eloxiert
Housing:	Anodised aluminium
Schutzart:	IP67
Protection rating:	IP67
Schutzklasse:	III
Protection class:	III
Abdeckung:	ESG klar, PMMA diffus oder ESG diffus
Cover:	PMMA diffuse, single- pane safety glass diffuse or single-pane safety glass clear
Farbtreue:	Ra / CRI ≥ 80
Colour rendering:	Ra / CRI ≥ 80
Lebensdauer:	min. 60 000h
Service life:	min. 60 000h
Lichtstrom:	ca. 3216 lm
Luminous flux:	Approx. 3216 lm
Max. Umgebungstemperatur:	-20°C / +45°C
Max. ambient temperature:	-20°C / +45°C
Belegung:	1 = DC (+) br br
Pin assignment:	2 = Eco (DC+) ws wh
	3 = DC (-) bl bl
	4 = NC

Normen / Approbationen Standards / approvals

- DIN EN 55015 (EMV)
- DIN EN 61547 (EMV)
- DIN EN 60598-1
- DIN EN 62471

Sangel-Bezeichnung Sangel description	Katalognr. Catalogue no.	Abdeckung Cover	Optik Optics	Anschlussart Connection type	Lichtfarbe Colour temperature
450 DIFF-0-3M-55	12080085	PMMA diffus PMMA diffuse	ohne Optik, 120° without optics, 120°	3m Kabel 3m cable	5.700K
450 ESGd-0-3M-55	12080086	ESG diffus Single-pane safety glass diffuse	ohne Optik, 120° without optics, 120°	3m Kabel 3m cable	5.700K
450 ESGk-0-3M-55	12080087	ESG klar Single-pane safety glass clear	ohne Optik, 120° without optics, 120°	3m Kabel 3m cable	5.700K
450 DIFF-0-M12-55	12080088	PMMA diffus PMMA diffuse	ohne Optik, 120° without optics, 120°	M12 Steckverbinder* M12 connector*	5.700K
450 ESGd-0-M12-55	12080089	ESG diffus Single-pane safety glass diffuse	ohne Optik, 120° without optics, 120°	M12 Steckverbinder* M12 connector*	5.700K
450 ESGk-0-M12-55	12080090	ESG klar Single-pane safety glass clear	ohne Optik, 120° without optics, 120°	M12 Steckverbinder* M12 connector*	5.700K
450 DIFF-0-3M-40	12080091	PMMA diffus PMMA diffuse	ohne Optik, 120° without optics, 120°	3m Kabel 3m cable	4.000K
450 ESGd-0-3M-40	12080092	ESG diffus Single-pane safety glass diffuse	ohne Optik, 120° without optics, 120°	3m Kabel 3m cable	4.000K
450 ESGk-0-3M-40	12080093	ESG klar Single-pane safety glass clear	ohne Optik, 120° without optics, 120°	3m Kabel 3m cable	4.000K
450 DIFF-0-M12-40	12080094	PMMA diffus PMMA diffuse	ohne Optik, 120° without optics, 120°	M12 Steckverbinder* M12 connector*	4.000K
450 ESGd-0-M12-40	12080095	ESG diffus Single-pane safety glass diffuse	ohne Optik, 120° without optics, 120°	M12 Steckverbinder* M12 connector*	4.000K
450 ESGk-0-M12-40	12080096	ESG klar Single-pane safety glass clear	ohne Optik, 120° without optics, 120°	M12 Steckverbinder* M12 connector*	4.000K

*Die passenden Anschlussleitungen finden Sie auf Seite 73. | The corresponding connection cables can be found on page 73.

Technische Änderungen vorbehalten. Lichtstrom und Lichtfarbe können variieren.
Subject to technical changes. The luminous flux and colour temperature may vary.

SANGEL[®]
Systemtechnik



**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk