



## INSULATED CHAIN TERMINALS WITH EASY ENTRY "CP" RANGE


















### GENERAL INFORMATIONS

- The terminals are for use for internal wiring of equipment only.
  - The terminals are for use with Cu wire.
  - 600V max. building wiring, 1000V max. in sign and fixtures.
  - The maximum operating temperature is 105°C.
  - Manufactured from electrolytic copper strip, annealed to guarantee optimum ductility and electrolytically tin plated to avoid oxidation.
  - Developed for use with production machinery, to give a quick and reliable crimped joint.
  - The unique shape of PC sleeve, a halogen free self extinguishing plastic material, guarantees total insertion of the conductor strands into the terminal barrel.
  - The internal surface of barrel is rifled to improve contact with conductor strands when crimped and to increase tensile strength.
- The CP range of terminals offers a wide selection of rings, forks, pins and blades, designed to meet ever changing requirements of the end users.

### INSTALLATION INSTRUCTIONS

- 1) Select the proper connector for the wire size used.
- 2) Select the proper applicator head as indicated in the table below.
- 3) Strip the cable insulation, to expose a length of conductor as recommended in the table below, taking care not to damage or cut any of the strands.
- 4) Crimp the connector as indicated in the operation and maintenance manual of the tool.

CATALOG NUMBER	TYPE	SLEEVE COLOR CODE	STUD SIZE	CONDUCTOR mm <sup>2</sup> (AWG) 	CABLE STRIP LENGTH mm 	INSTALLATION TOOLING & DIE
CRP-M3		RED	M3	0.25 ÷ 1.5 (22 ÷ 16)	5 ÷ 6	ELB-2 ELB-3 ELB-3Y BENCH PRESS & RA-2 RA-3 APPLICATOR HEAD
CRP-M3,5			M3,5			
CRP-M3,5/1			M3,5			
CRP-M4			M4			
CRP-M4/3			M4			
CRP-M5			M5			
CRP-M6			M6			
CRP-M6/1			M6			
CRP-M7			M7			
CRP-M8			M8			
CRP-U3		RED	M3			
CRP-U3,5			M3,5			
CRP-U3,5/2			M3,5			
CRP-U4			M4			
CRP-U4/1			M4			
CRP-U4/2			M4			
CRP-U5			M5			
CRP-U6			M6			
CRP-U6/1		RED	M6			
CRP-U8			M8			
CRP-P8		RED	M8			
CRP-P10						
CRP-P12						
CRP-PP12						
CRP-PP12/1		RED	M12			
CRP-PP12/23						
CRP-PP14						

CATALOG NUMBER	TYPE	SLEEVE COLOR CODE	STUD SIZE	CONDUCTOR mm <sup>2</sup> (AWG)	CABLE STRIP LENGTH mm	INSTALLATION TOOLING & DIE				
CBP-M3		BLUE	M3	1.5 ÷ 2.5 (16 ÷ 14)	5 ÷ 6	ELB-2 ELB-3 ELB-3Y BENCH PRESS & BA-2 BA-3 APPLICATOR HEAD				
CBP-M3,5			M3,5							
CBP-M3,5/1			M3,5							
CBP-M4			M4							
CBP-M5			M5							
CBP-M6			M6							
CBP-M6/1			M6							
CBP-M7			M7							
CBP-M8	M8									
CBP-U3			M3							
CBP-U3,5			M3,5							
CBP-U4			M4							
CBP-U4/1			M4							
CBP-U4/2			M4							
CBP-U5			M5							
CBP-U6	M6									
CBP-P8										
CBP-P10										
CBP-P12										
CBP-PP12										
CBP-PP12/25										
CGP-M3			YELLOW				M3	4 ÷ 6 (12 ÷ 10)	8 ÷ 9	ELB-2 ELB-3 ELB-3Y BENCH PRESS & GA-2 GA-3 APPLICATOR HEAD
CGP-M3,5							M3,5			
CGP-M4							M4			
CGP-M5		M5								
CGP-M6		M6								
CGP-M6/1		M6								
CGP-M7		M7								
CGP-M8		M8								
CGP-M8/1	M8									
CGP-U3,5		M3,5								
CGP-U4		M4								
CGP-U5		M5								
CGP-U6		M6								
CGP-P10										
CGP-P12										
CGP-P14										
CGP-PP12										
CGP-PP17										



www.cembre.com



**CEMBRE S.p.A.**  
via Serenissima, 9  
25135 Brescia  
Italy  
Ph +39 030 36921  
ufficio.vendite@cembre.com  
sales@cembre.com

**CEMBRE Ltd.**  
Dunton Park,  
Kingsbury Road,  
Curdworth, Sutton Coldfield  
West Midlands, B76 9EB  
United Kingdom  
Ph +44 01675 470440  
sales@cembre.co.uk

**CEMBRE S.a.r.l.**  
22 Avenue Ferdinand  
de Lesseps  
91420 Morangis Cedex  
France  
Ph +33 01 60 49 11 90  
info@cembre.fr

**CEMBRE España S.L.U.**  
Calle Verano 6 y 8  
Pl Las Monjas  
28850 Torrejón de Ardoz  
Madrid - Spain  
Ph +34 91 4852580  
comercial@cembre.com

**CEMBRE GmbH**  
Geschäftsbereich  
Energie- und Bahntechnik  
Heidemannstr. 166  
80939 München  
Germany  
Ph +49 89-3580676  
info@cembre.de

**CEMBRE GmbH**  
Geschäftsbereich  
Industrie und Handel  
Boschstraße 7  
71384 Weinstadt  
Germany  
Ph +49 7151-20536-60  
info-w@cembre.de

**CEMBRE Inc.**  
Raritan Center Business Park  
300 Columbus Circle-S.F.,  
Edison, NJ 08837 USA  
Ph +1 (732) 225-7415  
sales.us@cembre.com  
Midwest Office  
1051 Perimeter Dr #610  
Schaumburg, IL 60173