



2170934	DATA SHEET	
valid from: 15.11.2021	ETHERLINE® Cat. 7 FLEX 4x2x26/7 AWG	

Application

Field of use:	Connecting cable for cabling systems acc. to ISO/IEC 11801 and EN 50173. Meeting the transmission requirements of IEC 61156-6, Category 7 and EN 50288-4-2.
Performance:	4-pair, screened foiled twisted pair cable (S/FTP), having a nominal impedance of 100 Ω, supporting a bandwidth of 10 Gbit/s (e.g. 100BASE-T, 1000BASE-T, 2.5GBASE-T, 5GBASE-T, 10GBASE-T) over up to 100 m.
Characteristics:	Flame retardant, halogen free, UV-resistant, oil resistant, abrasion resistant
Applications:	EtherCAT, EtherNet/IP and others




Design

Certification	E63634 cRUus AWM Style 21238 80°C 600V I/II A/B acc. to UL 758 & CSA C22.2 No.210
Conductor	stranded bare copper 26/7 AWG
Insulation	polyolefin (foamed) core diameter: nom. 1.00 mm
Core identification code	pair 1: white/blue, pair 2: white/orange, pair 3: white/green, pair 4: white/brown (colored ring marking on the white cores is optional)
Stranding	2 cores stranded to pair, 4 pairs stranded to bundle
Pair screen	plastic laminated aluminium foil (overlapping)
Screen	braid of tinned copper wire (coverage ca. 70 %)
Outer sheath	PUR green, similar to RAL 6018 outer diameter: 6.4 mm (± 0.3 mm)

Electrical properties at 20 °C

Loop resistance	≤ 29 Ω/100 m	
Insulation resistance	≥ 5 GΩ×km	
Mutual capacitance	nom. 46 nF/km	
Transfer impedance	1 MHz:	≤ 15 mΩ/m
	10 MHz:	≤ 10 mΩ/m
	30 MHz:	≤ 30 mΩ/m
	100 MHz:	≤ 100 mΩ/m
Coupling attenuation	30 MHz - 100 MHz:	≥ 85 dB
	100 MHz - 600 MHz:	≥ 85 - 20×log ₁₀ (f / 100)
Characteristic impedance	100 MHz:	100 Ω acc. to IEC 61156-6
Velocity of propagation	100 MHz:	0.78 c
Signal propagation time	4 MHz - 600 MHz:	≤ 480 ns/100 m
Delay skew	4 MHz - 600 MHz:	≤ 25 ns/100 m
Maximum operating voltage	EN:	100 V (not for power applications)
Rated voltage	UL:	600 V
Test voltage	core/core:	2000 V
	core/screen:	2000 V

Creator: KIOS / PDC	Document: DB2170934EN	Page 1 of 2
Released: ALTE / PDC	Version: 07	

2170934	DATA SHEET	
valid from: 15.11.2021	ETHERLINE® Cat. 7 FLEX 4x2x26/7 AWG	

Electrical transmission properties at 20°C

The transmission characteristics meet the requirements of the standards EN 50288-4-2 and IEC 61156-6 for category 7. The normative requirements for the transmission properties are shown in the following table:

f [MHz]		4	10	20	62,5	100	200	250	500	600
(max.) Attenuation	[dB/100 m]	5,5	8,5	21,1	21,7	27,8	40,1	45,3	66,2	73,3
(min.) TCL	[dB]	34	30	27	22	20	17	16	13	12,2
(min.) EL TCTL	[dB/100 m]	23	15	9	—	—	—	—	—	—
(min.) NEXT	[dB]	80	80	80	75,5	72,4	67,9	66,5	61,9	60,8
(min.) PS EL FEXT	[dB/100 m]	77	71	65	55,1	51	45	43	37	35,4
(min.) ACR-F/EL FEXT	[dB/100 m]	80	74	68	58,1	54	48	46	40	38,4
(min.) Return Loss	[dB]	23	25	25	21,5	20,1	18	17,3	17,3	17,3

Mechanical and thermal properties

Minimum bending radius	fixed:	4 × outer diameter
	occasional flexing:	10 × outer diameter
Temperature range	fixed:	-50 °C up to +80 °C
	occasional flexing:	-40 °C up to +80 °C
	UL/CSA:	80 °C
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 HFT acc. to UL 1581 §1090	
Halogen free	acc. to VDE 0472-815	
UV resistance	acc. to ISO 4892-2, method A	
Oil resistance	acc. to EN 50363-10-2	

General requirements

This cable is conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances) and the LV-Directive 2014/35/EU (Low voltage Directive).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: KIOS / PDC	Document: DB2170934EN	Page 2 of 2
Released: ALTE / PDC	Version: 07	



**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk