

REINFORCED DISCONNECT TERMINALS RKF-F

*Female connectors, fully reinforced with copper sleeve.
PA6.6 insulated terminals*

'KF-' type terminals are designed to offer improved mechanical and electrical integrity under heavy-duty application. This is achieved via a Copper sleeve located between the Brass barrel and Polyamide insulation of the terminal. The funnel shape of this sleeve is designed to provide 'easy entry' of stranded conductor by smoothing the internal path. Then, during crimping, the insulation of the conductor is integrated into the crimp due to the Copper sleeve being deformed around it to maintain the level of 'grip' required in applications subject to continuous mechanical vibrations (e.g: mobile plant, vehicles, moving components).



Technical details:

The connectors are manufactured from brass P-Cu Zn 30 UNI 4895/1962 (corresponding to: Cu Zn 30 DIN 17660/1974 ; Cu Zn 30 NF A51-101/1977) full the IEC 760 requirements

The reinforcement tube is made of copper SF Cu DIN 1787/1973, F25

Main characteristics of the PA6.6 sleeve:

- >DIELECTRIC STRENGTH (kV/mm) : >16,5
- >VOLUME RESISTIVITY (Ω/cm) : $>10^{13}$
- >MAX OPERATING TEMPERATURE ($^{\circ}C$) : 105
- >FLAMMABILITY' (UL-94) : V-2
- >DENSITY (g/cm^3) : 1,14
- >WATER ABSORPTION (%) : 1,5
- >BREAKING LOAD (N/mm^2) : 77

"KF-" type terminals can be stored at a minimum temperature not below - 40 $^{\circ}C$.

REINFORCED DISCONNECT TERMINALS RKF-F

Technical characteristics



Halogen Free	yes
Min operating temperature range	-20 °C
Max operating temperature range	105 °C
Max operating temperature range (surge)	110 °C
Dimensional form	Female terminal
Material (Body)	Electrolytically tin-plated brass
Material (Fully reinforced)	ETP Copper electrolytically tinned
Material (Partially reinforced)	Polyamide PA6.6



REINFORCED DISCONNECT TERMINALS RKF-F

List of products

RKF-F Cable type: flexible copper, Minimum section: 0.25 mm ² , Maximum section: 1.5 mm ²						
Type	Colour	Width	Height of the hooked	Pack qty	Min. pack qty	
RKF-F305	Red	2.8 mm	0.5 mm	3,500	100	
RKF-F308	Red	2.8 mm	0.8 mm	3,500	100	
RKF-F405	Red	4.8 mm	0.5 mm	3,000	100	
RKF-F408	Red	4.8 mm	0.8 mm	3,000	100	
RKF-F608	Red	6.35 mm	0.8 mm	2,500	100	

RKF-F Cable type: copper, Minimum section: 0.25 mm ² , Maximum section: 1.5 mm ²						
Type	Colour	Width	Height of the hooked	Pack qty	Min. pack qty	
RKF-F305	Red	2.8 mm	0.5 mm	3,500	100	
RKF-F308	Red	2.8 mm	0.8 mm	3,500	100	
RKF-F405	Red	4.8 mm	0.5 mm	3,000	100	
RKF-F408	Red	4.8 mm	0.8 mm	3,000	100	
RKF-F608	Red	6.35 mm	0.8 mm	2,500	100	



**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk