



LED ELN-RGBW 140 PMMA_d-M8-57

Art. Nr. 1-000000-07522

Ktl. Nr. 15071096

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	4,075W / 1,025W / 0,75W / 0,97
Lichtstrom / Luminous Flux (W/R/G/B)	317lm / 23lm / 42lm / 13lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 150, b= 185mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	nein
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,25 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	




LED ELN-RGBW 280 PMMA_d-M8-57

Art. Nr. 1-000000-06628

Ktl. Nr. 15070702

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	8,15W / 2,05W / 1,5W / 2,0W
Lichtstrom / Luminous Flux (W/R/G/B)	634lm / 45lm / 84lm / 26lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 290, b= 315mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	nein
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,33 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	




LED ELN-RGBW 560 PMMA_d-M8-57

Art. Nr. 1-000000-06629

Ktl. Nr. 15070703

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	16,3W / 4,1W / 3W / 3,9W
Lichtstrom / Luminous Flux (W/R/G/B)	1268lm / 90lm / 168lm / 51lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 570, b= 595mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	nein
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,6 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	




LED ELN-RGBW 840 PMMA_d-M8-57

Art. Nr. 1-000000-06630

Ktl. Nr. 15070704

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	24,45W / 6,15W / 4,5W / 5,9W
Lichtstrom / Luminous Flux (W/R/G/B)	1902lm / 135lm / 252lm / 77lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 850, b= 875mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	nein
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,8 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	




LED ELN-RGBW 1120 PMMA_d-M8-57

Art. Nr. 1-000000-06631

Ktl. Nr. 15070705

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	32,6W / 8,2W / 6W / 7,8W
Lichtstrom / Luminous Flux (W/R/G/B)	2536lm / 180lm / 336lm / 102lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 1130, b= 1155mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	nein
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	1 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	




LED ELN-RGBW 1400 PMMA_d-M8-57

Art. Nr. 1-000000-07478

Ktl. Nr. 15071094

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	40,75W / 10,3W / 7,5W / 9,8W
Lichtstrom / Luminous Flux (W/R/G/B)	3170lm / 225lm / 420lm / 128lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 1410, b= 1435mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	nein
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	1,4 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	




LED ELN-RGBW 140 PMMA_d-M8D-57

Art. Nr. 1-000000-07523

Ktl. Nr. 15081097

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	4,075W / 1,025W / 0,75W / 0,97
Lichtstrom / Luminous Flux (W/R/G/B)	317lm / 23lm / 42lm / 13lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 150, b= 185mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	ja
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,25 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	



LED ELN-RGBW 280 PMMA_d-M8D-57


Art. Nr. 1-000000-06632

Ktl. Nr. 15070706

SANGEL[®]
Systemtechnik


Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	8,15W / 2,05W / 1,5W / 2,0W
Lichtstrom / Luminous Flux (W/R/G/B)	634lm / 45lm / 84lm / 26lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 290, b= 315mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	ja
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,33 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar


Zubehör / Equipment




LED ELN-RGBW 560 PMMA_d-M8D-57

Art. Nr. 1-000000-06633

Ktl. Nr. 15070707

SANGEL[®]
Systemtechnik



Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	16,3W / 4,1W / 3W / 3,9W
Lichtstrom / Luminous Flux (W/R/G/B)	1268lm / 90lm / 168lm / 51lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 570, b= 595mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	ja
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,6 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	




LED ELN-RGBW 840 PMMA_d-M8D-57

Art. Nr. 1-000000-07039

Ktl. Nr. 15070918

SANGEL[®]
Systemtechnik


Lichtfarbe / Light Colour	5000 K
Schutzart / Internal Protection	IP54
Netzanschluss / Main Supply	24 V DC
Dimmbar / Dimmable	nein
Bestückt / Fitted With	LED
Schutzklasse / Protection Class	3
Leistung / Power (W/R/G/B)	24,45W / 6,15W / 4,5W / 5,9W
Lichtstrom / Luminous Flux (W/R/G/B)	1902lm / 135lm / 252lm / 77lm
Farbtreue / Colour Rendering	RA / CRI ≥80
Betriebstemperatur / Operating Temp.	-20°C / 45°C
Lebensdauer / Lifetime	min. 60000 h
Optik / Optics	120°
Maße / Dimensions	a= 850, b= 875mm
Anschluss / Connection Type	M8, 5-pol, b-codiert
Kaskadierbar / Cascadable	ja
Gehäuse / Housing	Aluminium
Gewicht(Netto) / Weight(Net)	0,8 kg
Abdeckung / Cover	PMMA
Befestigung / Fastening	drehbar
Zubehör / Equipment	





**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk