

RING TERMINAL, PRE-INSULATED WITH PVC, FOR COPPER CONDUCTORS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20 °C
Maximum operating temperature	80 °C
Threshold of operating temperature for short periods	90 °C
Spy hole	No
Narrow connection	No
Bend angle of the connection	0 °
Number of holes on the palm	1
Barrel reinforcement ring	No
Markings found	marchio di fabbrica
Conditions of use	statico, al chiuso
Type	singolo
Type of insulation	parziale
Easy insertion input	Yes
Self-extinguishing fire class according to UL 94	V0
Reinforced with anti-vibration collar	No

WEIGHT AND DIMENSIONS

Center distance between holes	0 mm
-------------------------------	------

CLASSIFICATION AND DATA ORDERING


ETIM Class 7	Solderless copper terminals for copper conductors [EC001052]
Manufactured in	Italy

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	Electrolitic copper with purity above 99,95%
Minimum thickness of the surface coating of the conducting body	3 µm
Surface treatment of the conductor body	tin plating
Insulated cover material	PVC polyvinylchloride
Annealing	Yes
Internal surface of the barrel	knurled
Halogen free	No

LOGISTIC

Type of packaging	; box
Unit in minimal packaging	100 PCE
Minimum order quantity	100 PCE
Customs code	85369010



RF-M		Insulated cover color Rosso	Range of cable cross section 0.25 ÷ 1.5 mm²														
tipo	Reference standard	Screw diameter	ØD [mm]	B [mm]	N [mm]	M [mm]	I [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	
RF-M2	UL 486A-486B; UL 486C	M2	2.2	5.6	2.8	4.5	8.7	17.3	0,657	4.2	10.1	4	5.5	1.8	4.6	3,000	
RF-M3	UL 486A-486B; UL 486C	M3	3.2	5.6	2.8	4.5	8.7	17.3	0,605	4.2	10.1	4	5.5	1.8	4.6	3,000	
RF-M3.5	UL 486A-486B; UL 486C	M3.5	3.7	5.6	2.8	4.5	8.7	17.3	0,593	4.2	10.1	4	5.5	1.8	4.6	3,000	
RF-M3.5/1	UL 486A-486B; UL 486C	M3.5	3.7	6.2	3.1	7.1	11.3	20.2	0,698	4.2	10.1	4	5.5	1.8	4.6	3,000	
RF-M4	UL 486A-486B; UL 486C	M4	4.3	7	3.5	6.5	10.7	20	0,691	4.2	10.1	4	5.5	1.8	4.6	3,000	
RF-M4/3	UL 486A-486B; UL 486C	M4	4.3	7.8	3.9	7.1	11.3	21	0,771	4.2	10.1	4	5.5	1.8	4.6	3,000	
RF-M5	UL 486A-486B; UL 486C	M5	5.3	7.8	3.9	7.1	11.3	21	0,717	4.2	10.1	4	5.5	1.8	4.6	2,500	
RF-M6	UL 486A-486B; UL 486C	M6	6.4	9.4	4.7	8.1	12.3	22.8	0,815	4.2	10.1	4	5.5	1.8	4.6	2,500	
RF-M6/1	UL 486A-486B; UL 486C	M6	6.4	12	6	10.3	14.5	26.3	1,201	4.2	10.1	4	5.5	1.8	4.6	2,000	
RF-M7	UL 486A-486B; UL 486C	M7	7.2	9.4	4.7	8.1	12.3	22.8	0,762	4.2	10.1	4	5.5	1.8	4.6	2,500	
RF-M8	UL 486A-486B; UL 486C	M8	8.4	12	6	10.3	14.5	26.3	1,041	4.2	10.1	4	5.5	1.8	4.6	2,000	
RF-M10	UL 486A-486B; UL 486C	M10	10.5	15.5	7.75	13.05	17.25	30.8	1,401	4.2	10.1	4	5.5	1.8	4.6	1,500	
RF-M12	UL 486A-486B; UL 486C	M12	13	18	9	15.5	19.7	34.5	1,603	4.2	10.1	4	5.5	1.8	4.6	1,500	

BF-M		Insulated cover color Blue	Range of cable cross section 1.5 ÷ 2.5 mm²														
tipo	Reference standard	Screw diameter	ØD [mm]	B [mm]	N [mm]	M [mm]	I [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	
BF-M2		M2	2.2	5.6	2.8	5	9.2	17.8	0,748	4.2	10.1	4.9	6.4	2.4	4.6	3,000	
BF-M3	UL 486A-486B; UL 486C	M3	3.2	5.6	2.8	5	9.2	17.8	0,731	4.2	10.1	4.9	6.4	2.4	4.6	2,500	
BF-M3.5	UL 486A-486B; UL 486C	M3.5	3.7	5.6	2.8	5	9.2	17.8	0,708	4.2	10.1	4.9	6.4	2.4	4.6	2,500	
BF-M3.5/1	UL 486A-486B; UL 486C	M3.5	3.7	6.2	3.1	6.5	10.7	19.6	0,783	4.2	10.1	4.9	6.4	2.4	4.6	2,500	
BF-M4	UL 486A-486B; UL 486C	M4	4.3	8	4	6.5	10.7	20.5	0,868	4.2	10.1	4.9	6.4	2.4	4.6	2,500	

tipo	Reference standard	Screw diameter	ØD [mm]	B [mm]	N [mm]	M [mm]	I [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
BF-M5	UL 486A-486B; UL 486C	M5	5.3	8	4	7.5	11.7	21.5	0,849	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-M6	UL 486A-486B; UL 486C	M6	6.4	9.4	4.7	8.6	12.8	23.3	0,949	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-M6/1	UL 486A-486B; UL 486C	M6	6.4	12	6	10.3	14.5	26.3	1,317	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-M6/2		M6	6.4	8.4	4.2	5.4	9.6	19.6	0,744	4.2	10.1	4.9	6.4	2.4	4.6	2,500
BF-M7	UL 486A-486B; UL 486C	M7	7.2	10	5	7.8	12	22.8	0,918	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-M8	UL 486A-486B; UL 486C	M8	8.4	12	6	10.3	14.5	26.3	1,140	4.2	10.1	4.9	6.4	2.4	4.6	1,500
BF-M10	UL 486A-486B; UL 486C	M10	10.5	15.5	7.75	13.05	17.25	30.8	1,485	4.2	10.1	4.9	6.4	2.4	4.6	1,500
BF-M12	UL 486A-486B; UL 486C	M12	13	18	9	15.5	19.7	34.5	1,712	4.2	10.1	4.9	6.4	2.4	4.6	1,000

GF-MInsulated cover color
YellowRange of cable cross section
4 ÷ 6 mm²

tipo	Reference standard	Screw diameter	ØD [mm]	B [mm]	N [mm]	M [mm]	I [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
GF-M3	UL 486A-486B; UL 486C	M3	3.2	8	4	8.1	14.5	26.2	1,928	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M3.5	UL 486A-486B; UL 486C	M3.5	3.7	8	4	8.1	14.5	26.2	1,949	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M4	UL 486A-486B; UL 486C	M4	4.3	9	4.5	8.1	14.5	26.7	1,986	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M5	UL 486A-486B; UL 486C	M5	5.3	9	4.5	8.1	14.5	26.7	1,924	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M6	UL 486A-486B; UL 486C	M6	6.4	11	5.5	11.1	17.5	30.7	2,230	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M6/1	UL 486A-486B; UL 486C	M6	6.4	11	5.5	8.1	14.5	27.7	2,040	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M7	UL 486A-486B; UL 486C	M7	7.2	11	5.5	11.1	17.5	30.7	2,170	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M8	UL 486A-486B; UL 486C	M8	8.4	13.6	6.8	12.1	18.5	33	2,479	6.4	14.1	6.6	8.1	3.6	7	800
GF-M8/1	UL 486A-486B; UL 486C	M8	8.4	11	5.5	8.1	14.5	27.8	1,824	6.4	14.1	6.6	8.1	3.6	7	1,000
GF-M10	UL 486A-486B; UL 486C	M10	10.5	13.6	6.8	12.1	18.5	33	2,218	6.4	14.1	6.6	8.1	3.6	7	800
GF-M10/1	UL 486A-486B; UL 486C	M10	10.5	15.5	7.75	13.85	20.25	35.7	2,645	6.4	14.1	6.6	8.1	3.6	7	800

tipo	Reference standard	Screw diameter	ØD [mm]	B [mm]	N [mm]	M [mm]	I [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
GF-M12	UL 486A-486B; UL 486C	M12	13	19	9.5	15.1	21.5	38.7	3,196	6.4	14.1	6.6	8.1	3.6	7	500
GF-M14	UL 486A-486B; UL 486C	M14	15	21	10.5	16.1	22.5	40.7	3,400	6.4	14.1	6.6	8.1	3.6	7	500
GF-M16	UL 486A-486B; UL 486C	M16	17	24	12.5	17.1	23.5	43.2	3,780	6.4	14.1	6.6	8.1	3.6	7	500



Via Serenissima, 9 - 25135
Brescia - ITALY

© Copyright 2020 Cembre S.p.A.



**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk