

FORK TERMINAL, PRE-INSULATED WITH PVC, FOR COPPER CONDUCTORS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20 °C
Maximum operating temperature	80 °C
Threshold of operating temperature for short periods	90 °C
Fork type	flat
Barrel reinforcement ring	No
Markings found	marchio di fabbrica
Conditions of use	statico, al chiuso
Type	singolo
Type of insulation	parziale
Easy insertion input	Yes
Self-extinguishing fire class according to UL 94	V0
Reinforced with anti-vibration collar	No

MATERIAL COMPOSITION AND TREATMENTS


Conductor body material	Electrolytic copper with purity above 99,95%
Minimum thickness of the surface coating of the conducting body	3 µm
Surface treatment of the conductor body	tin plating
Annealing	Yes
Internal surface of the barrel	knurled
Halogen free	No

LOGISTIC

Type of packaging	; box
Unit in minimal packaging	100 PCE
Minimum order quantity	100 PCE
Customs code	85369010

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Solderless copper terminals for copper conductors [EC001052]
Manufactured in	Italy



RF-U		Insulated cover color Rosso	Range of cable cross section 0.25 ÷ 1.5 mm²														
tipo	Reference standard	Insulated cover material	Screw diameter	B [mm]	M [mm]	I [mm]	D [mm]	N [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
RF-U3	UL 486A-486B; UL 486C	PVC	M3	5.5	5.5	9.7	3.2	4	19.5	0,642	4.2	10.1	4	5	1.8	4.6	3,000
RF-U3.5	UL 486A-486B; UL 486C	PVC	M3.5	6	6.5	10.7	3.7	3.8	20.3	0,663	4.2	10.1	4	5	1.8	4.6	3,000
RF-U3.5/1	UL 486A-486B; UL 486C	PVC	M3.5	7.2	6.5	10.7	3.7	3.8	20.3	0,736	4.2	10.1	4	5	1.8	4.6	3,000
RF-U3.5/2		PVC	M3.5	6.4	6.5	10.7	3.7	3.8	20.3	0,700	4.2	10.1	4	5	1.8	4.6	3,000
RF-U4	UL 486A-486B; UL 486C	PVC	M4	6.5	7.5	11.7	4.3	3.7	21.2	0,695	4.2	10.1	4	5	1.8	4.6	3,000
RF-U4/1	UL 486A-486B; UL 486C	PVC	M4	8.5	7.5	11.7	4.3	3.7	21.2	0,739	4.2	10.1	4	5	1.8	4.6	3,000
RF-U4/2	UL 486A-486B; UL 486C	PVC	M4	7.5	7.5	11.7	4.3	3.7	21.2	0,759	4.2	10.1	4	5	1.8	4.6	3,000
RF-U5	UL 486A-486B; UL 486C	PVC	M5	8.5	7.5	11.7	5.3	3.7	21.2	0,739	4.2	10.1	4	5	1.8	4.6	2,500
RF-U5/1		PVC	M5	9.4	7.5	11.7	5.3	3.7	21.2	0,793	4.2	10.1	4	5	1.8	4.6	3,000
RF-U6	UL 486A-486B; UL 486C	PVC	M6	9.4	8.1	12.3	6.4	4.7	22.8	0,790	4.2	10.1	4	5	1.8	4.6	2,000
RF-U6/1	UL 486A-486B; UL 486C	PVC	M6	12	9.2	13.4	6.4	7.1	26.4		4.2	10.1	4	5	1.8	4.6	2,000
RF-U8	UL 486A-486B; UL 486C	PVC	M8	14	10	14.2	8.4	6.3	26.4	1,310	4.2	10.1	4	5	1.8	4.6	2,000
RF-U10	UL 486A-486B; UL 486C	PVC	M10	17.5	13.05	17.25	10.5	7.7	30.8	1,583	4.2	10.1	4	5	1.8	4.6	1,500
RF-U12	UL 486A-486B; UL 486C	PVC	M12	20	15.5	19.7	13	9	34.5	1,768	4.2	10.1	4	5	1.8	4.6	1,500

BF-U		Insulated cover color Blue	Range of cable cross section 1.5 ÷ 2.5 mm²														
tipo	Reference standard	Insulated cover material	Screw diameter	B [mm]	M [mm]	I [mm]	D [mm]	N [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
BF-U3	UL 486A-486B; UL 486C	PVC polyvinylchloride	M3	5.5	5.5	9.7	3.2	4	19.5	0,741	4.2	10.1	4.9	6.4	2.4	4.6	2,500
BF-U3.5	UL 486A-486B; UL 486C	PVC polyvinylchloride	M3.5	6.4	6.5	10.7	3.7	3.8	20.3	0,795	4.2	10.1	4.9	6.4	2.4	4.6	2,500
BF-U3.5/1	UL 486A-486B; UL 486C	PVC polyvinylchloride	M3.5	7.2	6.5	10.7	3.7	3.8	20.3	0,801	4.2	10.1	4.9	6.4	2.4	4.6	3,000

tipo	Reference standard	Insulated cover material	Screw diameter	B [mm]	M [mm]	I [mm]	D [mm]	N [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
BF-U4	UL 486A-486B; UL 486C	PVC polyvinylchloride	M4	6.5	7.5	11.7	4.3	3.7	21.2	0,794	4.2	10.1	4.9	6.4	2.4	4.6	2,500
BF-U4/1	UL 486A-486B; UL 486C	PVC polyvinylchloride	M4	8.5	7.5	11.7	4.3	3.7	21.2	0,917	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-U4/2	UL 486A-486B; UL 486C	PVC polyvinylchloride	M4	7.5	7.5	11.7	4.3	3.7	21.2	0,861	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-U5	UL 486A-486B; UL 486C	PVC polyvinylchloride	M5	8.5	7.5	11.7	5.3	3.7	21.2	0,854	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-U5/2		PVC polyvinylchloride	M5	12	11.3	15.5	5.3	5	26.3	1,502	4.2	10.1	4.9	6.4	2.4	4.6	1,500
BF-U6	UL 486A-486B; UL 486C	PVC polyvinylchloride	M6	9.4	8.1	12.3	6.4	4.7	22.8	0,883	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-U6/1	UL 486A-486B; UL 486C	PVC polyvinylchloride	M6	12	9.2	13.4	6.4	7.1	26.3	1,678	4.2	10.1	4.9	6.4	2.4	4.6	2,000
BF-U8	UL 486A-486B; UL 486C	PVC polyvinylchloride	M8	14	10	14.2	8.4	6.3	26.3	1,511	4.2	10.1	4.9	6.4	2.4	4.6	1,500
BF-U10	UL 486A-486B; UL 486C	PVC polyvinylchloride	M10	17.5	13.05	17.25	10.5	7.75	30.8	1,666	4.2	10.1	4.9	6.4	2.4	4.6	1,000
BF-U12	UL 486A-486B; UL 486C	PVC polyvinylchloride	M12	20	15.5	19.7	13	9	34.5	1,947	4.2	10.1	4.9	6.4	2.4	4.6	1,000

GF-U

Insulated cover color **Yellow** Range of cable cross section **4 ÷ 6 mm²**

tipo	Reference standard	Insulated cover material	Screw diameter	B [mm]	M [mm]	I [mm]	D [mm]	N [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
GF-U3.5	UL 486A-486B; UL 486C	PVC polyvinylchloride	M3.5	7.5	8.5	14.9	3.7	3.9	26.5	1,872	6.4	14.1	6.7	8.1	3.6	7	1,000
GF-U4	UL 486A-486B; UL 486C	PVC polyvinylchloride	M4	7.5	8	14.4	4.3	4.4	26.5	1,881	6.4	14.1	6.7	8.1	3.6	7	1,000
GF-U5	UL 486A-486B; UL 486C	PVC polyvinylchloride	M5	9.5	8	14.4	5.3	4.4	26.5	1,914	6.4	14.1	6.7	8.1	3.6	7	1,000
GF-U6	UL 486A-486B; UL 486C	PVC polyvinylchloride	M6	10	11	17.4	6.4	5.5	30.6	2,072	6.4	14.1	6.7	8.1	3.6	7	1,000
GF-U8	UL 486A-486B; UL 486C	PVC polyvinylchloride	M8	13.5	12	18.4	8.4	8	34.1	2,518	6.4	14.1	6.7	8.1	3.6	7	800
GF-U10	UL 486A-486B; UL 486C	PVC polyvinylchloride	M10	15.5	13	19.4	10.5	8	35.1	2,466	6.4	14.1	6.7	8.1	3.6	7	1,000
GF-U10/1	UL 486A-486B; UL 486C	PVC polyvinylchloride	M10	17.5	13.85	20.25	10.5	7.75	35.7	2,826	6.4	14.1	6.7	8.1	3.6	7	1,000
GF-U12	UL 486A-486B; UL 486C	PVC polyvinylchloride	M12	21	15.1	21.5	13	9.5	38.7	3,368	6.4	14.1	6.7	8.1	3.6	7	500

tipo	Reference standard	Insulated cover material	Screw diameter	B [mm]	M [mm]	I [mm]	D [mm]	N [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
GF-U14	UL 486A-486B; UL 486C	PVC polyvinylchloride	M14	23	16.1	22.5	15	10.5	40.7	3,632	6.4	14.1	6.7	8.1	3.6	7	500
GF-U16	UL 486A-486B; UL 486C	PVC polyvinylchloride	M16	26	17.1	23.5	17	11.5	42.7	4,052	6.4	14.1	6.7	8.1	3.6	7	500



Via Serenissima, 9 - 25135
Brescia - ITALY

© Copyright 2020 Cembre S.p.A.



**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk