

ASCO™ Series 256/ 356 Compact Valves

2-Way & 3-Way Stainless Steel, Lead-Free Brass, and Composite Valves
1/8" – 1/4" | In-Line and Pad-Mount Designs

Applications

Compact, lightweight, and powerful fluid control products for Original Equipment Manufacturers' (OEM) systems. A wide variety of certifications, elastomers, and body materials are designed for Air, Gas, Steam, Drinking Water, and Light Oil. Ideal for Compressors, Food and Beverage, Sterilizers, HVAC, Semiconductor, and other compact fluid control applications.



Features & Benefits

Wide Variety of Pressure and Flow Ratings

- Up to 30 bar (435 psi) Operating Pressure Differential (OPD).
- Direct Acting, 0 bar (psi) Min OPD.
- Flow Kv (Cv) from 0.05 – 0.48 (0.06 – 0.56)

Easy to Install and Maintain

- Nut-for-Tube (Compression Fitting) and push-to-connect fitting options allow for quick installation
- Fully rotatable coils allow for flexible electrical connections
- Removable coils, even when the valve is under pressure

Certifications, Approvals, and Directives Met

- NSF 169
- EC 1935/ 2004 approval
- UL429 / CSA
- EPA SDWA*
- EN 60335

Optional Features

- Manual Operator
- AC/DC interchangeability of the solenoid without disassembly of the valve
- NBR, EPDM, FPM, CR70N, Ruby discs and seals
- 2-Way Composite, Lead-Free Brass*, and 316 Stainless Steel Options
- 3-Way Lead-Free Brass* and 316 Stainless Steel

Specifications

Type	2-Way				2-Way / 3-Way			3-Way	
Design	In-Line Body Design				Pad Mount			In-Line with 3rd Port in Core Tube	
Body Material	Lead-Free Brass*, 316 Stainless Steel	Composite (PPS)			Lead-Free Brass*, 316 Stainless Steel			Lead-Free Brass*, 316 Stainless Steel	
Product Look									
End Connection	Female Thread	G-Thread	Push-to-connect	Compression Fitting	Compression Fitting	Pad-Mount 2Way	Pad-Mount 3Way	3-Way 3rd Port Female Thread	3-Way 3rd Port Male Thread
Operation	Normally Open or Normally Closed				Normally Open, Normally Closed, and Universal				
Pipe Size	1/8", 1/4"	1/8"			4.5mm (0.18")			1/8", 1/4"	
Flow Kv (Cv)	0.05 - 0.48 (0.06 - 0.55)	0.066 - 0.08 (0.07 - 0.09)			0.08 - 0.18 (0.09 - 0.21)			0.05 - 0.4 (0.06 - 0.46)	
MOPD Air bar (psi)	0 - 30 (0 - 435)	0 - 10 (0 - 145)			0 - 30 (0 - 435)			0 - 15 (0 - 218)	
Wattage	3 - 9 W	3 - 3.5 W			5 - 9 W			3 - 9 W	
Electrical Connections	DIN (with or without connector), Flying Leads								

*The term "Lead-Free" for brass materials is defined by SDWA 1417 as having a maximum weighted average lead content of 0.25% across the wetted surface area.

For more information:
Emerson.com/ASCO





**SCATTERGOOD
& JOHNSON LTD**
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk