

## SAC-5P-M12MS CAN TR - Termination resistor



1507816

<https://www.phoenixcontact.com/gb/products/1507816>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Terminating resistor CANopen<sup>®</sup>/DeviceNet<sup>™</sup> M12

## Commercial data

Item number	1507816
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BF1GVX
Product key	BF1GVX
Catalog page	Page 444 (C-6-2019)
GTIN	4017918900410
Weight per piece (including packing)	11.31 g
Weight per piece (excluding packing)	8.09 g
Customs tariff number	85332100
Country of origin	DE

## SAC-5P-M12MS CAN TR - Termination resistor



1507816

<https://www.phoenixcontact.com/gb/products/1507816>

## Technical data

## Product properties

Product type	Terminal resistor
Number of positions	5
Coding	A

## Insulation characteristics

Overvoltage category	II
Degree of pollution	3

## Electrical properties

Nominal voltage $U_N$	48 V AC
	60 V DC
	5 V <sub>rms</sub>
Nominal current $I_N$	4 A
	45 mA ( $I_{eff}$ )

## General

Termination resistor	120 $\Omega$ $\pm$ 1 %
Power consumption	$\leq$ 0.25 W

## Signaling

Status display	No
Status display present	No

## Dimensions

Dimensional drawing	
Width	15 mm
Height	14.8 mm
Length	56.3 mm

## Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

## SAC-5P-M12MS CAN TR - Termination resistor



1507816

<https://www.phoenixcontact.com/gb/products/1507816>

## Connector

## Connection 1

Type	Plug straight M12
Coding type	A

## Connection 2

Type	free cable end
------	----------------

## Mechanical properties

## Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

## Environmental and real-life conditions

## Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug)

## Approvals

## National Marine Electronics Association

Certificate	approved
-------------	----------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
 Halesfield 13, Telford  
 Shropshire, TF7 4PG  
 01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product manufacturers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)