


**192T4610**

**Split-core CT TO 58 1000A/5A Class 0,5 5VA**



**Strong points**

- Compatible accuracy class
- Wide range of ratings and dimensions
- Quick and easy to install

**General characteristics**

- Accuracy class: 0.2s — 0.5 or 1.
- Dielectric quality: 3 kV — 50 Hz — 1 min.
- Operating frequency: 50 — 60 Hz.
- Permanent overload: 1.2 In.
- Insulation class: E (120 °C).

**Compliance with standards**

- IEC 61869-2
- IEC 61439-1

**Access to resources (ex: manuals)**



<https://www.socomec.co.uk/en-gb/reference/192T4610>

Current transformers deliver to the secondary a standard current proportional to the primary current and adapted to the rating of the associated device. They are equipped as standard with removable terminal covers and double terminals allowing the secondary to be short-circuited without any risk.

They are mounted using two screw-on metal brackets or, in certain cases, by a clip-on DINrail fastener. The connections are made by screws or by fast-on terminals.

**----- System -----**

Fill rate E-Order Common	29
Fill rate E-Order Selection	67
<b>Classification</b>	
UNSPSC	39121032
ETIM Class	EC002048
IGCC	4186
<b>Commerce</b>	
Effective date	2004-04-29
Country of origin	HU
Discount Policy	1EA10
Discount Policy Label	CURRENT TRANSFORMER
<b>ETIM - Electrical characteristics</b>	
Rated primary current [A]	1000
Rated secondary current [A]	5
Rated secondary apparent power [VA]	5
Accuracy class	0.5
Overcurrent limiting factor	FS 5
Calibrated	No
<b>ETIM - Mechanical characteristics</b>	
With contact protection	No
Height opening [mm]	55..55
Width opening [mm]	85..85
Snap mounting	Yes
With copper rail	No
Secondary connection	Screw connection
<b>ETIM - Technical features</b>	
Model	Attachable current transformer
Number of primary inputs	1
<b>Logistics</b>	
GTIN/EAN	3596031742080
Customs number	8504318090
Price unit	PC
Weight of the packing unit	1.166
Length of the packing unit	0.16
Width of the packing unit	0.07
Depth of the packing unit	0.18
<b>Norms</b>	
Conformity to standards	IEC
<b>Technical Characteristics</b>	
Model	TO 58

Opening	55x85
Rated current	1000
Secondary rated current	5