

Eaton 106729

Catalog Number: 106729

Eaton Moeller® series LS Position switch, Rounded plunger, Basic device, expandable, 2 NC, Screw terminal, Yellow, Insulated material, -25 - +70 °C



General specifications

Product Name	Catalog Number
Eaton Moeller® series LS Position switch	106729
Model Code	EAN
LS-S02	4015081064960
Product Length/Depth	Product Height
33.5 mm	76.5 mm
Product Width	Product Weight
31 mm	0.05 kg
Certifications	Catalog Notes
CSA-C22.2 No. 14	Contacts with safety function, by positive opening to IEC/EN 60947-5-1
CE	
IEC/EN 60947-5	
UL	
UL Category Control No.: NKCR	
CSA Class No.: 3211-03	
UL 508	
UL File No.: E29184	
CSA	
CSA File No.: 012528	
IEC/EN 60947	

Type

- Position switch
- Safety position switch

Features

- Expandable
- Forced opening
- Positive opening

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

Catalogs

- [eaton-safety-switches-rs-titan-flyer-fl053001en-en-us.pdf](#)
- [eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)
- [eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

Certification reports

- [DA-DC-00004160.pdf](#)
- [DA-DC-00004133.pdf](#)

Drawings

- [eaton-position-switches-plunger-ls-dimensions-002.eps](#)
- [eaton-position-switches-plunger-ls-dimensions-004.eps](#)
- [eaton-operating-button-symbol-008.eps](#)
- [eaton-position-switches-plunger-ls-3d-drawing.eps](#)

eCAD model

- [DA-CE-ETN.LS-S02](#)

Installation instructions

- [IL053001ZU](#)

mCAD model

- [DA-CS-ls](#)
- [DA-CD-ls](#)

Wiring diagrams

- [eaton-position-switches-contact-ls-wiring-diagram-003.eps](#)

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Electric connection type

Cable entry metrical

Enclosure material finishing

Other

Operating frequency

6000 Operations/h

Pollution degree

3

Actuator alignment

Roller cam straight

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Enclosure material

Plastic

Insulated material

Enclosure type

Cuboid

Rated operational current (I_e) at DC-13, 110 V

0.6 A

Rated operational current (I_e) at DC-13, 125 V

0.8 A

Rated operational current (I_e) at DC-13, 220 V, 230 V

0.3 A

Rated operational current (I_e) at DC-13, 24 V

3 A

Rated operational current for specified heat dissipation (I_n)

6 A

Sensor height

61 mm

Sensor length

33.5 mm

Static heat dissipation, non-current-dependent P_{vs}

0 W

Width sensor

31 mm

Product category

Rounded plunger

Action

2020122120328-Mechanical Limit Switches.xlsm-Data

Rated impulse withstand voltage (U_{imp})

4000 V AC

Enclosure color

Yellow Cover

Actuating force at beginning/end of stroke

1.0 N/8.0 N

Explosion safety category for dust

None

Explosion safety category for gas

None

Actuator type

Plunger

Actuating torque of rotary drives

0.2 Nm

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Diameter sensor

0 mm

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0.17 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

2

Number of contacts (normally open contacts)

0

Number of safety auxiliary contacts

2

Rated insulation voltage (U_i)

400 V

Rated operational current (I_e) at AC-15, 125 V

6 A

Rated operational current (I_e) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (I_e) at AC-15, 24 V

6 A

Rated operational current (I_e) at AC-15, 380 V, 400 V, 415 V

4 A

Mounting position

As required

Rated conditional short-circuit current (I_q)

1 kA

Overvoltage category

III

Control circuit reliability

1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)

1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)

Connection type

Screw terminal

Temperature resistance

100 °C, Contact temperature of roller head

Degree of protection

IP66/IP67

NEMA Other

Interface type

None

Switch function type

Slow-action switch

Lifespan

8,000,000 mechanical Operations

Repetition accuracy

0.15 mm (Contacts/switching capacity)

Shock resistance

25 g, Standard-action contact, Mechanical, Half-sinusoidal shock

20 ms

Supply frequency

Max. 400 Hz, Contacts

Suitable for

Safety functions

Operating speed

For angle of actuation $\alpha = 0^\circ/30^\circ$

Max. 1/0.5 m/s (with DIN cam, mechanical actuation)

Short-circuit protection rating

Max. 6 A gG/gL, Fuse, Contacts

Terminal capacity (flexible with ferrule)

1 x (0.5 - 1.5) mm²

Terminal capacity (solid)

1 x (0.5 - 2.5) mm²



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)