



Product designation

Motor protection
circuit breaker
SM3R

Product type designation

Electrical features

Number of poles	Nr.	3
Magnetic protection		yes
Thermal protection		yes
Phase failure detection		yes
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	6
Rated frequency	Hz	50/60
Thermal trip adjustment range		80...100
Rated current (I_n)	A	100
Magnetic tripping		13 x I_n
Power dissipation per pole		

max W 7

Operational short-circuit current breaking capacity (I_{cs}) at AC

230V	kA	100
400V	kA	38
440V	kA	30
500V	kA	6
690V	kA	4

Maximum short-circuit current breaking capacity (I_{cu}) at AC

230V	kA	100
400V	kA	50
440V	kA	40
500V	kA	8
690V	kA	5

Tripping class 10A

IEC Utilization category A

Operations

Mechanical life	cycles	50000
Electrical life	cycles	25000

Mechanical features

Tightening torque for terminals

min	Nm	4.5
max	Nm	4.5
min	lbin	4.4
max	lbin	4.4

Max number of wires simultaneously connectable Nr. 2

Conductor section


AWG/Kcmil

min	18
max	3


Flexible c/w lug conductor section

	min	mm ²	10
	max	mm ²	50
Flexible with insulated spade lug conductor section			
	min	mm ²	10
	max	mm ²	50
Screwdriver			Allen 4mm
Power terminal protection according to IEC/EN 60529			IP20
Cable stripping length			
	main circuit	mm	1
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-20
	max	°C	+70
Storage temperature			
	min	°C	-50
	max	°C	+80
Compensation temperature			
	min	°C	-50
	max	°C	+40
Max altitude		m	3000
Operating position			
	normal allowable		Vertical plan Any
Fixing			Screw / DIN rail 35mm
Weight		g	2200
UL technical data			
Motor Disconnect			
	at 480V	kA	40
	at 600V	kA	10
	protection		Fuse or CB
Group Motor Installation			
	at 480V	kA	40
	at 600V	kA	10
	protection		Fuse or CB
Tap Conductor Protection			
	at 480Y/277V	kA	40
	at 600Y/347V	kA	10
UL508 / UL 60947-4-1 Manual Self Protected Combination Motor Controller (Type E) Short circuit current			
	at 240V	kA	100
	at 480Y/277V	kA	40
Maximum UL/CSA horsepower ratings single-phase			
	110V-120V	HP	10
	220V-240V	HP	20
Maximum UL/CSA horsepower ratings three-phase, 3-pole			
	200V-208V	HP	30
	220V-240V	HP	30
	440V-480V	HP	75
	550V-600V	HP	100

Dimensions [mm (in)]



Wiring diagrams



Certifications and compliance

Certifications

CSA C22.2 n° 14

IEC/EN 60947-1

IEC/EN 60947-2

IEC/EN 60947-4-1

UL508

Compliance

cULus

EAC

ETIM classification

ETIM 8.0

EC000074 -
Motor protection
circuit-breaker