



Product designation				Auxiliary contact	
Product type designation				11BGX10	
<b>Contact characteristics</b>					
Number of poles	Nr.			4	
Rated insulation voltage $U_i$ IEC/EN	V			690	
Rated impulse withstand voltage $U_{imp}$	kV			6	
IEC Conventional free air thermal current $I_{th}$	A			10	
Tightening torque for terminals	min	Nm	0.8		
	max	Nm	1		
	min	lbin	9		
	max	lbin	9		
	<hr/>				
Tightening torque for coil terminal	min	lbin	9		
	max	lbin	9		
<hr/>					
Max number of wires simultaneously connectable	Nr.			2	
Conductor section	AWG/Kcmil				
		max	12		
	<hr/>				
	Flexible w/o lug conductor section				
		min	mm <sup>2</sup>	0.75	
		max	mm <sup>2</sup>	2.5	
	<hr/>				
Flexible c/w lug conductor section					
	min	mm <sup>2</sup>	0.75		
	max	mm <sup>2</sup>	2.5		
<hr/>					
Flexible with insulated spade lug conductor section					
	min	mm <sup>2</sup>	0.75		
	max	mm <sup>2</sup>	2.5		
<hr/>					
<b>Mechanical features</b>					
Operating position	normal		On vertical plane		
	allowable		Any		
<hr/>					
Fixing				Front centre mounting	
<hr/>					
Weight				g 28	
<hr/>					
Terminals screw				Screw	
<hr/>					
Conductor section	AWG/kcmil conductor section				
		max	12		
	<hr/>				
IEC					
	max	mm <sup>2</sup>	1 or 2 x 2.5		
<hr/>					
<b>Auxiliary contact characteristics</b>					
Type of contact				1NO+3NC	
Thermal current $I_{th}$	A			10	
IEC/EN 60947-5-1 designation				A600 - Q600	

Operating current AC15

230V	A	3
400V	A	1.9
500V	A	1.4

Operating current DC13

24V	A	3
48V	A	1.5
60V	A	1.2
110V	A	0.6
125V	A	0.55
220V	A	0.27
600V	A	0.1

Electrical characteristics

Conductivity	5V 10 mA
UL/CSA and IEC/EN 60947-5-1 designation	A600 Q600

Operating current AC15

120V	A	6
240V	A	3
480V	A	1.5
600V	A	1.2

Operating current DC13

12V	A	10
250V	A	0.27
440V	A	0.15
500V	A	0.13

Ambient conditions

Temperature

Operating temperature

min	°C	-50
max	°C	+70


Storage temperature

min	°C	-60
max	°C	+80


Max altitude

m 3000

Dimensions [mm (in)]



Wiring diagrams



### Certifications and compliance

#### Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-5-1

IEC/EN 60947-1

IEC/EN 60947-5-1

UL 60947-1

UL 60947-5-1

#### Certificates

CCC

cULus

EAC

### ETIM classification

ETIM 8.0

EC000041 -  
Auxiliary contact  
block