



Residual current  
circuit breaker  
with overcurrent  
protection  
(RCBO)  
P1 RB  
1P+N  
2  
IEC

Product designation

Product type designation

Number of poles

Number of DIN modules

Compliance

**Electrical features**

Rated insulation voltage $U_i$ IEC/EN	V	400
Rated impulse withstand voltage $U_{imp}$	kV	4
Rated operational voltage AC (IEC)	VAC	230
Rated frequency	Hz	50/60
Rated current ( $I_n$ )	A	10
Tripping curve		C
Residual operation characteristic		AC
Rated residual current	mA	30
Short circuit rating (IEC)	kA	10
Power dissipation per pole max	W	1.7

**Ambient conditions**


Operating temperature	min	°C	-35
	max	°C	70
Storage temperature	min	°C	-40
	max	°C	80
Max altitude	m	2000	

**Mechanical features**


Operating position	normal	Vertical plan			
Fixing		35mm DIN rail			
Tightening torque for terminals	min	Nm	1.8		
	max	Nm	2		
	min	lbin	16		
	max	lbin	17.7		
Terminals tool		Pz 2			
Conductor section	IEC	min	mm <sup>2</sup>	1	
		max	mm <sup>2</sup>	25	
	AWG/Kcmil	min		16	
		max		3	
		Weight		g	205

Frontal IP degree	IP20
Pollution degree	2

**Dimensions [mm (in)]**



**Wiring diagrams**



**Certifications and compliance**

Compliance	IEC/EN 61009-1
Certifications	EAC TÜV-Rheinland

**ETIM classification**

ETIM 8.0	EC000905 - Earth leakage circuit breaker
----------	--