



## E2E-X20MB1TL18 2M

Proximity sensor, inductive, nickel-brass, long body, M18, unshielded, 20 mm, DC, 3-wire, PNP NO, IO-Link COM3, 2 m cable

# Specifications


<b>Size</b>	M18
<b>Mounting type</b>	Non-flush
<b>Sensing distance</b>	20 mm
<b>Overall length</b>	77.3 mm
<b>Thread length</b>	47 mm
<b>Material housing</b>	Brass, nickel plated
<b>Output type</b>	IO-Link, PNP
<b>Operation mode</b>	NO
<b>Connection method</b>	Cable
<b>Cable specifications</b>	PVC (oil-resistant)
<b>Cable length</b>	2 m
<b>IO-Link function</b>	✓
<b>IO-Link baud rate</b>	COM3 (230.4 kbps)
<b>Degree of protection (IP)</b>	IP67/IP67G/IP69K

## CAD Library



### E2E NEXT Datasheet

EN PDF 39 MB



### E2E(Q) - Basic Models Index list

EN PDF 719 KB



### E2E(Q) - Premium Models Index list

EN PDF 719 KB



### E2E[Q]-XxBxxxx IO-Link IODD file

EN ZIP 1.35 MB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### IO-Link Series Brochure

EN PDF 8.05 MB