



E2E-X40MB1TL30-M1

Proximity sensor, inductive, nickel-brass, long body, M30, unshielded, 40 mm, DC, 3-wire, PNP NO, IO-Link COM3, M12 connector

Specifications

| | |
|---------------------------|----------------------|
| Size | M30 |
| Mounting type | Non-flush |
| Sensing distance | 40 mm |
| Overall length | 80 mm |
| Thread length | 50 mm |
| Material housing | Brass, nickel plated |
| Output type | IO-Link, PNP |
| Operation mode | NO |
| Connection method | Connector M12 |
| Cable specifications | - |
| IO-Link function | ✓ |
| IO-Link baud rate | COM3 (230.4 kbps) |
| Degree of protection (IP) | IP67/IP69K |

Related products



M12 Connectors & Cordsets


Industrial connectors & cordsets for any application

CAD Library



E2E NEXT Datasheet

EN PDF 39 MB



E2E(Q) - Basic Models Index list

EN PDF 719 KB



E2E(Q) - Premium Models Index list

EN PDF 719 KB



E2E[Q]-XxBxxxx IO-Link IODD file

EN ZIP 1.35 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 8.05 MB