



E3AS-HL500MT 2M

Photoelectric sensor, rectangular housing, stainless steel, red laser class 1, background suppression, spot beam, 35-500 mm, 10-30 VDC, PNP, Light-ON/Dark-ON, IO-Link COM3, 2 m cable

Specifications

Shape	Cuboid
Sensing method	Background suppression
Sensing distance	500 mm
Sensing distance (min.)	35 mm
Setting method	IO-Link, Teach-In
Connection method	Cable
Cable length	2 m
Output type	IO-Link, PNP
Operation mode	Dark-ON, Light-ON
IO-Link baud rate	COM3 (230.4 kbps)
Response time	1.5 ms
Material housing	Stainless steel
Product Width (unpacked)	15.5 mm
Product Height (unpacked)	48.6 mm
Product Depth (unpacked)	30.4 mm
Type of light	Laser diode, red light
Laser class	1
Spot size	2.5 mm x 1.5 mm
Power supply voltage	10-30 V
Functions	Timer
Degree of protection (IP)	IP67/IP67G/IP69K



E39-E16

Air blow unit



E39-E19

Front protection cover for E3AS-HL



E39-L221

L-shaped mounting bracket



E39-L222

Horizontal protective cover bracket



E39-L223

Rear mounting bracket



E39-L224

Robust mounting bracket



E39-L261

Flexible mounting bracket



E39-L262

50mm post for flexible mounting bracket E39-L261



E39-L263

100mm post for flexible mounting bracket E39-L261

CAD Library



E3AS – Automotive Brochure

EN PDF 18.7 MB



E3AS – Food & Commodities Datasheet

EN PDF 18.1 MB



E3AS-HL Instruction Sheet

EN PDF 7.9 MB



E3AS-HL Index list

EN PDF 1.34 MB



E3AS-HL Distance-settable Photoelectric Sensors Datasheet

EN PDF 5.11 MB



E3AS-HLxxx[x]xx IO-Link IODD file

EN ZIP 1.15 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 8.05 MB