

# Eaton 102158

Catalog Number: 102158

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 2-pole, tripping characteristic: C, rated current In: 1 A, Switchgear for export to North America (UL-listed)



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB	102158
	<b>Model Code</b>
	FAZ-C1/2-NA
<b>EAN</b>	<b>Product Length/Depth</b>
4015081020348	105 mm
<b>Product Height</b>	<b>Product Width</b>
75.5 mm	35.4 mm
<b>Product Weight</b>	<b>Compliances</b>
0.244 kg	RoHS conform

## Certifications

CSA (File No. 204453)  
CSA (Class No. 1432-01)  
IEC/EN 60947-2  
UL 489, CSA C22.2 No. 5  
UL (Category Control Number DIVQ)  
North America (UL listed, CSA certified)  
CE marking  
IEC 60947-2  
UL 489  
Specially designed for North America,  
suitable as BCPD  
CSA-C22.2 No. 5-09  
UL (File No. E235139)  
EN45545-2  
IEC 61373

## Delivery program

### Application

Feeder circuits, branch circuits  
Switchgear for export to North America (UL-listed)

### Number of poles

Two-pole

### Number of poles (total)

2

### Number of poles (protected)

2

### Tripping characteristic

C

### Release characteristic

C

### Amperage Rating

1 A

### Type

FAZ-NA  
Miniature circuit breaker

## Technical data - electrical

### Voltage type

AC

### Voltage rating

277 V AC / 480 V AC

### Voltage rating at DC

60 V DC

### Voltage rating (IEC/EN 60947-2)

440 V

### Voltage rating (UL)

480Y/277 V

### Rated operational voltage (U<sub>e</sub>) - max

415 V

### Rated insulation voltage (U<sub>i</sub>)

440 V

### Rated impulse withstand voltage (U<sub>imp</sub>)

4 kV

### Frequency rating - min

50 Hz

### Frequency rating - max

60 Hz

### Rated switching capacity (IEC/EN 60947-2)

15 kA

### Breaking capacity

10 kA (UL489)

### Rated short-circuit breaking capacity (EN 60898) at 230 V

0 kA

### Rated short-circuit breaking capacity (EN 60898) at 400 V

0 kA

### Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

15 kA

### Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

15 kA

### Selectivity class

3

### Overvoltage category

III

Pollution degree

2

Lifespan, electrical

20000 operations

Direction of incoming supply

As required

## Technical data - mechanical

Frame

45 mm

Enclosure width

105 mm

Width in number of modular spacings

2

Built-in depth

70.5 mm

Mounting width per pole

17.7 mm

Mounting width

17.7 mm

Mounting Method

Top-hat rail IEC/EN 60715

Mounting position

As required

Degree of protection

IP40 (when fitted)

IP20

UL/CSA Type: -

IP20 (IEC)

Terminals (top and bottom)

Twin-purpose terminals

Connectable conductor cross section (solid-core) - min

1 mm<sup>2</sup>

Connectable conductor cross section (solid-core) - max

25 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - min

1 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - max

25 mm<sup>2</sup>

Terminal protection

Finger and hand touch safe, DGUV VS3, EN 50274

Tightening torque

Max. 2.4 Nm

UL: 4 Nm (36 lb-in) for AWG 6

UL: 2.4 Nm (21 lb-in) for AWG 18 - AWG 12

UL: 2.8 Nm (25 lb-in) for AWG 10 - AWG 8

## Design verification as per IEC/EN - technical data

Rated operational current for specified heat dissipation (In)

1 A

Heat dissipation per pole, current-dependent

0 W

Equipment heat dissipation, current-dependent

2.2 W

Static heat dissipation, non-current-dependent

0 W

Heat dissipation capacity

0 W

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

75 °C

## Design verification as per IEC/EN 61439

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

## Additional information

Current limiting class

3

Features

Additional equipment possible

Functions

Current limiting circuit breaker

Special features

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

Used with

FAZ-NA

Miniature circuit breaker

## Resources

Brochures

[eaton-pdd-railrolling-stock-brochure-br011002en-en-us.pdf](#)

Catalogs

[eaton-xeffect-faz-na-rt-mcb-catalog-ca003032en-en-us.pdf](#)

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### Certification reports

DA-DC-03\_FAZ-NA

DA-DC-03\_FAZ-B-C-D

### Characteristic curve

eaton-xeffect-faz-na,-mcb-characteristic-curve.jpg

eaton-xeffect-faz-na,-mcb-dimensions-005.jpg

eaton-xeffect-faz-na,-mcb-3d-drawing-002.jpg

eaton-mcb-xeffect-faz-na,-characteristic-curve.eps

eaton-xeffect-faz-na,-mcb-3d-drawing-006.jpg

eaton-xeffect-faz-na,-mcb-characteristic-curve-002.jpg

eaton-mcb-xeffect-faz-na,-characteristic-curve-002.eps

### Drawings

eaton-xeffect-faz-na,-mcb-dimensions.jpg

eaton-mcb-xeffect-faz-na,-3d-drawing-003.eps

### eCAD model

ETN.FAZ-C1\_2-NA

### Installation instructions

IL019133ZU

### mCAD model

faz\_na\_2p.dwg

faz\_na\_2p.stp

### Wiring diagrams

eaton-mcb-xeffect-faz-na,-wiring-diagram-003.eps

PLS\_2P



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)