



Fuse-link, LV, 32 A, AC 500 V, BS88/A2, 22 x 85 mm, gM, BS, 32M35



AA032M35

General specifications		
Product name		Eaton Bussmann series low voltage british standard fuse
Part no.		AA032M35
EAN		5027590491556
Product Length/Depth		85 millimetre
Product height		21 millimetre
Product width		21 millimetre
Product weight		50.1 gram
Compliances		CE Marked RoHS Compliant
Certifications		EAC IEC 60269 BS88
Product Tradename		None
Product Type		Low voltage british standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		35 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gM
Product specifications		
Application		general industrial applications
Fuse type		AA0
Fuse size		BS88/A2
Fitted with:		Offset bolted tags
Connection		73 mm fixing centre
Compatible fuse holder		
Suitable for		CM32F Camaster fuse holder RS32 Red spot fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Fuse system E
Fuse construction type according to IEC 60269		A2
Type of current		AC
Rated voltage AC	V	500
Rated voltage DC	V	
Rated current	A	35
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M5
Centre-to-centre distance of connections	mm	73