



Fuse-link, LV, 40 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS

CE040

Similar to illustration

General specifications		
Product name		Eaton Busmann series low voltage british standard fuse
Part no.		CE040
EAN		5027590496292
Product Length/Depth		109.5 millimetre
Product height		24.5 millimetre
Product width		21 millimetre
Product weight		77.6 gram
Compliances		Contact Manufacturer
Product Tradename		None
Product Type		Low voltage british standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		40 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Product specifications		
Application		general industrial applications
Fuse type		CEO
Fuse size		BS88/A4
Fitted with:		Offset bolted tags
Connection		94 mm fixing centre
Compatible fuse holder		
Suitable for		RS100 Red spot fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Fuse system E
Fuse construction type according to IEC 60269		A4
Type of current		AC
Rated voltage AC	V	500
Rated voltage DC	V	
Rated current	A	40
Utilization category		gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	4.7
Mounting holes		M8
Centre-to-centre distance of connections	mm	94