



INFORMATION

- + Closed, permanent grip and adjustable marker sleeves.
- + For applications including electrical engineering, pneumatics and hydraulics.
- + Twist-protection for secure combination marking
- + Excellent legibility



PROPERTIES

**Temperature range**

PA: -30°C to +60°C

PAZ: -30°C to +90°C

**Material**

PA: PVC

PAZ: ZEREX (Halogen free)

**Print**

hot stamped

**Standard colours**


PA: yellow and white

international colour code for 0-9

PAZ: yellow and white


**Text**

0-9, A-Z, + - / . : ~ ↓





+ DIMENSIONS



TYPE	HEIGHT (H mm)	WIDTH (B mm)	TEXT HEIGHT [mm]
PY-01	3.3	3.5	2.6
PA-02	3.6	3.5	2.6
PA-1	5.5	4.2	2.6
PA-2	9.5	6.6	4.0
PA-3	16.5	11.0	4.0

+ SIZES AND PACKAGING

TYPE	DIAMETER / AREA*	LENGTH	NUMBER OF CHARACTERS	PACKAGING
PY-01	~1.0 - 2.0 mm ~0.2 - 0.7 mm <sup>2</sup>	3 mm	1	bag of 5x200 pcs - cut  roll of 1000 pcs.
PA-02/PAZ02	~1.3 - 3.0 mm 0.5 to 0.75 mm <sup>2</sup>	3 mm	1	bag of 5x200 pcs - cut  roll of 1000 pcs bag of 250 pcs - strips disc of 500 pcs
PA-1/PAZ1	~2.5 - 5.0 mm 0.75 to 4.0 mm <sup>2</sup>	3 mm	1	bag of 5x200 pcs - cut  roll of 1000 pcs bag of 250 pcs - strips disc of 500 pcs
PA-2/PAZ2	~4.0 - 10.0 mm 2.5 to 10.0 mm <sup>2</sup>	4 mm	1	bag of 5x100 pcs - cut  disc of 250 pcs bag of 250 pcs - strips
PA-3/PAZ3	~8.0 - 16.0 mm 16.0 to 50.0 mm <sup>2</sup>	6 mm	1	bag of 5x20 pcs - cut

\* Size shown refers to BS6231 tri-rated cable.

+ RELATED PRODUCTS

+ APPLICATION



MD/MDH  
▶ PAGE 102



CAS  
▶ PAGE 103



PUJ/MD10  
▶ PAGE 105

