



## E2E-X4C312-M1

Proximity sensor, inductive, nickel-brass, short body, M12, shielded, 4 mm, DC, 3-wire, NPN NO+NC, M12 connector

# Specifications

Size	M12
Mounting type	Quasi-flush
Sensing distance	4 mm
Overall length of sensor	48 mm
Thread length	29 mm
Material housing	Brass, nickel plated
Output type	NPN
Operation mode	NO + NC
Connection method	Connector M12
Cable specifications	-
IO-Link function	✘
Degree of protection (IP)	IP67/IP69K

# Accessories



Y92E-J12S18

Mounting Sleeves e-jig for M12 Prox

# Related products



## M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

# Downloads

CAD Library



### E2E NEXT Datasheet

EN PDF 38.9 MB



### E2E(Q) - Basic Models Index list

EN PDF 719 KB



### E2E(Q) - Premium Models Index list

EN PDF 719 KB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### IO-Link Series Brochure

EN PDF 7.5 MB

## TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 25 June, 2024. Click here for [terms of use](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU