



E3AS-F1000IMT 2M

Photoelectric sensor, rectangular housing, stainless steel, infrared laser class 1, time-of-flight, 1000 mm, PNP, Light-ON/Dark-ON, IO-Link COM3, 2 m cable

Specifications

Shape	Cuboid
Sensing method	Background suppression
Sensing distance	1000 mm
Sensing distance (min.)	50 mm
Setting method	IO-Link, Teach-In
Connection method	Cable
Cable length	2 m
Output type	IO-Link, PNP
Operation mode	Dark-ON, Light-ON
IO-Link baud rate	COM3 (230.4 kbps)
Response time	90 ms
Material housing	Stainless steel
Product Width (unpacked)	11.4 mm
Product Height (unpacked)	38 mm
Product Depth (unpacked)	22 mm
Type of light	Laser diode, infrared light
Laser class	1
Spot size	95 mm
Power supply voltage	10-30 V
Features	TOF (Time of Flight)

Accessories



E39-L201

L-shaped mounting bracket for E3AS-F/L cable and pigtail models.



E39-L202

Horizontal protective cover bracket for E3AS-F/L cable and pigtail models.



E39-L203

Rear mounting bracket for E3AS-F/L models



E39-L204

Robust mounting bracket for E3AS-F/L cable and pigtail models.

Downloads

CAD Library



**E3AS – Automotive
Brochure**

EN PDF 18.7 MB



**E3AS – Food &
Commodities
Datasheet**

EN PDF 18.1 MB



**E3AS-F
Index list**

EN PDF 235 KB



**E3AS-F
Instruction Sheet**

EN PDF 1.38 MB



**E3AS-Fxxxxxx
IO-Link IODD file**

EN ZIP 1.1 MB



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**IO-Link Series
Brochure**

EN PDF 7.5 MB

