



## R88M-1M40030T-BS2

1S AC servo motor, 400 W, 230 VAC, 3000 rpm, 1.27 Nm, absolute encoder, with brake

# Specifications

Servo control method	EtherCAT
Drive supply voltage	230 V single phase
Rated output	0.4 kW
Rated speed	3000 r/min
Rated torque	1.27 Nm
Peak torque	4.5 Nm
Encoder type	Absolute without battery
Encoder resolution	23 Bit
Motor with brake	✓
Motor with oil seal	✗
Flange size square (LC)	60 mm
Shaft diameter	14 mm
Shaft with key	✓
Shaft with tap	✓
Product Weight (unpacked)	1900 g



## R88D-1SN04H-ECT

1S servo drive, EtherCAT type, 400 W, 1~ 230 VAC

## Accessories



**R88A-CA1A001-5BF-E**

1S series servo brake cable, 1.5 m, 230 V: 100 to 750 W



**R88A-CA1A001-5SF-E**

1S series servo motor power cable, 1.5 m, 230 V: 100 to 750 W



**R88A-CA1A003BF-E**

1S series servo brake cable, 3 m, 230 V: 100 to 750 W



**R88A-CA1A003SF-E**

1S series servo motor power cable, 3 m, 230 V: 100 to 750 W



**R88A-CA1A005BF-E**

1S series servo brake cable, 5 m, 230 V: 100 to 750 W



**R88A-CA1A005SF-E**

1S series servo motor power cable, 5 m, 230 V: 100 to 750 W



**R88A-CA1A010BF-E**

1S series servo brake cable, 10 m, 230 V: 100 to 750 W



**R88A-CA1A010SF-E**

1S series servo motor power cable, 10 m, 230 V: 100 to 750 W



**R88A-CA1A015BF-E**

1S series servo brake cable, 15 m, 230 V: 100 to 750 W



**R88A-CA1A015SF-E**

1S series servo motor power cable, 15 m, 230 V: 100 to 750 W



**R88A-CA1A020BF-E**

1S series servo brake cable, 20 m, 230 V: 100 to 750 W



**R88A-CA1A020SF-E**

1S series servo motor power cable, 20 m, 230 V: 100 to 750 W



**R88A-CR1A001-5CF-E**

1S series servo encoder cable, 1.5m, 230V: 50-750W



**R88A-CR1A003CF-E**

1S series servo encoder cable, 3m, 230V: 50-750W



**R88A-CR1A005CF-E**

1S series servo encoder cable, 5m, 230V: 50-750W



**R88A-CR1A010CF-E**

1S series servo encoder cable, 10m, 230V: 50-750W



**R88A-CR1A015CF-E**

1S series servo encoder cable, 15m, 230V: 50-750W



**R88A-CR1A020CF-E**

1S series servo encoder cable, 20m, 230V: 50-750W



**R88A-SC011S-E**

1S series cable clamp A. Used in 230 V drives up to 750 W

## CAD Library



### 1S Series Users Manual

EN PDF 22.5 MB



### 1S Series - Expanded with high capacity range: 4 - 15 kW Flyer

EN PDF 1.64 MB



### 1S Series Incremental Encoder Type Users Manual

EN PDF 6.34 MB



### 1S Series Multi-axis Setup and Tuning Getting Started Guide

EN PDF 7.86 MB



### 1S Servo System Brochure

EN PDF 25.2 MB



### 1S-series Servos Instruction Manual

EN PDF 5.63 MB



### AC Servomotor\_Servo Drives - Replace Guide Replacement guide

EN PDF 4.74 MB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### Motor Sizing Tool Operation Manual

EN PDF 3.83 MB



### R88M-1\_1S-series Servo Motor Datasheet

EN PDF 1.56 MB



### Redundancy and Motion Safety Flyer

EN PDF 960 KB



### Sysmac Catalogue

EN PDF 43.5 MB



### Sysmac: A Fully Integrated Platform Brochure

EN PDF 11.8 MB



### Using R88A-CA1G power cables Technical Information

EN PDF 1.6 MB



### motor\_sizing\_tool\_v1.80.1.16 Configurator

EN ZIP 36.1 MB