

PSEN cable M8-8sf, 5m

533151



Connection cable, PUR, yellow RAL1003, suitable for drag chains, 8-pin, socket straight M8, on open line end, A-coded, cable length: 5m

Technical details

General data

Approval: CE, UKCA, cULus Listed

Technical data

Electrical data

Rated current: 1.5 A

Typ. conductor resistance K1: 140 Ohm/km

Specific contact resistance K1: $\geq 7E+15 \text{ Ohm} \cdot \text{cm}$

Specific conductor capacity K1: 57.5pF/m

Environmental data

Ambient temperature: -40 - 80 °C

Pollution degree clear.&creep.: 3

Mechanical data

Connector type 1: 8-pin M8 female connector

Shape of connector type 1: straight

Matl threaded ring conn 1: GD-Zn, Ni

Contact surfaces material 1: Au

Material of sockets: CuSn

Cable material K1: Cu

Insulation material cable K1: PP cold resistance

Cable type K1: LiF9Y11Y

Length cable:	5 m
Colour cable insulation 1:	Yellow, similar to RAL 1003
Housing colour:	Black
Material of cable insulation 1:	TPU / TPE-U, PUR
Trailing capability of cable 1:	yes
Bend radius (when laying) K1:	5 x Ø
Max. outside diameter cable K1:	5.7 - 5.7 mm
Conductor cross section:	0.14 - 0.14 mm ²
Cable cross section AWG K1:	26
Stranding K1:	8 cores round cotton filler
Shielding K1:	no
Number of conductors:	8
Approvals for cable K1:	UL AWM-Style 20233, UL/CSA
Approvals for connector 1:	UL 94 HB
Halogen-free:	yes
Oil resistance:	resistant
Flame resistance:	CSA FT-2, UL 1581, Cable Flame
Housing material:	PUR
Torque interlocking screw:	0.4 Nm
Net weight:	178 g
Gross weight:	181 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1

CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85444290
UNSPSC 25:	26121603
EAN-Code:	4046548049985
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27060311
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC001855
Volume:	0 dm3