

PSEN ma1.3a-20/PSEN ma1.3-08/8mm/1unit

506220



Magnetic safety switch 3 n/o, round M12 design, IP67, operating distance 8 mm, PU = 1 piece with M12 actuator coded, with 5 m cable (PUR).

## Technical details

### General data

Approval:	CE, UKCA, cULus Listed, ECOLAB, EAC (Eurasian), TÜV
Sensor principle:	magnetic
Coding level to ISO 14119:	Low
Classification to EN 60947-5-3:	PDDB
Suitable for series connection:	no
unit type:	Unit

### Technical data

#### Electrical data

Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Switching voltage:	24 V

#### Environmental data

Ambient temperature:	-25 - 70 °C
Climatic suitability standard:	IEC 60068-2-30
Humidity rating:	93 % r. h. at 40 °C
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 60947-5-3
Vibration to standard ...:	EN 60947-5-2
Acc. shock to standard1:	30g

Pollution degree clear.&creep.:	3
<b>Mechanical data</b>	
Type 1 actuator:	PSEN ma1.3-08
Sensor can be flush-mounted:	Ja, Montagehinweis beachten
Connection type:	5 m cable
Cable lines:	LiY11Y 6 x 0.25 mm <sup>2</sup>
Housing material upper part:	PBT
Height dimension:	11 mm
Width dimension:	12 mm
Depth dimension:	59.1 mm
Net weight:	196 g
Gross weight:	205 g
<b>Environment</b>	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
Harmonized System Code:	85365019
UNSPSC 25:	39122205
EAN-Code:	4046548049770
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272402
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002544
Volume:	0 dm <sup>3</sup>

## Optional accessories



540334

PSEN/PDP67 M12-8sm screw terminals

---