












Mechanical safety guard locking device, with radius actuator, interlock principle: Spring force 1500 N, contacts: 1 N/O, 3 N/C, supply voltage 110 - 230 V AC.

Technical details

General data	
Approval:	CE, CCC, BG, cCSAus, EAC (Eurasian)
unit type:	Unit
Technical data	
Electrical data	
Supply voltage (V):	110 - 110 V
Type of supply voltage U1:	AC
Power consumption AC:	8 VA
Supply voltage 2 (V):	230 - 230 V
Type of supply voltage U2:	AC
Relay outputs	
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	230 V
Max. current AC15 safety cont.:	2.5 A
Environmental data	
Ambient temperature:	-25 - 70 °C
Mechanical data	
Holding force:	1500 N
Connection terminal:	Spring-loaded terminal
Height dimension:	184 mm

Width dimension:	42.5 mm
Depth dimension:	51 mm
Net weight:	337 g
Gross weight:	515 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85365080
UNSPSC 25:	39122205
EAN-Code:	4046548065732
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272603
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002593
Volume:	1.330 dm ³

Optional accessories

	380706	PDP67 cable M12-5sm, 10m
	380707	PDP67 cable M12-5sm, 20m
	380705	PDP67 cable M12-5sm, 3m
	380708	PDP67 cable M12-5sm, 30m
	540312	PSEN screw M5x20 10pcs
	773600	PDP67 F 8DI ION
	570101	PSEN me1AS
	570102	PSEN me1AR
	570793	PSEN cable 200m-8x0.25mm ²