

## PSEN me1M / 1AS

570004



Safety gate system with guard locking, with standard actuator, interlocking principle magnetic force, contacts 2 n/o, 2 n/c, supply voltage 24 V AC/DC.

## Technical details

### General data

Approval: CCC, CE, BG, cCSAus, EAC (Eurasian)

unit type: Unit

### Technical data

#### Electrical data

Supply voltage (V): 24 - 24 V

Type of supply voltage U1: AC/DC

Power consumption AC: 4.4 VA

Power consumption DC: 4.4 W

#### Relay outputs

Utilisation cat. AC/DC1 stand.: EN 60947-4-1

Voltage AC1 safety cont.: 240 V

Max. current AC1 safety cont.: 2.5 A

Utilisation cat. AC15/DC13sta.: EN 60947-5-1

Voltage AC15 safety cont.: 230 V

Max. current AC15 safety cont.: 2.5 A

#### Environmental data








Ambient temperature: -25 - 70 °C

#### Mechanical data

Holding force: 1500 N

Connection terminal:	Spring-loaded terminal
Terminal style:	fixed
Height dimension:	184 mm
Width dimension:	42.5 mm
Depth dimension:	51 mm
Net weight:	341 g
Gross weight:	421 g
<b>Environment</b>	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Phenol
%-part of the pollutant:	> 0,1
CAS No.:	84852-15-3
WEEE classification (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
Harmonized System Code:	85365080
UNSPSC 25:	39122205
EAN-Code:	4046548002874
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272603
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002593
Volume:	1.258 dm <sup>3</sup>

## Optional accessories

	380706	PDP67 cable M12-5sm, 10m
	380707	PDP67 cable M12-5sm, 20m
	380705	PDP67 cable M12-5sm, 3m
	540310	PSEN screw M4x16 10pcs
	380708	PDP67 cable M12-5sm, 30m
	570101	PSEN me1AS
	773600	PDP67 F 8DI ION
	570102	PSEN me1AR
	570793	PSEN cable 200m-8x0.25mm <sup>2</sup>