

PSEN rs1.0-300

570300



Rope pull switch incl. E-STOP pushbutton, metal housing, 2xNC+2xNO contacts, 300 N max. spring force.

Technical details

General data

Approval: CE, UKCA, BG, cCSAus, EAC (Eurasian)

Technical data

Relay outputs

Utilisation cat. AC15/DC13sta.: EN 60947-5-1

Voltage AC15 safety cont.: 240 V

Max. current AC15 safety cont.: 3 A

Voltage DC13 safety cont.: 250 V

Environmental data

Ambient temperature: -30 - 80 °C

Mechanical data

Housing material lower section: Aluminium die cast

Housing material upper part: Aluminium die cast

Material actuator: Zn die cast

Connection terminal: Screw terminal

Height dimension: 88 mm

Width dimension: 282 mm

Depth dimension: 90.1 mm

Net weight: 939 g

Gross weight: 1056 g

Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6b, 6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85365080
UNSPSC 25:	39122205
EAN-Code:	4046548062816
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27270607
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002033
Volume:	0 dm3

Optional accessories



380706

PDP67 cable M12-5sm, 10m



380707

PDP67 cable M12-5sm, 20m

	380705	PDP67 cable M12-5sm, 3m
	570314	PSEN rs rope d3/d4 50m
	380708	PDP67 cable M12-5sm, 30m
	570315	PSEN rs rope d3/d4 100m
	570312	PSEN rs pulley 75
	570313	PSEN rs pulley flex
	570310	PSEN rs spring 175
	773600	PDP67 F 8DI ION
	570311	PSEN rs spring 300



570793

PSEN cable 200m-8x0.25mm²
