

1053

PLUG, IN POLYAMIDE PA6, METRIC PITCH, IP54



Features

TECHNICAL INFORMATION


Range of operating temperature (dynamic)	-20 ÷ 90 °C
Range of operating temperature (static)	-40 ÷ 100 °C
Threshold of operating temperature for short periods	110 °C
Ingress Protection	IP54
Markings found	factory mark; thread type
Reference standard	CEI EN 60423
Self-extinguishing fire class according to UL 94	HB

LOGISTIC

Type of packaging	box
-------------------	-----

CERTIFICATIONS

ROHS compliant	Yes
----------------	-----



MATERIAL COMPOSITION AND TREATMENTS

Material	Polyamide 6
Halogen free	No

CLASSIFICATION AND DATA ORDERING

Electrocode	36A
ETIM Class 7	Plug for cable screw gland [EC000032]
Customs code	39269097

1053

tipo	P	Colour	C [mm]	Fixing hole diameter [mm]	Width [mm]	H [mm]	Gross weight [g]
1053M12	M12x1,5	Grey RAL 7035	6	12.2	15	8	0,874
1053M12N	M12x1,5	Black RAL 9005	6	12.2	15	8	0,860
1053M16	M16x1,5	Grey RAL 7035	6	16.2	20	9	1,617
1053M16N	M16x1,5	Black RAL 9005	6	16.2	20	9	1,620
1053M20	M20x1,5	Grey RAL 7035	7	20.5	25	10	2,700
1053M20N	M20x1,5	Black RAL 9005	7	20.5	25	10	2,780
1053M25	M25x1,5	Grey RAL 7035	7	25.4	30	10	3,535
1053M25N	M25x1,5	Black RAL 9005	7	25.4	30	10	3,580
1053M32	M32x1,5	Grey RAL 7035	9	32.5	37	12	5,280
1053M32N	M32x1,5	Black RAL 9005	9	32.5	37	12	5,680
1053M40	M40x1,5	Grey RAL 7035	9	40.5	47	13	8,883
1053M40N	M40x1,5	Black RAL 9005	9	40.5	47	13	9,467
1053M50	M50x1,5	Grey RAL 7035	10	50.5	58	15	14,645
1053M50N	M50x1,5	Black RAL 9005	10	50.5	58	15	15,800
1053M63	M63x1,5	Grey RAL 7035	12	64	72	18	27,000
1053M63N	M63x1,5	Black RAL 9005	12	64	72	18	26,290