


1900 M

MAXIBLOCK CABLE GLAND, IN POLYAMIDE PA6.6, METRIC PITCH, IP68



CERTIFICATIONS & APPROVALS



Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-20 ÷ 90 °C
Range of operating temperature (static)	-40 ÷ 100 °C
Ingress Protection	IP68
Counter nut	No
Dust-proof disc	No
Internal washers	No
EMC	No
Markings found	factory mark; thread type; certification logos
Reference standard	CEI EN 60423; CEI EN 62444
Self-extinguishing fire class according to UL 94	V2

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	Polyamide PA6.6
Inner seal material	Neoprene
Body material	Polyamide PA6.6
Halogen free	No

LOGISTIC


Type of packaging	box
-------------------	-----

CLASSIFICATION AND DATA ORDERING

Electrocode	36A
ETIM Class 7	Cable gland [EC000441]
Customs code	39269097

CERTIFICATIONS

ROHS compliant	Yes
----------------	-----



1900 M

tipo	P	External seal	Colour	Outer seal material	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width [mm]	Gross weight [g]
1900.M12	M12x1,5	No	Grey RAL 7035		2.7	3.5 ÷ 7	15	15	8	18 ÷ 22	12.2	16.5	3,460
1900.M12N	M12x1,5	No	Black RAL 9005		2.7	3.5 ÷ 7	15	15	8	18 ÷ 22	12.2	16.5	3,520
1900.M12G	M12x1,5	No	Dark grey RAL 7001		2.7	3.5 ÷ 7	15	15	8	18 ÷ 22	12.2	16.5	3,480
1900.M16	M16x1,5	No	Grey RAL 7035		5	5 ÷ 10	19	19	8	22 ÷ 27	16.2	21.4	6,620
1900.M16N	M16x1,5	No	Black RAL 9005		5	5 ÷ 10	19	19	8	22 ÷ 27	16.2	21.4	6,580
1900.M16G	M16x1,5	No	Dark grey RAL 7001		5	5 ÷ 10	19	19	8	22 ÷ 27	16.2	21.4	6,520
1900.M20	M20x1,5	No	Grey RAL 7035		7	7 ÷ 13	25	25	9	24 ÷ 30	20.5	25	11,280
1900.M20N	M20x1,5	No	Black RAL 9005		7	7 ÷ 13	25	25	9	24 ÷ 30	20.5	25	11,060
1900.M20G	M20x1,5	No	Dark grey RAL 7001		7	7 ÷ 13	25	25	9	24 ÷ 30	20.5	25	11,220
1900.M25	M25x1,5	No	Grey RAL 7035		7.5	10 ÷ 17	30	30	10	28 ÷ 39	25.4	33	18,560
1900.M25N	M25x1,5	No	Black RAL 9005		7.5	10 ÷ 17	30	30	10	28 ÷ 39	25.4	33	18,120
1900.M25G	M25x1,5	No	Dark grey RAL 7001		7.5	10 ÷ 17	30	30	10	28 ÷ 39	25.4	33	18,200
1900.M32	M32x1,5	Yes	Grey RAL 7035	Neoprene	8	13 ÷ 21	36	36	10	33 ÷ 44	32.5	39.5	29,200
1900.M32N	M32x1,5	Yes	Black RAL 9005	Neoprene	8	13 ÷ 21	36	36	10	33 ÷ 44	32.5	39.5	28,480
1900.M32G	M32x1,5	Yes	Dark grey RAL 7001	Neoprene	8	13 ÷ 21	36	36	10	33 ÷ 44	32.5	39.5	28,000
1900.M40	M40x1,5	Yes	Grey RAL 7035	Neoprene	8	19 ÷ 28	46	46	10	36 ÷ 45	40.5	51	49,867
1900.M40N	M40x1,5	Yes	Black RAL 9005	Neoprene	8	19 ÷ 28	46	46	10	36 ÷ 45	40.5	51	52,500
1900.M40G	M40x1,5	Yes	Dark grey RAL 7001	Neoprene	8	19 ÷ 28	46	46	10	36 ÷ 45	40.5	51	50,000
1900.M50	M50x1,5	Yes	Grey RAL 7035	Neoprene	15	27 ÷ 35	55	55	12	43 ÷ 52	50.5	61	80,000
1900.M50N	M50x1,5	Yes	Black RAL 9005	Neoprene	15	27 ÷ 35	55	55	12	43 ÷ 52	50.5	61	80,800

tipo	P	External seal	Colour	Outer seal material	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width [mm]	Gross weight [g]
1900.M50G	M50x1,5	Yes	Dark grey RAL 7001	Neoprene	15	27 ÷ 35	55	55	12	43 ÷ 52	50.5	61	80,000
1900.M63	M63x1,5	Yes	Grey RAL 7035	Neoprene	15	34 ÷ 45	66	66	12	45 ÷ 55	64	72	117,780
1900.M63N	M63x1,5	Yes	Black RAL 9005	Neoprene	15	34 ÷ 45	66	66	12	45 ÷ 55	64	72	112,000
1900.M63G	M63x1,5	Yes	Dark grey RAL 7001	Neoprene	15	34 ÷ 45	66	66	12	45 ÷ 55	64	72	110,800



Via Serenissima, 9 - 25135
Brescia - ITALY